Save

2" 178-068

Schlumberger

MICROLATEROLOG-MICROLOG

COMPANY EXXON COMPANY USA

RECEIVED
SEP 01 1983
Alaska Oil & Gas Cons. Commission
Anchorage

WELL DUCK ISLAND #1

FIELD WILDCAT

COUNTY NORTH SLOPE STATE ALASKA

COUNTY	NORTH SLOPE
FIELD	WILDCAT
LOCATION	DUCK ISLAND #1
WELL	
COMPANY	EXXON COMPANY USA

LOCATION 200'S. & 800'E.

50-029-29280

API SERIAL NO.	SEC.	TWP	RANGE
	8	11N	17E

Other Services:
LSS HDT
CST CBL DIL
TEMP BHC
FDC/CNL

Permanent Datum: MSL ; Elev.: 0
Log Measured From KB 28 Ft. Above Perm. Datum
Drilling Measured From KB

Elev.: K.B. 28
D.F.
G.L. 6

Date	1/19/79			
Run No.	ONE			
Depth—Driller	12800			
Depth—Logger (Schl.)	12790			
Btm. Log Interval	12788			
Top Log Interval	11392			
Casing—Driller	9⅝ @11403	@	@	@
Casing—Logger	11392			
Bit Size	8½			
Type Fluid in Hole	BENEX			
Dens. / Visc.	9.6 / 50			
pH / Fluid Loss	11.0 / 8.2 ml	ml	ml	ml
Source of Sample	FLOWLINE			
Rm @ Meas. Temp.	2.02@60 °F	@ °F	@ °F	@ °F
Rmf @ Meas. Temp.	2.50@54 °F	@ °F	@ °F	@ °F
Rmc @ Meas. Temp.	3.27@54 °F	@ °F	@ °F	@ °F
Source: Rmf / Rmc	M / M			
Rm @ BHT	.61 @214 °F	@ °F	@ °F	@ °F
TIME Circulation Stopped	1/18 0730			
TIME Logger on Bottom	1/19 0430			
Max. Rec. Temp.	214 °F	°F	°F	°F
Equip. / Location	267 / 4614			
Recorded By	CHAFFEY/LIPPINCOTT			
Witnessed By Mr.	CROWSON ET AL			

FOLD HERE

The well name, location and borehole reference data were furnished by the customer.

RUN NO.	ONE
Service Order No.	75526
Fluid Level	SURFACE
Salinity—PPM Cl	575

EQUIPMENT DATA	
Panel (MPP)	CB 247
Cartridge (MPC)	FB 139
Sonde (MPS)	E 454
Tape Recorder (TTR)	EB 987
Depth Encoder (DRE)	A 189
Pressure Wheel (CPW)	H 992

BOTTOM HOLE TEMPERATURE	
Thermometer #1	°F
Thermometer #2	°F
Thermometer #3	°F

SCALE CHANGES			
Type Log	Depth	Scale Up Hole	Scale Down Hole
4N-MI	12400	0-10	0-50

REMARKS:

All interpretations are opinions based on inferences from electrical or other measurements and we cannot, and do not guarantee the accuracy or correctness of any interpretations, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to Clause 4 of our General Terms and Conditions as set out in our current Price Schedule.

CALIPER DIAM. IN INCHES
6 — 16

DEPTH

RESISTIVITY OHMS. M²/M
MICRO INVERSE 1" X 1"
10 — 0

MICRO NORMAL 2"
10 — 0

RESISTIVITY OHMS. M²/M
MICROLATEROLOG
.2 — 1.0 — 10 — 100 — 1000

11400