2"

Schlumberger

save F

BOREHOLE COMPENSATED SONIC GR

CSU Field Log

COMPANY: SOHIO ALASKA PETROLEUM CO.

WELL: ALASKA ISLAND #1

SOHIO CONFIDENTIAL

FIELD: WILDCAT
BOROUGH: N. SLOPE
STATE: ALASKA

LOCATION: 205'E OF W. LINE & 520'N OF S. LINE

SEC: 11 TWP: 10N RGE: 22E
LATITUDE: 70 13' 47" N
LONGITUDE: 146 29' 58" W

PERMANENT DATUM: MSL
ELEV. OF PERM. DATUM:
LOG MEASURED FROM: KB
44.0' ABOVE PERM. DATUM
DRLG. MEASURED FROM: KB

ELEVATIONS-
KB: 44.0'
DF: 43.0'
GL: 7.0'

DATE: 12 MAR 1982
RUN NO: 3D

DEPTH-DRILLER: 15090.0'
DEPTH-LOGGER: 15081.0'
BTM. LOG INTERVAL: 15042.0'
TOP LOG INTERVAL: 11682.0'

CASING-DRILLER: 11683'
CASING-LOGGER: 11682'
CASING: 9 5/8
WEIGHT: 53.00 LB/F
BIT SIZE: 8.5
DEPTH: 15090'

RECEIVED
JUL - 7 1982
Alaska Oil & Gas Cons. Commission
Anchorage

OTHER SERVICES-
DIL
FDC/CNL/GR
HDT

API SERIAL NO:
5002920018

PROGRAM
TAPE NO:
20.2
SERVICE
ORDER NO:
117286

TYPE FLUID IN HOLE: GEL/SEAWATER POLYMER
DENSITY: 15.5 LB/G
VISCOSITY: 63.0 S
PH: 10.5
FLUID LOSS: 7.2 C3
SOURCE OF SAMPLE: CIRC.
RM: 3.240 OHMM AT 76.0 DF
RMF: 1.800 OHMM AT 76.0 DF
RMC: 5.510 OHMM AT 76.0 DF
SOURCE RMF/RMC: CIRC./CIRC.
RM AT BHT: 1.351 OHM AT 192. DF
RMF AT BHT: 0.750 OHM AT 192. DF
RMC AT BHT: 2.298 OHM AT 192. DF

TIME CIRC. STOPPED: 1600
TIME LOGGER ON BTM.: 0130

MAX. REC. TEMP: 192.0 DF

LOGGING UNIT NO: 7910
LOGGING UNIT LOC: 4614
RECORDED BY: LIERHAUS
WITNESSED BY: KONRAD/WOLFE

REMARKS:

3" HOLEFINDER AND 2" STANDOFFS USED
TOOLS RUN IN COMBINATION
LOG TIED INTO PREVIOUS RUN