






Derives outlines from U.S. Geological Survey T-1000 Series R-2, R-3, R-4, 1984.
 U.S.G.S. G-3-C, 1:50,000, Quadrangle Alaska



DESCRIPTIVE NOTES
 The geophysical data were acquired with a DIGHEM[®] Electromagnetic (EM) system, a Scintrex cesium CS2 magnetometer, and a Herz VLF system installed in an AS350B-1 Squirrel helicopter. In addition, the survey recorded data from a radar altimeter, GPS navigation system, 50/60 Hz monitors and video camera. Flights were performed at a mean terrain clearance of 200 feet along survey flight lines with a spacing of a quarter of a mile. The lines were flown perpendicular to the flight lines at intervals of approximately 3 miles.
 A Serial Real-Time Differential Global Positioning System (RT-DGPS) was used for both navigation and flight path recovery. The helicopter position was derived every 0.5 seconds using real-time differential positioning to a relative accuracy of better than 10 m. Flight path positions were projected onto the Clarke 1886 (UTM) spheroid, 1927 North American datum using a central meridian (CM) of 152° 0' north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10 m with respect to the UTM grid.

RESISTIVITY
 The DIGHEM[®] EM system measured inphase and quadrature components at five frequencies. Two vertical coplanar coil-pairs operated at 900 and 5000 Hz while three horizontal coplanar coil-pairs operated at 900, 7200 and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system responds to bedrock conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 900 Hz using the pseudo-layer half space model. The data were interpolated onto a regular 100 m grid using a modified Akima (1970) technique.
 Akima, H., 1970. A new method of interpolation and smooth curve fitting based on local procedures. *Journal of the Association of Computing Machinery*, v. 17, no. 4, p.589-602.



**900 Hz COPLANAR APPARENT RESISTIVITY
 OF THE PETERSVILLE MINING DISTRICT,
 ALASKA**
PARTS OF TALKETNA QUADRANGLE
 by
 Laurel E. Burns, Fugro Airborne Surveys Corp., and Stevens Exploration Management Corp.
 2004

SURVEY HISTORY
 The map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys, and Stevens Exploration Management Corp. The map was produced by Fugro Airborne Surveys and supersedes the earlier full color version released by DGG in 1997. Airborne geophysical data for the area were acquired and processed in 1996 under contract between DGG and WGM. Mining and Geological Consultants, Inc. The subcontractor acquiring and processing the data was DIGHEM, a division of CGC Canada Ltd. Other products from this survey are available from DGG, 3354 College Road, Fairbanks, Alaska, 99709-3707.