


Scale: 1:63,360. Scale bars in miles (0 to 4) and kilometers (0 to 5). Contour interval: 100 feet datum near sea level.



DESCRIPTIVE NOTES
 The geophysical data were acquired with a RESOLVE Electromagnetic (EM) system and a Scintrex cesium magnetometer. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from a radar altimeter, GPS navigation system, 50/60 Hz monitors and video camera. Flights were performed using AS350B-2 and AS350B-3 Squirrel helicopters at a mean terrain clearance of 200 feet along N45°E (300') survey flight lines with a spacing of a quarter of a mile. The lines were flown perpendicular to the flight lines at intervals of approximately 3 miles.
 An Ashtech G24 NAVSTAR / GLONASS Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a relative accuracy of better than 5 m. Flight path positions were projected onto the Clarke 1866 (UTM zone 7) spheroid, 1927 North American datum using a central meridian (CM) of 141°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10 m, with respect to the UTM grid.

TOTAL MAGNETIC FIELD OF THE ALASKA HIGHWAY CORRIDOR, EAST-CENTRAL ALASKA

PARTS OF NABESNA and TANACROSS QUADRANGLES


by
 Laurel E. Burns, Fugro Airborne Surveys Corp., and Stevens Exploration Management Corp.
 2006

TOTAL MAGNETIC FIELD

The magnetic total field contours were produced using digitally recorded data from a Scintrex cesium CS2 magnetometer, with a sampling interval of 0.1 seconds. The magnetic data were (1) corrected for diurnal variations by subtraction of the digitally recorded base station magnetic data, (2) adjusted for regional variations (or IGRF gradient, 2005, updated to November 2005) using altimeter adjusted IGRF, (3) leveled to the tie line data, and (4) interpolated onto a regular 80 m grid using a modified Akima (1970) technique.
 Akima, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures, Journal of the Association of Computing Machinery, v. 17, no. 4, p. 589-602.

COLOR BAR HISTOGRAM

Approximately 98% of the entire Alaska Highway Corridor aeromagnetic data lie within the range displayed on the color bar, data values actually range from 56106 nT (dark blue) to about 60189 nT (magenta). Actual values can be seen on digital publication DPR 2006-6.



SURVEY HISTORY
 This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGG&S), and Stevens Exploration Management Corp. Airborne geophysical data for the new area were acquired and processed by Fugro Airborne Surveys Corp. in late 2005 and early 2006.
 This map and other products from this survey are available by mail order or in person from DGG&S, 3354 College Road, Fairbanks, Alaska 99709-3707. Published maps are also available for viewing or downloading as Adobe Acrobat Files (*.pdf) on our Web site (<http://www.dgg&s.dnr.state.ak.us/pubs/>).