Compressibility test data for the following seven NPRA wells:

Husky Oil NPR Oper. Inc. (U.S.G.S.)	Inigok Test Well No. 1
Husky Oil NPR Oper. Inc. (U.S.G.S.)	Ikpikpuk Test Well No. 1
U.S. Navy	South Barrow Test Well No. 1
U.S. Navy	South Barrow No. 2
U.S. Navy	South Barrow No. 3
Husky Oil NPR Oper. Inc. (U.S.G.S.)	Peard Test Well No. 1
U.S. Navy	Point Barrow Core Test No. 1

Received 14 June 1988

Total of 2 pages in report

TABLE P-45

Husky NPR #1 Inigok Test Well 2632.0 ft

Confining Pressure (psig)	Porosity (%)	Percent Ambient Porosity (%)	Pore Volume Compressibility (vol/vol/psi)
0	12.6	100.0	
250	12.3	97.2	1.3E-04
500	12.0	95.0	1.1E-04
1000	11.8	93.5	3.5E-05
1500	11.7	92.6	2.2E-05
2000	11.6	91.8	2.1E-05
3000	11.4	90.3	1.8E-05
4000	11.3	89.4	1.2E-05
5000	11.2	88.6	1.0E-05
6000	11.1	87.9	7.8E-06
7000	11.0	87.4	7.2E-06

Husky NPR #1 Inigok Test Well 2655.9 ft

Confining Pressure (psig)	Porosity (%)	Percent Ambient Porosity (%)	Pore Volume Compressibility (vol/vol/psi)
0	19.2	100.0	
250	18.9	98.2	9.0E-05
500	18.6	96.7	7.3E-05
1000	18.5	96.3	1.2E-05
1500	18.4	95.9	1.0E-05
2000	18.4	95.7	5.5E-06
3000	18.3	95.2	5.5E-06
4000	18.2	94.9	5.1E-06
5000	18.2	94.5	4.8E-06
6000	18.1	94.1	5.2E-06
7000	18.0	93.7	4.4E-06

Husky NPR #1 Inigok Test Well 3081 ft

Confining Pressure (psig)	Porosity (%)	Percent Ambient Porosity (%)	Pore Volume Compressibility (vol/vol/psi)
0	20.3	100.0	
250	20.2	99.2	3.9E-05
500	20.0	98.6	3.3E-05
1000	19.9	97.8	1.9E-05
1500	19.8	97.2	1.5E-05
2000	19.7	96.9	9.7E-06
3000	19.6	96.3	7.2E-06
4000	19.5	95.9	5.6E-06
5000	19.4	95.5	5.3E-06
6000	19.3	95.1	5.0E-06
7000	19.3	94.8	3.7E-06

Husky NPR #1 Inigok Test Well 8851 ft

Confining Pressure (psig)	Porosity (%)	Percent Ambient Porosity (%)	Pore Volume Compressibility (vol/vol/psi)
0	7.9	100.0	
250	7.6	96.9	1.4E-04
500	7.4	94.3	1.2E-04
1000	7.3	93.0	3.1E-05
1500	7.3	92.5	1.2E-05
2000	7.2	92.0	1.1E-05
3000	7.2	91.3	8.9E-06
4000	7.1	90.6	8.0E-06
5000	7.1	90.0	6.3E-06
6000	7.1	89.6	5.4E-06
7000	7.0	89.1	5.5E-06

Husky NPR #1 Ikpikpuk Test Well 7141.2 ft

Confining Pressure (psig)	Porosity (%)	Percent Ambient Porosity (%)	Pore Volume Compressibility (vol/vol/psi)
0	12.9	100.0	
250	12.6	97.9	9.9E-05
500	12.4	96.1	8.2E-05
1000	12.3	95.5	1.6E-05
1500	12.2	94.9	1.2E-05
2000	12.1	94.5	1.1E-05
3000	12.1	93.9	7.4E-06
4000	12.0	93.4	5.8E-06
5000	11.9	92.9	5.8E-06
6000	11.9	92.6	3.5E-06
7000	11.9	92.4	2.9E-06

U.S. Navy #1 S. Barrow Test Well 1912.6 ft

Confining Pressure (psig)	Porosity (%)	Percent Ambient Porosity (%)	Pore Volume Compressibility (vol/vol/psi)
0	28.5	100.0	
250	28.0	98.3	9.8E-05
500	27.6	96.8	8.1E-05
1000	27.1	95.1	5.0E-05
1500	26.8	94.3	2.3E-05
2000	26.7	93.8	1.6E-05
3000	26.4	92.9	1.3E-05
4000	26.2	92.2	9.5E-06
5000	26.2	91.9	3.9E-06
6000	26.1	91.7	3.9E-06
7000	26.0	91.4	3.4E-06

TABLE P-45
CONT.

U.S. Navy #2 S. Barrow Test Well 1763 ft

Confining Pressure (psig)	Porosity (%)	Percent Ambient Porosity (%)	Pore Volume Compressibility (vol/vol/psi)
0	18.1	100.0	
250	17.8	98.5	7.3E-05
500	17.6	97.3	6.0E-05
1000	17.4	96.1	3.0E-05
1500	17.2	95.3	2.1E-05
2000	17.1	94.7	1.5E-05
3000	16.9	93.8	1.1E-05
4000	16.8	93.2	8.3E-06
5000	16.7	92.6	8.0E-06
6000	16.6	92.0	6.8E-06
7000	16.5	91.6	6.4E-06

U.S. Navy #3 S. Barrow Test Well 225.5 ft

Confining Pressure (psig)	Porosity (%)	Percent Ambient Porosity (%)	Pore Volume Compressibility (vol/vol/psi)
0	28.9	100.0	
250	28.6	99.0	5.7E-05
500	28.4	98.2	4.7E-05
1000	28.1	97.3	2.6E-05
1500	28.0	96.8	1.4E-05
2000	27.9	96.3	1.2E-05
3000	27.7	95.8	7.8E-06
4000	27.6	95.3	7.5E-06
5000	27.4	94.8	6.8E-06
6000	27.3	94.4	5.6E-06
7000	27.2	94.0	5.6E-06

Husky NPR #1 Peard Test Well 3052.1 ft

Confining Pressure (psig)	Porosity (%)	Percent Ambient Porosity (%)	Pore Volume Compressibility (vol/vol/psi)
0	15.3	100.0	
250	15.0	98.6	6.8E-05
500	14.9	97.4	5.6E-05
1000	14.7	96.6	2.0E-05
1500	14.6	95.9	1.7E-05
2000	14.5	95.4	1.2E-05
3000	14.4	94.7	8.0E-06
4000	14.4	94.1	7.6E-06
5000	14.3	93.7	4.9E-06
6000	14.2	93.4	4.1E-06
7000	14.2	93.1	3.6E-06

Husky NPR #1 Peard Test Well 5416.8 ft

Confining Pressure (psig)	Porosity (%)	Percent Ambient Porosity (%)	Pore Volume Compressibility (vol/vol/psi)
0	12.7	100.0	
250	12.6	98.6	6.4E-05
500	12.4	97.5	5.3E-05
1000	12.3	96.3	2.7E-05
1500	12.2	95.6	1.6E-05
2000	12.1	95.0	1.4E-05
3000	12.0	94.2	9.8E-06
4000	11.9	93.7	6.7E-06
5000	11.9	93.2	5.7E-06
6000	11.8	92.8	5.2E-06
7000	11.8	92.4	4.2E-06

U.S. Navy #1 Point Barrow Coretest 179 ft

Confining Pressure (psig)	Porosity (%)	Percent Ambient Porosity (%)	Pore Volume Compressibility (vol/vol/psi)
0	30.2	100.0	
250	29.3	97.2	1.6E-04
500	28.7	95.0	1.3E-04
1000	28.1	93.0	6.0E-05
1500	27.7	91.9	3.3E-05
2000	27.5	91.0	2.7E-05
3000	27.3	90.3	9.8E-06
4000	27.2	90.0	4.6E-06
5000	27.1	89.7	4.6E-06
6000	27.0	89.5	3.0E-06
7000	27.0	89.3	3.0E-06