SOUTHERN DISHNA RIVER ELECTROMAGNETIC AND MAGNETIC AIRBORNE GEOPHYSICAL SURVEY DATA COMPILATION

L.E. Burns, G.R.C Graham, J.D. Barefoot, T.J. Naibert, CGG, and Fugro Airborne Surveys Corp.

Geophysical Report 2018-5

2019
STATE OF ALASKA
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF GEOLOGICAL & GEOPHYSICAL SURVEYS

STATE OF ALASKA

Michael J. Dunleavy, Governor

DEPARTMENT OF NATURAL RESOURCES

Corri A. Feige, Commissioner

DIVISION OF GEOLOGICAL & GEOPHYSICAL SURVEYS

Steve Masterman, State Geologist & Director

Publications produced by the Division of Geological & Geophysical Surveys are available to download from the DGGs website (dgg.alaska.gov). Publications on hard-copy or digital media can be examined or purchased in the Fairbanks office:

Alaska Division of Geological & Geophysical Surveys (DGGs)

3354 College Road | Fairbanks, Alaska 99709-3707

Phone: 907.451.5010 | Fax 907.451.5050

dggspubs@alaska.gov | dgg.alaska.gov

DGGs publications are also available at:

Alaska State Library, Historical
Collections & Talking Book Center
395 Whittier Street
Juneau, Alaska 99801

Alaska Resource Library and
Information Services (ARLIS)
3150 C Street, Suite 100
Anchorage, Alaska 99503

Suggested citation:

Burns, L.E., Graham, G.R.C., Barefoot, J.D., Naibert, T.J., CGG, and Fugro Airborne Surveys Corp., 2019, Southern Dishna River electromagnetic and magnetic airborne geophysical survey data compilation: Alaska Division of Geological & Geophysical Surveys Geophysical Report 2018-5. <http://doi.org/10.14509/29819>

SOUTHERN DISHNA RIVER ELECTROMAGNETIC AND MAGNETIC AIRBORNE GEOPHYSICAL SURVEY DATA COMPILATION

L.E. Burns, G.R.C Graham, J.D. Barefoot, T.J. Naibert, CGG, and Fugro Airborne Surveys Corp.

ABSTRACT

The Southern Dishna River survey is one of several geophysical surveys, collectively known as the Five Spot project (Southern Dishna River, Beaver Creek, and Fox Hills surveys), located in the Iditarod-Innoko and Aniak mining districts, which is about 575 km southwest from Fairbanks, Alaska. Frequency domain electromagnetic and magnetic data were collected with the DIGHEM^V system from September to November 2012. A total of 4546.9 line kilometers were collected covering 1614.9 square kilometers for the Southern Dishna River survey. Line spacing was 400 meters (m). Data were collected 30 m above the ground surface from a helicopter towed sensor platform (“bird”) on a 30 m long line.

PURPOSE

This airborne geophysical survey is part of a program to acquire data on Alaska’s most promising mineral belts and districts. The information acquired is aimed at catalyzing new private-sector exploration, discovery, and ultimate development and production. The purpose of the survey was to map the magnetic and conductive properties of the survey area. The Iditarod-Innoko and Aniak mining districts have a history of placer mining, and the discovery of the Donlin Gold lode deposit, 40 kilometers (25 miles) to the southwest, has kept mining activity in the region high. Other gold and base-metal anomalies, altered zones, favorable lithologies, and structural zones are known to exist throughout the survey area.

SURVEY OVERVIEW DESCRIPTION

This document provides an overview of the survey and includes text and figures of select primary and derivative products of this survey. A table of digital data packages available for download is provided to assist users in data selection. For reference, a catalog of the available maps is presented in reduced resolution. Please consult the metadata, project report, and digital data packages for more information and data.

ACKNOWLEDGMENTS

Funding was provided by the Alaska State Legislature as part of the DGGs Airborne Geophysical/Geological Mineral Inventory (AGGMI) program.

AVAILABLE DATA

Data Type	Provider	Description
ascii_data	contractor	ASCII format line data, other ASCII data
databases_geosoft	contractor	Geosoft format database of final line data, other Geosoft format databases
documents	contractor and DGGS	Project and field reports, survey background information, gridded data explanations, other documentation
grids_ermapper	contractor	Geographically registered gridded data, ER Mapper ERS format
grids_geosoft	contractor and DGGS	Geosoft-format grids, these grids can be viewed in ESRI ArcMap using a free plugin from Geosoft or the free viewer available from Geosoft
images_registered	DGGS	GeoTiff format images of all gridded data
kmz	DGGS	Keyhole markup language (kml) kmz archive files of project data. Viewable in Google Earth and other compatible programs
maps_pdf_format	contractor	Printable maps in pdf format
maps_prn_format	contractor	Printable maps in HPGL/2 printer file format with extension .prn
profiles_stacked	contractor	Distance-based profiles of the digitally recorded geophysical data are generated and plotted at an appropriate scale. The profiles display electromagnetic anomalies with their respective interpretive symbols. Printable in pdf format
vector_data	contractor and DGGS	Line path, data contours, and survey boundary in ESRI shapefile (SHP) format, ESRI Geodatabase format, and/or AutoCAD dxf format
video_flightpath	contractor	Survey flight path downward facing video

REFERENCES

- Akima, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures: Journal of the Association of Computing Machinery, v. 17, n. 4, p. 589–602.
- Burns, L.E., CGG, and Fugro GeoServices, Inc., 2015, Project report, interpretation maps, EM anomalies, stacked multi-channel profiles, and other products of the airborne geophysical survey for the southern Dishna River, Fox Hills, and Beaver Creek survey areas, Iditarod, Ophir, and Holy Cross quadrangles, western Alaska: Alaska Division of Geological & Geophysical Surveys Geophysical Report 2014-3, 126 sheets, 1 DVD. <http://doi.org/10.14509/27326>
- Burns, L.E., Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc., 2013, Southern Dishna River, Fox Hills, and Beaver Creek survey areas: Airborne Magnetic and electromagnetic data in line (point), grid, vector, and map formats, Iditarod, Ophir, and Holy Cross quadrangles, western Alaska: Alaska Division of Geological & Geophysical Surveys Geophysical Report 2013-1, scale 1:63,360, 1 DVD. <http://doi.org/10.14509/26701>

Figure 1. Southern Dishna River electromagnetic and magnetic airborne geophysical survey location shown in western Alaska (inset). Southern Dishna River survey area shown with adjacent DGGs geophysical surveys, landmarks, relevant 1:250,000-scale quadrangle boundaries, mountain ranges, rivers, glaciers, and elevation hillshade.

Figure 3. The magnetic total field data were processed using digitally recorded data from a Fugro D1344 magnetometer with a Scintrex CS3 cesium sensor. Data were collected at a sampling interval of 0.1 seconds. The magnetic data were (1) corrected for diurnal variations by subtracting the digitally recorded base station magnetic data, (2) IGRF corrected (IGRF model 2010, updated for date of flight and altimeter variations), (3) leveled to the tie line data, and (4) interpolated onto a regular 80 m grid using a modified Akima (1970) technique.

Figure 4. The magnetic total field data were processed using digitally recorded data from a Fugro D1344 magnetometer with a Scintrex CS3 cesium sensor. Data were collected at a sampling interval of 0.1 seconds. The magnetic data were (1) corrected for diurnal variations by subtracting the digitally recorded base station magnetic data, (2) IGRF corrected (IGRF model 2010, updated for date of flight and altimeter variations), (3) leveled to the tie line data, (4) a constant value of approximately 55,000 nT was added to all data, and (5) interpolated onto a regular 80 m grid using a modified Akima (1970) technique.

Figure 5. The first vertical derivative grid was calculated from the diurnally-corrected, IGRF-corrected total magnetic field grid using a FFT base frequency domain filtering algorithm. The resulting first vertical derivative grid provides better definition and resolution of near-surface magnetic units and helps to identify weak magnetic features that may not be evident on the total field data.

Figure 6. Analytic signal is the total amplitude of all directions of magnetic gradient calculated from the sum of the squares of the three orthogonal gradients. Mapped highs in the calculated analytic signal of magnetic parameter locate the anomalous source body edges and corners (such as contacts, fault/shear zones, etc.). Analytic signal maxima are located directly over faults and contacts, regardless of structural dip, and independent of the direction of the induced and/or remanent magnetizations.

Figure 7. The tilt derivative is the angle between the horizontal gradient and the total gradient, which is useful for identifying the depth and type of source. The tilt angle is positive over the source, crosses through zero at, or near, the edge of a vertical sided source, and is negative outside the source region. It has the added advantage of responding equally well to shallow and deep sources and is able to resolve deeper sources that may be masked by larger responses from shallower sources.

Figure 8. The DIGHEM[®] EM system measured inphase and quadrature components at five frequencies. Two vertical coaxial coil-pairs operated at 1000 and 5500 Hz while three horizontal coplanar coil-pairs operated at 900, 7,200, and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system responds to bedrock conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 56,000 Hz using the pseudo-layer half space model. The data were interpolated onto a regular 80 m grid using a modified Akima (1970) technique.

Figure 9. The DIGHEM[®] EM system measured inphase and quadrature components at five frequencies. Two vertical coaxial coil-pairs operated at 1000 and 5500 Hz while three horizontal coplanar coil-pairs operated at 900, 7,200, and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system responds to bedrock conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 7,200 Hz using the pseudo-layer half space model. The data were interpolated onto a regular 80 m grid using a modified Akima (1970) technique.

Figure 10. The DIGHEM[®] EM system measured inphase and quadrature components at five frequencies. Two vertical coaxial coil-pairs operated at 1000 and 5500 Hz while three horizontal coplanar coil-pairs operated at 900, 7,200, and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system responds to bedrock conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 900 Hz using the pseudo-layer half space model. The data were interpolated onto a regular 80 m grid using a modified Akima (1970) technique.

Table 1. Copies of the following maps are included at the end of this booklet. The low-resolution, page-size maps included in this booklet are intended to be used as a search tool and are not the final product. Large-scale, full-resolution versions of each map are available to download on this publication's citation page: <http://doi.org/10.14509/29819>.

Map Title	Description
southerndishna_residualmag_topo_map_1of2.pdf	residual magnetic intensity grid with topographic base map
southerndishna_residualmag_topo_map_2of2.pdf	residual magnetic intensity grid with topographic base map
southerndishna_residualmag_contours_plss_map_1of2.pdf	residual magnetic intensity grid with data contours and public land survey system base layer
southerndishna_residualmag_contours_plss_map_2of2.pdf	residual magnetic intensity grid with data contours and public land survey system base layer
southerndishna_analyticsignal_topo_map_1of2.pdf	analytic signal grid with topographic base map
southerndishna_analyticsignal_topo_map_2of2.pdf	analytic signal grid with topographic base map
southerndishna_analyticsignal_contours_plss_map_1of2.pdf	analytic signal grid with data contours and public land survey system base layer
southerndishna_analyticsignal_contours_plss_map_2of2.pdf	analytic signal grid with data contours and public land survey system base layer
southerndishna_calculated1vd_topo_map_1of2.pdf	calculated first vertical derivative of the residual magnetic intensity grid with topographic base map
southerndishna_calculated1vd_topo_map_2of2.pdf	calculated first vertical derivative of the residual magnetic intensity grid with topographic base map
southerndishna_tiltderivative_contours_topo_map_1of2.pdf	magnetic tilt derivative grid with data contours and topographic base map
southerndishna_tiltderivative_contours_topo_map_2of2.pdf	magnetic tilt derivative grid with data contours and topographic base map
southerndishna_residualmag_shaded_tiltderivative_contours_topo_map_1of2.pdf	shaded residual magnetic intensity grid with tilt derivative data contours and topographic base map
southerndishna_residualmag_shaded_tiltderivative_contours_topo_map_2of2.pdf	shaded residual magnetic intensity grid with tilt derivative data contours and topographic base map
southerndishna_res56khz_topo_map_1of2.pdf	56,000 Hz apparent resistivity grid with topographic base map
southerndishna_res56khz_topo_map_2of2.pdf	56,000 Hz apparent resistivity grid with topographic base map
southerndishna_res56khz_contours_plss_map_1of2.pdf	56,000 Hz apparent resistivity grid with data contours and public land survey system base layer
southerndishna_res56khz_contours_plss_map_2of2.pdf	56,000 Hz apparent resistivity grid with data contours and public land survey system base layer

Table 1, continued. Copies of the following maps are included at the end of this booklet. The low-resolution, page-size maps included in this booklet are intended to be used as a search tool and are not the final product. Large-scale, full-resolution versions of each map are available to download on this publication's citation page: <http://doi.org/10.14509/29819>.

Map Title	Description
southerndishna_res7200hz_topo_map_1of2.pdf	7,200 Hz apparent resistivity grid with topographic base map
southerndishna_res7200hz_topo_map_2of2.pdf	7,200 Hz apparent resistivity grid with topographic base map
southerndishna_res7200hz_contours_plss_map_1of2.pdf	7,200 Hz apparent resistivity grid with data contours and public land survey system base layer
southerndishna_res7200hz_contours_plss_map_2of2.pdf	7,200 Hz apparent resistivity grid with data contours and public land survey system base layer
southerndishna_res900hz_topo_map_1of2.pdf	900 Hz apparent resistivity grid with topographic base map
southerndishna_res900hz_topo_map_2of2.pdf	900 Hz apparent resistivity grid with topographic base map
southerndishna_res900hz_contours_plss_map_1of2.pdf	900 Hz apparent resistivity grid with data contours and public land survey system base layer
southerndishna_res900hz_contours_plss_map_2of2.pdf	900 Hz apparent resistivity grid with data contours and public land survey system base layer
southerndishna_emanomalies_residualmag_detailed_topo_map_1of4.pdf	detailed electromagnetic anomalies with residual magnetic intensity grid and topographic base map
southerndishna_emanomalies_residualmag_detailed_topo_map_2of4.pdf	detailed electromagnetic anomalies with residual magnetic intensity grid and topographic base map
southerndishna_emanomalies_residualmag_detailed_topo_map_3of4.pdf	detailed electromagnetic anomalies with residual magnetic intensity grid and topographic base map
southerndishna_emanomalies_residualmag_detailed_topo_map_4of4.pdf	detailed electromagnetic anomalies with residual magnetic intensity grid and topographic base map
southerndishna_interpretation_plss_map_1of2.pdf	interpretation based on the geophysical data with public land survey system base layer
southerndishna_interpretation_plss_map_2of2.pdf	interpretation based on the geophysical data with public land survey system base layer
southerndishna_interpretation_residualmag_plss_map_1of2.pdf	interpretation based on the geophysical data with residualmagnetic intensity grid and public land survey system base layer
southerndishna_interpretation_residualmag_plss_map_2of2.pdf	interpretation based on the geophysical data with residualmagnetic intensity grid and public land survey system base layer

The geophysical data were acquired with a DIGHEM Electromagnetic (EM) system and a Fugro D134-2000 helicopter-mounted magnetometer and a fluxgate sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and a flight log. The flight was performed with an AS-350-B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW-SE (340°) survey flight lines with a spacing of a quarter of a mile. The flight lines were perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds and post-flight differential positioning to a relative accuracy of better than 5m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 1000000 and a scale constant of 0.9996. The accuracy of the presented data is better than 10m with respect to the UTM grid.

[illegible]

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

The magnetic total field data were processed using digitally recorded data from a Fugro D1344 magnetometer with a Schlumberger CS3 cesium sensor. Data were corrected for diurnal variations and magnetic declination. The magnetic data were (1) corrected for diurnal variations by subtraction of the digitally recorded base station magnetic data, (2) IGRF corrected (IGRF model 2010, updated for dates of flight and cesium sensor variations), (3) leveled to the tie line data, and (4) interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Aasma, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures. *Journal of the Association of Computing Machinery*, v. 17, no. 4, p. 589-602.

The geophysical data were acquired with a DIGEM[®] Electromagnetic (EM) system and a Fugro D1344 cesium magnetometer with a Sincro CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet, in addition the survey recorded data from radar and laser altimeters, GPS, inertial navigation system (INS) monitors and video camera. Flights were performed with an AS-350B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW-SE (340°) survey flight lines with a spacing of a quarter of a mile. The lines were perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a relative accuracy of better than 5m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

The magnetic total field data were processed using a digitally recorded data from a Fugro D1 344 magnetic sensor with a sampling interval of 0.2 seconds. The magnetic data were (1) corrected for diurnal variations by subtraction of the digitally recorded base station magnetic data, (2) IGRF corrected (IGRF model 2010, updated for Scope of flight and timing variations), (3) leveled to the tie line data, and (4) interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size grid down to a 25 m cell size to produce the maps and final grids contained in this publication.

Ajima, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures. *Journal of the Association of Computing Machinery*, v. 17, no. 4, p. 589-602.

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

Laurel E. Burns, Fugro Albema Surveys Corp., and Fugro GeoServices, Inc.
2013

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired on the Fugro F2000 platform in 2009, 2010, 2011, 2012, and 2013. Previously flown DGGGS surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of acquisition. The project was funded by the Alaska State Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee of \$100.00. The data are available in the following formats: 99709-3707, and are downloadable for free from the DGGGS website (www.dggs.alaska.gov/pubs). Maps are also available on paper through the DGGGS office, and can be viewed online at the website in Adobe Acrobat PDF file format.

..... 100 nT
 20 nT
 4 nT
 2 nT

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

The geophysical data were acquired with a DIGHAM Electromagnetic (EM) system and a Fugro D1351 cesium magnetometer with a Scintrex C35 cesium fluxgate magnetometer. The EM system was towed in a flow at a height of 100 feet. In addition the system included a Fugro D1351 1000 m depth sounder, GPS navigation system, 50/60 Hz monitors and video camera. Flights were conducted at a mean terrain clearance of 200 feet with a maximum depth of 1000 m. The horizontal spacing of a quarter of a mile, tie lines were spaced every second approximately the flight was 1000 m.

A Novatel OEM4-02 Global Positioning System was used for navigation. The helicopter position was determined by a differential GPS system with a relative accuracy of better than 5 m. Flight path positions were determined by a differential GPS system with a relative accuracy of better than 5 m. The flight path positions were determined by a differential GPS system with a relative accuracy of better than 5 m. The flight path positions were determined by a differential GPS system with a relative accuracy of better than 5 m.

The magnetic total field data were processed using digitally recorded data from a Fugro D1 444 magnetic survey system. Seismic data were collected at a sampling interval of 0.1 seconds. The magnetic data were (1) corrected for diurnal variations by subtraction of the digitally recorded base station magnetic data, (2) IGRF corrected (IGRF model 2010, updated for scale of flight and instrument variations), (3) leveled to the tie line data, and (4) interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Akima, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures: *Journal of the Association of Computing Machinery*, v. 17, no. 4, p. 589-602.

This map has been compiled and drawn under contract between the State of Alaska Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro GeoServices, Inc. from 2006 to 2013. Previously flown DGGS surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of acquisition. The project was funded by the Alaska Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in digital format as DVD-ROMs for Alaska residents. DGGS, 3300 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGS website (www.dggs.alaska.gov/pubs/). Maps are also available on paper through the DGGS office, and are available online at the website in Adobe Acrobat PDF file format.

Scale from 1:50,000 to 1:250,000. Scale from 1:50,000 to 1:250,000. Scale from 1:50,000 to 1:250,000.

DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGHEM Electromagnetic (EM) system and a Fugro D1344 cesium magnetometer with a Scintrex CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition to the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and video cameras. Flights were performed with an AC-130B-28 Super Hercules at a mean terrain clearance of 200 feet along the Dishna River (SAR) survey flight line with a spacing of a quarter of a mile. The lines were flown perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 100 feet. The position was projected onto the Clarke 1886 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

ANALYTIC SIGNAL WITH TOPOGRAPHY OF THE SOUTHERN DISHNA RIVER SURVEY AREA, WESTERN ALASKA

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Alaska Surveys Corp., and Fugro Geoservices, Inc.
2013

ANALYTIC SIGNAL

Analytic signal is the total amplitude of all directions of magnetic gradient calculated from the sum of the squares of the three orthogonal gradients. Mapped highs in the calculated analytic signal of magnetic parameter locate the anomalous source body edges and corners (e.g., contacts, fault/shear zones, etc.). Analytic signal maxima are located directly over faults and contacts, regardless of structural dip, and independently of the direction of the induced and/or remanent magnetizations.

LOCATION INDEX

SURVEY HISTORY

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through DGG, 3354 College Road, Fairbanks, Alaska, 99703-2701, and are downloadable for free from the DGG website (www.dggsutah.gov/pubs). Maps are also available on paper through the DGG office and are viewable online at the website in Adobe Acrobat PDF file format.

The geophysical data were acquired with a DIGHEMV electromagnetic (EM) system and a Fugro D1344 central magnetic sensor (CMS) mounted on a Fugro 2100 sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and a compass. The EM survey was performed with an AS-350-B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW-SE (340°) survey flight lines with a spacing of a quarter of a mile. The lines were spaced perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a relative accuracy of better than 5m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

Abstract The purpose of this study was to determine the effect of a 12-week, low-intensity, supervised walking program on the physical and psychological health of sedentary, middle-aged women. The study was a randomized, controlled trial. The subjects were 40 sedentary, middle-aged women who were randomly assigned to either a supervised walking program or a control group. The walking program consisted of 12 weeks of supervised walking, 3 times per week, for 30 minutes per session. The control group consisted of 20 women who did not participate in the walking program. The subjects were assessed at baseline and at 12 weeks. The walking program had a significant positive effect on the physical and psychological health of the subjects. The walking program significantly improved the subjects' physical health, as measured by the 6-minute walk test, and their psychological health, as measured by the Beck Depression Inventory and the State-Trait Anxiety Inventory. The walking program also significantly improved the subjects' quality of life, as measured by the SF-36. The walking program was well tolerated and had no adverse effects. The results of this study suggest that a supervised walking program can be an effective intervention for improving the physical and psychological health of sedentary, middle-aged women.

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro Geoservices, Inc.
2013

ANALYTIC SIGNAL

Analytic signal is the total amplitude of all directions of magnetic gradient calculated from the sum of the squares of the three orthogonal gradients. Mapped highs in the calculated analytic signal of magnetic parameter locate the anomalous source body edges and corners (e.g., contacts, fault/shear zones, etc.). Analytic signal maxima are located directly over faults and contacts, regardless of structural dip, and independently of the direction of the induced and/or remanent magnetizations.

The geophysical data were acquired with a DIGHEM Electromagnetic (EM) system and a Fugro D1344-0100 helicopter-mounted magnetometer system (see Fig. 1). The EM and magnetic sensors were flown at a height of 100 feet; in addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60-Hz monitors and barometers. The EM data were performed with an AS-350-B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW–SE (340°) survey flight lines with a spacing of a quarter of a mile. The flight lines were perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a relative accuracy of better than 5m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

Analytic signal is the total amplitude of all directions of magnetic gradient calculated from the sum of the squares of the three orthogonal gradients. Mapped highs in the calculated analytic signal of magnetic parameter locate the anomalous source body edges and corners (e.g., contacts, fault/shear zones, etc.). Analytic signal maxima are located directly over faults and contacts, regardless of structural dip, and independently of the direction of the induced and/or remanent magnetizations.

Analytic signal is the total amplitude of all directions of magnetic gradient calculated from the sum of the squares of the three orthogonal gradients. Mapped highs in the calculated analytic signal of magnetic parameter locate the anomalous source body edges and corners (e.g., contacts, fault/shear zones, etc.). Analytic signal maxima are located directly over faults and contacts, regardless of structural dip, and independently of the direction of the induced and/or remanent magnetizations.

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

This map has been compiled and dropped under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro GeoServices, Inc. in 2012 and 2013. Previously flown DGGS surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of acquisition. The map is part of the Alaska Airborne Geophysical & Geological Mineral Inventory Program.

All data and maps produced to and from this survey are available in digital format on DVD or a formatted hard drive through DGGS, 3554 College Road, Fairbanks, Alaska 99709-3707, and are downloadable for free from the DGGS website (www.dggs.alaska.gov/pub/). Maps are also available on paper through the DGGS office, and can be downloaded online at the Alaska Acrobat PDF file format.

This map has been compiled and dropped under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro GeoServices, Inc. in 2012 and 2013. Previously flown DGGS surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of acquisition. The map is part of the Alaska Airborne Geophysical & Geological Mineral Inventory Program.

All data and maps produced to and from this survey are available in digital format on DVD or a formatted hard drive through DGGS, 3554 College Road, Fairbanks, Alaska 99709-3707, and are downloadable for free from the DGGS website (www.dggs.alaska.gov/pub/). Maps are also available on paper through the DGGS office, and can be downloaded online at the Alaska Acrobat PDF file format.

_____ 0.50 nT/metre
 _____ 0.10 nT/metre
 _____ 0.02 nT/metre
 _____ 0.01 nT/metre

_____ 0.50 nT/metre
 _____ 0.10 nT/metre
 _____ 0.02 nT/metre
 _____ 0.01 nT/metre

The geophysical data were acquired with a DIGHEMY Electromagnetic (EM) system and a Fugro D134-2000 magnetometer. The EM system consisted of a magnetometer. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and a flight log. The flight log was performed with an AS-350-B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW-SE (340°) survey flight lines with a spacing of a quarter of a mile. The line lines were perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a relative accuracy of better than 5m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

Analytic signal is the total amplitude of all directions of magnetic gradient calculated from the sum of the squares of the three orthogonal gradients. Mapped highs in the calculated analytic signal of magnetic parameter locate the anomalous source body edges and corners (e.g., contacts, fault/shear zones, etc.). Analytic signal maxima are located directly over faults and contacts, regardless of structural dip, and independently of the direction of the induced and/or remanent magnetizations.

Analytic signal is the total amplitude of all directions of magnetic gradient calculated from the sum of the squares of the three orthogonal gradients. Mapped highs in the calculated analytic signal of magnetic parameter locate the anomalous source body edges and corners (e.g., contacts, fault/shear zones, etc.). Analytic signal maxima are located directly over faults and contacts, regardless of structural dip, and independently of the direction of the induced and/or remanent magnetizations.

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro GeoServices Corp. in 2012 and 2013. Previously flown DGGS surveys from 1979 to the current survey are shown in the location map by dashed lines, survey name, and date of acquisition. The project is part of the Alaska State Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee of \$100.00. DGGS, 2215 West Northern Avenue, Anchorage, Alaska 99503-3707, and are downloadable for free from the DGGS website (www.dggs.alaska.gov/pubs). Maps are also available on paper through the DGGS office, and are available online at the website in Adobe Acrobat PDF file format.

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro GeoServices Corp. in 2012 and 2013. Previously flown DGGS surveys from 1979 to the current survey are shown in the location map by dashed lines, survey name, and date of acquisition. The project is part of the Alaska Seismicity and Geology Program, authorized by the Alaska Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee of \$100.00. DGGS, 2215 West Northern Avenue, Anchorage, Alaska 99503-3707, and are downloadable for free from the DGGS website (www.dggs.alaska.gov/pubs). Maps are also available on paper through the DGGS office, and are available online at the website in Adobe Acrobat PDF file format.

ANALYTIC SIGNAL CONTROLS

_____		0.50 nT/metre
_____		0.10 nT/metre
_____		0.02 nT/metre
_____		0.01 nT/metre

FIRST VERTICAL DERIVATIVE OF THE MAGNETIC FIELD OF THE SOUTHERN DISHNA RIVER SURVEY AREA, WESTERN ALASKA

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Alabone Surveys Corp., and Fugro Geoservices, Inc.
2013

DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGHEM[®] Electromagnetic (EM) system and a Fugro D1344 cesium magnetometer with a Scintrex CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition to the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and video cameras. Flights were performed with an AC-130B-28 Super Hercules at a mean terrain clearance of 200 feet above the 1927 North American datum using a spacing of a quarter of a mile. The lines were flown perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was determined using a real-time kinematic (RTK) differential positioning to a relative accuracy of better than 5 cm. Flight paths and positions were projected onto the Clarke 1886 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

COLOR BAR HISTOGRAM

Approximately 98% of the first vertical derivative of the magnetic field for the Southern Dishna River Survey Area is within the range displayed on the color bar. Data values actually range from -8.207 nT/m (dark blue) to about 23.313 nT/m (magenta).

FIRST VERTICAL DERIVATIVE OF THE MAGNETIC FIELD

The magnetic total field data were processed using digitally recorded data from a Fugro D1344 magnetometer with a Scintrex CS3 cesium sensor. Data were collected at a sampling interval of 0.1 seconds. The magnetic data were (1) corrected for diurnal variations by subtraction of the digitally recorded base station magnetic data, (2) IIRF corrected (IIRF model 2010, updated for data of flight and altimeter variations), (3) leveled to the tie line data, and (4) interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 20 m cell size to produce the maps and final grids contained in this publication. The first vertical derivative grid was calculated from the processed total magnetic field grid using a FFT base frequency domain filtering algorithm. The resulting first vertical derivative grid provides better definition and resolution of near-surface magnetic units and helps to identify weak magnetic features that may not be evident on the total field data.

Alaska, 1975, A new method of interpolation and smoothing using wavelet analysis, *Journal of the Association of Computing Machinery*, v. 22, no. 4, p. 588-602.

LOCATION INDEX

SURVEY HISTORY

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through DGGIS, 3354 College Road, Fairbanks, Alaska, 99709-3701, and are downloadable for free from the DGGIS website (www.dggis.alaska.gov/pubs). Maps are also available on paper through the DGGIS office, and are viewable online at the website in Adobe Acrobat PDF format.

The geophysical data were acquired with a DIGHEM[®] Electromagnetic (EM) system and a Fugro D1344[®] centrifugal magnetometer. The EM system consists of a sensor, the EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and a compass. The EM data were performed with an AS-350-B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW-SE (340°) survey flight lines with a spacing of a quarter of a mile. The lines were spaced at 1000 ft. The EM data were collected at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a relative accuracy of better than 5m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

Approximately 98% of the first vertical derivative of the magnetic field for the Southern Dishna River Survey Area dataset lie within the range displayed on the color bar. Data values actually range from -8.207 nT/m (dark blue) to about 23.313 nT/m (magenta).

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

The magnetic total field data were processed using digitally recorded data from a Fugro D1344 magnetometer with a Scintrex Cesium central sensor. Data were processed using the following steps:

- (1) The magnetic data were (1) corrected for diurnal variations by subtraction of the digitally recorded base station magnetic data, (2) IGRF corrected (IGRF model 2010) updated for the magnetic declination (magnetic variations), (3) leveled to the tie line data, and (4) interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled to a regular 80 m x 80 m grid to a 25 m x 25 m size cell. The resulting grids are then processed to produce the product. The first vertical derivative grid was calculated from the processed total magnetic field grid using a base station magnetic field.

The resulting first vertical derivative grid provides better definition and resolution of near-surface magnetic units and features. Ideally, the features that are not dependent on the total grid data are the features that are not dependent on the total grid data.

This map has been compiled and drawn under contract by the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGs), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro GeoServices, Inc. in 2012 and 2013. Previously flown DGGs surveys related to the current survey are shown in the location map by dashed lines, survey name, and date of acquisition. The map was prepared for the Alaska Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee of \$100.00. The data are available in the following formats: 99709-3707, and are downloadable for free from the DGGs website (www.dggs.alaska.gov/pub/). Maps are also available on paper through the DGGs office, and online at the website in Adobe Acrobat PDF file format.

The geophysical data were acquired with a DIGEM[®] Electromagnetic (EM) system and a Fugro D1344 cesium magnetometer with a Sincro CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet, in addition the survey recorded data from radar and laser altimeters, GPS, inertial navigation system (INS) monitors and video camera. Flights were performed with an AS-350-B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW-SE (340°) survey flight lines with a spacing of a quarter of a mile. The lines were perpendicular to the flight lines at intervals of approximately 3 miles.

The tilt derivative is the angle between the horizontal gradient & the total gradient, which is useful for identifying the depth & type of source. The tilt angle is positive over the source, crosses through zero at, or near, the edge of a vertical sided source, and is negative outside the source region. It has the added advantage of responding equally well to shallow and deep sources and also to respo deeper sources that may be masked by larger responses from shallower sources.

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

This map has been compiled and drawn under contract from the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGs), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro GeoServices in 2012 and 2013. Previously flown DGGs surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of acquisition. The original data are in the custody of the Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee. The data are available in the following formats: 99709-3707, and are downloadable for free from the DGGs website (www.dggs.alaska.gov/pub/). Maps are also available on paper through the DGGs office, and are available online at the website in Adobe Acrobat PDF file format.

Figure 1 shows a 1D lattice with 10 sites. The sites are numbered 1 to 10 from left to right. The lattice is divided into two halves by a vertical dashed line between sites 5 and 6. The left half (sites 1-5) is labeled 'Left half' and the right half (sites 6-10) is labeled 'Right half'. The sites are connected by horizontal lines representing bonds. The sites are labeled with their corresponding energy levels: site 1 is +45 degrees, site 2 is +30 degrees, site 3 is +15 degrees, site 4 is 0 degrees, site 5 is -15 degrees, site 6 is -30 degrees, site 7 is -45 degrees, site 8 is -60 degrees, site 9 is -75 degrees, and site 10 is -90 degrees. The energy levels are indicated by horizontal lines with dots at the ends, and the corresponding angle values are listed to the right of each line.

File: 2013-1-6B, Magnetic Tilt Derivative C-1, 1000 C-1, 1000
 Date: 2013-1-6B, 1000, 1000, 1000

DESCRIPTIVE NOTES

The geophysical data were acquired with a DigiEMV Dictionmagnetic (DM) system and a Fugro D1344 cesium magnetometer with a Scintrex CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz microphones and video cameras. Flights were performed with an AC-130A-28 square helicopter at a mean terrain clearance of 200 feet above the 1:50,000 (1:50,000) square helicopter at a spacing of a quarter of a mile. Tie lines were flown perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-D2S, Digital Positioning System was used for navigation. The helicopter position was determined every 10 seconds using a real-time differential positioning to a relative accuracy of better than 5m. Flight path and data were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

MAGNETIC TILT DERIVATIVE

The tilt derivative is the angle between the horizontal gradient & the total gradient, which is useful for identifying the depth & type of source. The tilt angle is positive over the source, crosses through zero at, or near, the edge of a vertical sided source, and is negative outside the source region. It has the added advantage of responding equally well to shallow and deep sources and is able to resolve deeper sources that may be masked by larger responses from shallower sources.

MAGNETIC TILT DERIVATIVE WITH TOPOGRAPHY AND DATA CONTOURS OF THE SOUTHERN DISHNA RIVER SURVEY AREA, WESTERN ALASKA

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
 Laurel E. Burns, Fugro Alaboma Surveys Corp., and Fugro GeoServices, Inc.
 2013

LOCATION INDEX

SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGG), and Fugro GeoServices, Inc. All geophysical data for the area were acquired and processed by Fugro Alaboma Surveys Corp. in 2012 and 2013. Previously flown DGGG surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of publication. The project was funded by the Alaska State Legislature as part of the Alaska Alaboma Geophysical and Geological Mineral Inventory Program. All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through DGGG, 3354 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGG website (www.dggg.alaska.gov/pubs). Maps are also available on paper through the DGGG office, and are viewable online at the website in Adobe Acrobat PDF file format.

MAGNETIC TILT DERIVATIVE CONTOURS

Laurel E. Burns, Fugro Albema Surveys Corp., and Fugro GeoServices, Inc.
2013

The magnetic total field data were processed using digitally recorded data from a Fugro D13-4 magnetometer with a Sinter CS3 cesium sensor. Data were collected at a sampling interval of 0.1 seconds. The magnetic data were (1) corrected for diurnal variations, (2) corrected for the digitally recorded base station magnetic data, (2) IGRF corrected (IGRF model 2010, updated for date of flight and altimeter variations), (3) leveled to the tie line data, and (4) projected onto a regular 80 m grid using a modified Adams (1970) least squares method. The data were then from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

The tilt derivative is the angle between the horizontal gradient & the total gradient, which is useful for identifying the depth & type of source. The tilt angle is positive over the source, crosses through zero at, or near, the edge of a vertical sided source, and is negative outside the source region. It has the added advantage of responding equally well to shallow and deep sources and is able to resolve deeper sources that may be masked by larger responses from shallower sources.

.....+45 degrees
.....+30 degrees
.....+15 degrees
..... 0 degrees
.....-15 degrees
.....-30 degrees
.....-45 degrees

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro Airborne Surveys Corp. in 2012 and 2013. Previously flown DGGS surveys adjacent to the current survey are shown in the location of the dashed line. The map is a technical report publication. The project was funded by the Alaska State Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available on the web for use for a nominal fee through DGGS, 3354 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGS website (www.dggs.alaska.gov/pubs). Maps are available in PDF format. The maps and data are viewable online at the website in Adobe Acrobat PDF file format.

Surveying Data: U.S. Geological Survey Mission C-A, 1984, C-A, 1984
U.S. Geological Survey, Alaska

DESCRIPTIVE NOTES

The geophysical data were acquired with a Digimov® Dictionographic (DM) system and a Fugro D1344 cesium magnetometer with a Sinterex CS3 cesium sensor. The DM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz microphones and video cameras. Flights were performed with an AC-130B2 Super Hercules at a mean terrain clearance of 200 feet along 100-ft (3407) survey lines with a spacing of a quarter of a mile. Tie lines were flown perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-D2S, Global Positioning System was used for navigation. The helicopter position was determined by a differential positioning system and served every 100 feet. The position data were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

RESIDUAL MAGNETIC FIELD

The magnetic total field data were processed using digitally recorded data from a Fugro D1344 magnetometer with a Sinterex CS3 cesium sensor. Data were collected at a sampling interval of 0.1 seconds. The magnetic data were (1) corrected for diurnal variations by subtraction of the digitally recorded base station magnetic data, (2) IGR corrected (IGR model 2010, updated for date of flight and altimeter variations), (3) leveled to the tie line data, and (4) interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Alaska, by 1975. A new method of interpretation and smooth curve fitting based on local processing. Journal of the Association of Geophysical Geologists, v. 17, no. 4, p. 181-182.

COLOR SHADOW RESIDUAL MAGNETIC FIELD WITH MAGNETIC TILT DERIVATIVE DATA CONTOURS OF THE SOUTHERN DISHNA RIVER SURVEY AREA, WESTERN ALASKA

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Alaboma Surveys Corp., and Fugro Geoservices, Inc.
2013

Sun Azimuth: 0 degrees
Sun Inclination: 45 degrees

MAGNETIC TILT DERIVATIVE

The tilt derivative is the angle between the horizontal gradient & the total gradient. It is useful for identifying the depth & type of source. The tilt angle is positive over the source, crosses through zero at, or near, the edge of a vertical sided source, and is negative outside the source region. It has the added advantage of responding equally well to shallow and deep sources and is able to resolve deeper sources that may be masked by larger responses from shallower sources.

MAGNETIC TILT DERIVATIVE CONTOURS

LOCATION INDEX

SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGG), and Fugro Geoservices, Inc. Alaboma geophysical data for the area were acquired and processed by Fugro Alaboma Surveys Corp. in 2012 and 2013. Previously flown DGGG surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of publication. The project was funded by the Alaska State Legislature as part of the Alaska Alaboma Geophysical and Geological Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through DGGG, 3354 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGG website (www.dggg.alaska.gov/pub). Maps are also available on paper through the DGGG office, and are viewable online at the website in Adobe Acrobat PDF file format.

Scale from 1:50,000 to 1:250,000. Contour interval 100 feet. Contour lines are labeled with elevation in feet. Contour lines are labeled with elevation in feet.

DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGHEM[®] Electromagnetic (EM) system and a Fugro D1344 cesium magnetometer with a Scintrex CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition to the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and video cameras. Flights were performed with an AC-130B-28 Super Hercules at a mean terrain clearance of 200 feet above the ground (MAG) survey flight with a spacing of a quarter of a mile. The lines were flown perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was determined every 10 seconds using a real-time differential positioning to a relative accuracy of better than 5m. The path positions were projected onto the Clarke 1886 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

SCALE 1:63,360
0 1 2 3 4 MILES
0 1 2 3 4 KILOMETERS
CONTAINING DATA ON 1:50,000 SCALE

56,000 Hz COPLANAR APPARENT RESISTIVITY WITH TOPOGRAPHY OF THE SOUTHERN DISHNA RIVER SURVEY AREA, WESTERN ALASKA

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro Geoservices, Inc.
2013

RESISTIVITY

The DIGHEM[®] EM system measured inphase and quadrature components at five frequencies, two vertical coil-coil pairs operated at 1000 and 5000 Hz with three horizontal coil-coil pairs operated at 300, 7200 and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system response to conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 56,000 Hz using the pseudo-layer half space model. The data were interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Adapted, in part, from a map published by the Alaska Division of Geological & Geophysical Surveys (ADGGS) in 1970. A map published by the Alaska Division of Geological & Geophysical Surveys (ADGGS) in 1970. A map published by the Alaska Division of Geological & Geophysical Surveys (ADGGS) in 1970.

LOCATION INDEX

SURVEY HISTORY

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through ADGGS, 3354 College Road, Fairbanks, Alaska, 99709-2707, and are downloadable for free from the ADGGS website (www.adggs.alaska.gov/pubs). Maps are also available on paper through the ADGGS office, and are viewable online at the website in Adobe Acrobat PDF format.

FIG. 1. 56,000 Hz Coplanar Apparent Resistivity Map of the Southern Dishna River Survey Area, Western Alaska.

DESCRIPTIVE NOTES

The geophysical data were acquired with a Dighem[®] Electromagnetic (EM) system and a Fugro D1344 cesium magnetometer with a Scintrex CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and video cameras. Flights were performed with an AC-130A-2000 helicopter at a mean terrain clearance of 200 feet above the 1:50,000 survey flow lines with a spacing of a quarter of a mile. The lines were flown perpendicular to the right lines at intervals of approximately 3 miles.

A Novatel OEM4-D2L Global Positioning System was used for navigation. The helicopter position and sensor every second using post-flight differential positioning to a relative accuracy of better than 5 m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10 m with respect to the UTM grid.

SCALE 1:63,360
0 1 2 3 4 MILES
0 1 2 3 4 KILOMETERS

56,000 Hz COPLANAR APPARENT RESISTIVITY WITH TOPOGRAPHY OF THE SOUTHERN DISHNA RIVER SURVEY AREA, WESTERN ALASKA

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

RESISTIVITY

The Dighem[®] EM system measured in-phase and quadrature components at five frequencies. Two vertical coplanar coil-pairs operated at 1000 and 5500 Hz while three horizontal coplanar coil-pairs operated at 1000, 7200 and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system responds to bedrock, conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the in-phase and quadrature component of the coplanar 56,000 Hz using the pseudo-layer half space model. The data were interpolated onto a regular 80 m grid using a modified Akima (1972) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Adams, W. 1972. A new method of interpolation and smooth curve fitting based on local procedures. *Journal of the Association of Computing Machinery*, v. 17, no. 3, p. 549-552.

LOCATION INDEX

SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGG), and Fugro GeoServices, Inc. in 2013. Geophysical data for the area were acquired and processed by Fugro Airborne Surveys Corp. in 2011 and 2013. Previously flown DGGG surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of publication. The project was funded by the Alaska State Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program. All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through DGGG, 3354 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGG website (www.dggg.alaska.gov/pubs). Maps are also available on paper through the DGGG office, and are viewable online at the website in Adobe Acrobat PDF file format.

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGHEM Electromagnetic (EM) system and a Fugro D1344-2000 helicopter-mounted magnetometer system (see caption). The EM and magnetic sensors were flown at a height of 100 feet, in addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60-Hz monitors and barometers. The EM data were performed with an AS-350-B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW-SE (340°) survey flight lines with a spacing of a quarter of a mile. The flight lines were perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a relative accuracy of better than 5m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

RESISTIVITY

The DIGHEM[®] EM system measured inphase and quadrature components at two frequencies. Two vertical coaxial coil-pairs operated at 1000 and 5500 Hz while three horizontal coplanar coil-pairs operated at 900, 7200 and 56,000 Hz. EM data were sampled at 0.1 m intervals. EM data were collected from 100 m long conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 56,000 Hz using the partial induction equation (Parker, 1947) and is interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Aldma, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures *Journal of the Association of Computing Machinery*, v. 17, no. 4, p. 589-602.

LOCATION INDEX

RESISTIVITY CONTOURS

SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGs), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro GeoServices, Inc. in 2009 and 2013. Previously flown DGGs surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of publication. The project is funded by the Alaska Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available on the web at www.dggs.alaska.gov for a nominal fee through DGGs, 3504 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGs website (www.dggs.alaska.gov/pubs). Maps are also available on paper through the DGGs website. All maps are available online at the website in Adobe Acrobat PDF file format.

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

The geophysical data were acquired with a DIGHEMY Electromagnetic (EM) system and a Fugro D134 cesium gravimeter. The EM system consisted of a 100-m sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and an Inertial Flight recorder. The survey was performed with an AS-350-B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW-SE (340°) survey flight lines with a spacing of a quarter of a mile. The lines were perpendicular to the strike-slip fault lines at intervals of approximately 3 miles.

The DIGHEMY EM system measured inphase and quadrature components at frequencies. The vertical coaxial coil-pairs operated at 1000 and 5500 Hz, three horizontal coplanar coil-pairs operated at 900, 7200 and 56,000 Hz. EM data were sampled at 0.1 m intervals along the profile. The system used shielded conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 56,000 Hz using the $\rho_a = Z_{xy}/I$ relationship. The data were then interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Aldma, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures *Journal of the Association of Computing Machinery*, v. 17, no. 4, p. 589-602.

Contours in ohm-m at 10 intervals per decade

This map was compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired on several occasions by Fugro GeoServices, Inc. in 2000 and 2013. Previously flown DGGS surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of acquisition. The project is funded by the Alaska Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in digital format as a nominal free download through DGGS, 3554 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGS website (www.dggs.alaska.gov/pubs). Maps are also available on paper through the DGGS office, and are available online at the website in Adobe Acrobat PDF file format.

The geophysical data were acquired with a DIGHEM Electromagnetic (EM) system and a Fugro D1344-2000 helicopter-mounted magnetometer system (see caption). The EM and magnetic sensors were flown at a height of 100 feet, in addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and barometers. The EM data were performed with an AS-350-B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW-SE (340°) survey flight lines with a spacing of a quarter of a mile. The flight lines were perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a relative accuracy of better than 5m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

1000 1000 1000 1000 1000

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

The DIGHEM[®] EM system measured inphase and quadrature components of the frequencies. Ten vertical coil-pairs operated at 1000 and 5500 Hz with three horizontal coplanar coil-pairs operated at 900, 7200 and 56,000 Hz. EM data were sampled at 0.1 m intervals over a 100 m by 100 m area. The conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 7200 Hz using the coplanar coil-pair. The vertical coil-pairs were interpolated onto a regular 80 m grid using a modified Alcala (1970) technique. All grids were then resampled from the 80 m cell size and down to a 25 m cell size to produce the maps and final grids contained in this publication.

Aldin, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures: *Journal of the Association of Computing Machinery*, v. 17, no. 4, p. 589-602.

This map has been compiled and drawn under contract between the State of Alaska Department of Natural Resources, Division of Geological & Geophysical Surveys (DGG&S), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro GeoServices, Inc. in 2002 and 2013. Previously from DGG&S survey adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of acquisition. The project was funded by the Alaska Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee. Phone: 907-255-3350, Fax: 907-255-3359, Email: alaska.dgg@alaska.gov, 99709-3707, and are downloadable for free from the DGG&S website (www.dgg.alaska.gov/pub/). Maps are also available on paper through the DGG&S office, and available online at the website in Adobe Acrobat PDF file format.

DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGHEM[®] Electromagnetic (EM) system and a Fugro D1344 cesium magnetometer with a Sinter CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz magnetic and video cameras. Flights were performed with an AC-130A2 Super Hercules at a mean terrain clearance of 200 feet at a 1000 ft (300 m) survey velocity. The line spacing of a quarter of a mile, tie lines were flown perpendicular to the right lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every second using post-flight differential positioning to a relative accuracy of better than 5 m. Right path points were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10 m with respect to the UTM grid.

SCALE 1:63,360
0 1 2 3 4 MILES
0 1 2 3 4 KILOMETERS
COORD. REF. TO 15.0°

7200 Hz COPLANAR APPARENT RESISTIVITY WITH TOPOGRAPHY OF THE SOUTHERN DISHNA RIVER SURVEY AREA, WESTERN ALASKA

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro Geoservices, Inc.
2013

RESISTIVITY

The DIGHEM[®] EM system measured inphase and quadrature components of five frequencies. Two vertical coiled coil-pairs operated at 1000 and 2000 Hz with three horizontal coplanar coil-pairs operated at 7200, 7200 and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system responds to bedrock, conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 7200 Hz using the pseudo-layer half space model. The data were interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Alaska, N. 1970. A new method of interpolation and smooth curve fitting based on local averaging. *Journal of the Association of Computing Machinery*, v. 17, no. 2, p. 589-602.

LOCATION INDEX

SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGGS), and Fugro Geoservices, Inc. in 2013 and 2014. Previously flown DGGGS surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of publication. The project was funded by the Alaska State Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program. All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through DGGGS, 3354 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGGS website (www.dgggs.alaska.gov/pubs). Maps are also available on paper through the DGGGS office, and are viewable online at the website in Adobe Acrobat PDF file format.

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGEM[®] Electromagnetic (EM) system and a D344 cesium magnetometer with a Sinter CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz microphone and barometer. The EM survey was performed with an AS-350-B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW-SE (340°) survey flight lines with a spacing of a quarter of a mile. The lines were perpendicular to the strike-slip fault at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a relative accuracy of better than 5m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

RESISTIVITY

The DIGHEM[®] EM system measured inphase and quadrature components at frequencies. The vertical coaxial coil-pairs operated at 1000 and 5500 Hz while three horizontal coplanar coil-pairs operated at 900, 7200 and 56,000 Hz. EM data were sampled at 0.1 m intervals over a 100 m by 100 m area. The conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 7200 Hz using the partial induction method (Parker, 1947) and is interpolated onto a regular 80 m grid using a modified Aldin (1970) technique. All grids were then resampled from the 80 m cell size final grids to a 25 m cell size to produce the maps and final grids contained in this publication.

Aldra, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures. *Journal of the Association of Computing Machinery*, v. 17, no. 4, p. 589-602.

LOCATION INDEX

RESISTIVITY CONTOURS

SURVEY HISTORY

This map is being compiled and drawn under contract from the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired by Fugro Airborne Geophysics, Inc. in 2012 and 2013. Previously flown DGGS surveys are adjacent to the current survey are shown in the location of the shaded area. The map is a preliminary publication. The project was funded by the Alaska State Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in electronic format as a nonfinal file through DGGS, 3354 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGS website (www.dggs.alaska.gov/pubs). Maps are available on-line only through the nonfinal PDF file format. The maps are available in Adobe Acrobat PDF file format.

DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGHEM[®] Dictionographic (DM) system and a Fugro D1344 cesium magnetometer with a Scintrex CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from rotor and laser altimeters, GPS navigation system, 50/60 Hz monitors and video cameras. Flights were performed with an aircraft at a constant altitude of a mean terrain clearance of 200 feet (61 m) and a ground speed of 150 knots. The spacing of a quarter of a mile. Tie lines were flown perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-D2S, Global Positioning System was used for navigation. The helicopter position was determined by a relative accuracy of better than 5 m. Flight lines were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10 m with respect to the UTM grid.

RESISTIVITY

The DIGHEM[®] EM system measured inphase and quadrature components at five frequencies. Two vertical coplanar coils operated at 1000 and 5000 Hz while three horizontal coplanar coils operated at 900, 7200 and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system required no battery conductors, conductive overboard, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 7200 Hz using the pseudo-1970 technique. All grids were then resampled into a regular 80 m grid using a modified Adams (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Adams, H., 1970. A new method of interpolation and error maps (flying lines) in total magnetic field of the Association of Geophysical Geologists, v. 17, no. 4, p. 168-169.

7200 Hz COPLANAR APPARENT RESISTIVITY AND DATA CONTOURS OF THE SOUTHERN DISHNA RIVER SURVEY AREA, WESTERN ALASKA

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Alabone Surveys Corp., and Fugro Geoservices, Inc.
2013

RESISTIVITY CONTOURS

LOCATION INDEX

SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGG), and Fugro Alabone Surveys, Inc. The geophysical data for the area were acquired and processed by Fugro Alabone Surveys Corp. in 2011 and 2013. Previously flown DGGG surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of publication. The project was funded by the Alaska State Legislature as part of the Alaska Alabone Geophysical and Geological Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through DGGG, 3354 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGG website (www.dggg.alaska.gov/pubs). Maps are also available on paper through the DGGG office, and are available online at the website in Adobe Acrobat PDF file format.

Scale from U.S. National Survey (NAD 83) to Alaska State Plane (NAD 83) projection. Scale: 1:100,000.

DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGHEM[®] Electromagnetic (EM) system and a Fugro D1344 cesium magnetometer with a Scintrex CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition to the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and video cameras. Flights were performed with an AC-130H-28 Super Hercules at a mean terrain clearance of 200 feet above the ground (MAG) survey flight with a spacing of a quarter of a mile. The lines were flown perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-22L Global Positioning System was used for navigation. The helicopter position was determined every 10 seconds using a real-time differential positioning to a relative accuracy of better than 5m. The path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

900 Hz COPLANAR APPARENT RESISTIVITY WITH TOPOGRAPHY OF THE SOUTHERN DISHNA RIVER SURVEY AREA, WESTERN ALASKA

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro Geoservices, Inc.
2013

RESISTIVITY

The DIGHEM[®] EM system measured inphase and quadrature components at five frequencies: two vertical coil-coil pairs operated at 1000 and 5000 Hz while three horizontal coil-coil pairs operated at 300, 7200 and 56,200 Hz. EM data were sampled at 0.1 second intervals. The EM system response to bedrock, conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 900 Hz using the pseudo-layer half space model. The data were interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Adapted from: 1970, A new method of interpolation and smooth curve fitting based on local procedures. Journal of the Association of Computing Machinery, v. 17, no. 4, p. 161-165.

LOCATION INDEX

SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGG), and Fugro Geoservices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro Airborne Surveys Corp. in 2012 and 2013. Previously flown DGGG surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of publication. The project was funded by the Alaska State Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through DGGG, 3354 College Road, Fairbanks, Alaska, 99709-2707, and are downloadable for free from the DGGG website (www.dggg.alaska.gov/pubs). Maps are also available on paper through the DGGG office, and are viewable online at the website in Adobe Acrobat PDF format.

FIG. 12B. 900 Hz Coplanar Apparent Resistivity with Topography, 2013.

DESCRIPTIVE NOTES

The geophysical data were acquired with a DigiEMV Electromagnetic (EM) system and a Fugro D1344 cesium magnetometer with a Scintrex CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz microphones and video cameras. Flights were performed with an AC-130B aircraft equipped with a mean terrain clearance of 200 feet above the 1:50,000 contour lines with a spacing of a quarter of a mile. Tie lines were flown perpendicular to the right lines at intervals of approximately 3 miles.

A Novatel OEM4-D2S Global Positioning System was used for navigation. The helicopter position and sensor every second using post-flight differential positioning to a relative accuracy of better than 5 m. Right path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10 m with respect to the UTM grid.

SCALE 1:63,360
0 1 2 3 4 MILES
0 1 2 3 4 KILOMETERS

900 Hz COPLANAR APPARENT RESISTIVITY WITH TOPOGRAPHY OF THE SOUTHERN DISHNA RIVER SURVEY AREA, WESTERN ALASKA

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

RESISTIVITY

The DigiEMV EM system measured in-phase and quadrature components of five frequencies. Two vertical coaxial coil-pairs operated at 1000 and 2500 Hz with three horizontal coplanar coil-pairs operated at 900, 7200 and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system responded to bedrock, conductors, conductive overburden, and cultural sources. Apparent resistivity is generated from the in-phase and quadrature component of the coplanar 900 Hz using the pseudo-layer half-space model. The data were interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

AKIMA, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures, *Journal of the Association of Computing Machinery*, v. 17, no. 4, p. 589-602.

LOCATION INDEX

SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGG), and Fugro GeoServices, Inc. in 2013. Geophysical data for the area were acquired and processed by Fugro Airborne Surveys Corp. in 2011 and 2013. Previously flown DGGG surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of publication. The project was funded by the Alaska State Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through DGGG, 3354 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGG website (www.dggg.alaska.gov/pub). Maps are also available on paper through the DGGG office, and are viewable online at the website in Adobe Acrobat PDF file format.

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
Laurel E. Burns, Fugro Airborne Surveys Corp., and Fugro GeoServices, Inc.
2013

DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGHEMY Electromagnetic (EM) system and a Fugro D1344-01 magnetometer mounted on a Cessna 441 aircraft. The sensor, The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and barometers. All FGW surveys were performed with an AS-350-B2 Squirrel helicopter at a mean terrain clearance of 200 feet along NW-SE (340°) survey flight lines with a spacing of approximately a quarter mile. Crosswind direction perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a relative accuracy of better than 5m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10m with respect to the UTM grid.

RESISTIVITY

The DIGHEM[®] EM system measured inphase and quadrature components of the magnetic field. Two vertical coaxial coil-pairs operated at 1000 and 5500 Hz while three horizontal coplanar coil-pairs operated at 900, 7200 and 56,000 Hz. EM data were sampled at 0.1 m intervals. EM data were collected from 100 m long conductors, conductive overden, and cultural sources. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 900 Hz using the standard TEM equations. The data were then linearly interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Aldma, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures *Journal of the Association of Computing Machinery*, v. 17, no. 4, p. 589-602.

LOCATION INDEX

RESISTIVITY CONTOURS

SURVEY HISTORY

This map was compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by Fugro GeoServices, Inc. in 2008 and 2013. Previously flown DGGS surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of acquisition. The project is part of the Alaska Legislature as part of the Alaska Airborne Geophysical and Geological Mineral Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD in a nominal file format: DGGS_XXXXX.Collage, where XXXXX is 99709-3707, and are downloadable for free from the DGGS website (www.dggs.alaska.gov/pubs). Maps are also available on paper through the DGGS office, and can be downloaded online at the Alaska Acrobat PDF file format.

Geophysical Data, U.S. Geological Survey, Alaska Division, Alaska
 U.S. Geological Survey, Alaska Division, Alaska

DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGHEM[®] Dighem[®] (DM) system and a Fugro D1344 cesium magnetometer with a Sinter CS3 cesium sensor. The EM and magnetic sensors were flown at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, GPS navigation system, 50/60 Hz monitors and video cameras. Flights were performed with an aircraft at 500 ft above the ground at a mean terrain clearance of 200 feet (610 m). The survey area was divided into three horizontal coplanar quadrants of 900, 7200 and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system required a 1000 ft line spacing perpendicular to the flight lines at intervals of approximately 3 miles.

A Novatel OEM4-D2S, Global Positioning System was used for navigation. The helicopter position was determined by a real-time kinematic (RTK) differential positioning to a relative accuracy of better than 5 cm. Flight paths and data were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 datum, datum using a central meridian (CM) of 159°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10 m with respect to the UTM grid.

RESISTIVITY

The DIGHEM[®] EM system measured inphase and quadrature components at five frequencies. Two vertical coplanar coils operated at 1000 and 500 Hz while three horizontal coplanar coils operated at 900, 7200 and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system required a 1000 ft line spacing perpendicular to the flight lines at intervals of approximately 3 miles. Apparent resistivity is generated from the inphase and quadrature component of the coplanar 900 Hz using the pseudo-resistivity half space model. The data were interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

Atkinson, H., 1970. A new method of interpolation and error analysis for resistivity data. *Journal of the Association of Geophysical Engineers*, v. 17, no. 4, p. 168-182.

SCALE 1:63,360
 0 1 2 3 4 MILES
 0 1 2 3 4 KILOMETERS

900 Hz COPLANAR APPARENT RESISTIVITY AND DATA CONTOURS OF THE SOUTHERN DISHNA RIVER SURVEY AREA, WESTERN ALASKA

PARTS OF THE OPHIR AND IDITAROD QUADRANGLES

by
 Laurel E. Burns, Fugro Alaboma Surveys Corp., and Fugro Geoservices, Inc.
 2013

RESISTIVITY CONTOURS

Contour interval is 10 ohm-m at 10 intervals per decade
 --- resistivity line

LOCATION INDEX

SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGG), and Fugro Alaboma Surveys, Inc. The geophysical data for the area were acquired and processed by Fugro Alaboma Surveys, Inc. in 2011 and 2013. Previously flown DGGG surveys adjacent to the current survey are shown in the location map by dashed lines, survey name, and date of publication. The project was funded by the Alaska State Legislature as part of the Alaska Alaboma Geophysical and Geological Inventory Program.

All data and maps produced to date from this survey are available in digital format on DVD for a nominal fee through DGGG, 3354 College Road, Fairbanks, Alaska, 99709-3707, and are downloadable for free from the DGGG website (www.dggg.alaska.gov/pubs). Maps are also available on paper through the DGGG office, and are available online at the website in Adobe Acrobat PDF file format.

The geophysical data were acquired with a DSDP/8000 Dacronautics 1300 system. A Flugs 3134-cm diameter magnetometer with a Scintrex CS3 caesium fluxgate magnetometer was mounted on a 100-m steel towed vessel at a height of 100 feet. In addition the survey recorded data from radar and laser altimeters, a north arrow, a compass, a depth gauge, monitors and video camera. Flights were made at a mean terrain clearance of 200 feet at 100 ft/sec. The aircraft was flown at a constant spacing of a quarter of a mile. The three lines were parallel perpendicular to the flight line at 100 ft spacing.

A Novatel OEMA-32 Global Positioning System was used for navigation. The helicopter position relative to the ground was determined by differential positioning to a relative accuracy of better than 5 m. Flight path bearings were determined by a Novatel DG-1000 DGPS receiver, 1977 Irish American datum using a GPS receiver (Garmin 100) with a relative accuracy of 0.0 and an east constant of 500,000. Positional accuracy was better than 10 m. The flight track was better than 10 m with respect to the UTM grid.

Legend:

- Area:** Indicates the occipital lobe area (occipital pole = 0°)
- IP:** IP direction
- Mag:** Magnetic correlation in ST
- Interpretive symbol:**
 - S:** Corneal shield
 - D:** Scleral dark conductor
 - C:** Corneal nerve ("darkened thin sheet")
 - H:** Short corneal nerve unit, short corneal nerve unit, short corneal nerve unit ("darkened thin sheet")
 - L:** Long corneal nerve unit, long corneal nerve unit ("darkened thin sheet")
 - M:** Magnetic field
 - Y:** Magnetic field
- Interpretive symbol:**
 - S:** Corneal shield
 - D:** Scleral dark conductor
 - C:** Corneal nerve ("darkened thin sheet")
 - H:** Short corneal nerve unit, short corneal nerve unit, short corneal nerve unit ("darkened thin sheet")
 - L:** Long corneal nerve unit, long corneal nerve unit ("darkened thin sheet")
 - M:** Magnetic field
 - Y:** Magnetic field

Intensity:

- 100 elements
- 50-100 elements
- 20-50 elements
- 10-20 elements
- 5-10 elements
- 1-5 elements
- < 1 element

Classification:

- Quantitative intensity
- Qualitative intensity
- Culture

**PARTS of EDITAROD D-3, D-4 and
OPHIR A-3, A-4 QUADRANGLES**

by
Laural E. Burns, CEO, and Pagra GasServices, Inc.
2014

To determine the location of EM anomalies or their boundaries, the EM system measures lightning and other components of magnetic fields. Two vertical coaxial-coil pairs operated at 1000 and 5500 Hz and three horizontal coplanar-coil pairs operated at 900, 7500 and 5500 Hz, respectively, are located at 100 m intervals. The EM system responds to bedrock conductive overburden, and cultural sources. The type of conductor is indicated by the characteristic map by the EM system. The EM system also provides information of the type of conductor is based on EM anomaly shapes of the coaxial- and coplanar-coil responses, together with the EM system's ability to discriminate between power line and magnetic field sources. The EM system power line monitor can detect and locate power lines to locate cultural sources.

The magnetic field data were processed using digitally recorded data from a Fugro D1344 magnetometer with a Schlumberger CS3 cesium sensor. Data were collected at a sampling interval of 0.1 seconds. The magnetic data were (1) corrected for diurnal variations by subtraction of the digitally recorded baseline magnetic data, (2) GDF corrected (GDF mode, 2010, updated for date of flight and altimeter variations), (3) leveled to the tie line data, and (4) interpolated onto a regular 80 m grid using a modified Akima (1970) technique. All grids were then resampled from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGG), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by CGO in 2012, 2013, and 2014. Previously flown DGGG surveys adjacent to the current survey are shown in the location map. The map was prepared for publication by the DGGG. The project was funded by the Alaska State Legislature as part of the Alaska Airborne Geological & Geophysical Mineral Inventory Program.

All data and maps produced to date from this survey are available for use by the public for a nominal fee through DGGG, 3354 College Road, Fairbanks, Alaska, 99707-3707, and are downloadable for free from the DGGG website (www.dggg.asg.gov/pubs). Maps are also available for purchase. The DGGG website also has a searchable index of the website in Adobe Acrobat PDF file format.

PARTS of IDITAROD C-4 and D-4 QUADRANGLES

by
 Leonard E. Burns, CEO, and Pagra Consulting, Inc.
 2014

AMERICAN SOCIETY OF MECHANICAL ENGINEERS

DESCRIPTIVE NOTES

The geophysical data were acquired with a D98EM Electromagnetic (EM) system and a Fugro D1344 real-time processing unit. The EM system consists of a sensor, the EM and magnetic sensors were mounted on a survey vessel. The EM system was used to collect survey recorded data from rodder and lower receiver. The data were collected by the EM system monitors and video camera. Flights were performed with an AG-250-B2 Seabird helicopter. The flight path was approximately 10 km long along N65°E, 340°r survey flight lines with a constant altitude of 100 m. The flight lines were flown perpendicular to the flight lines at right angles to the approach direction.

A Novatel EGGA-G2L Global Positioning System was used for navigation. The helicopter position was derived every 30 seconds using post-flight processing. The accuracy of the position was better than 5 m. Flight path positions were determined by the GPS system. The flight path sphere, 1927 North American datum using a WGS84 datum. The flight path was defined as 0° and an east constant of 500,000. Positional error was less than 10 m. The distance was greater than 10 m with respect to the UTM grid.

[illegible]

To determine the location of EM anomalies or their boundaries, the DIHEM[®] EM system measured inphase and quadrature components at five frequencies. Two vertical coil-coupled coils operated at 1000 and 5500 Hz with a 1000 Hz common-mode rejection ratio (CMR) ratio. The 1000 and 5500-Hz EM data were sampled at 0.1 second intervals. The EM system responds to bedrock conductors, conductive overburden, and cultural sources. The type of EM response is determined by the type of conductor. An interpretive symbol attached to each EM anomaly. Determination of the type of conductor is based on EM anomaly shapes of the coil-coupled and coil-coupled coil responses, together with the EM system's depth of penetration and its 1000-Hz power line monitor and the flight track video were examined to locate cultural sources.

The magnetic total field data were processed using digitally recorded data from a Fugro D1344 magnetometer with a Geotek C53 core logger. Data were collected at a sampling interval of 0.1 seconds. The magnetic data were (1) corrected for diurnal variations by subtraction of the digitally recorded base magnetic data, (2) corrected (GSM model) for 2010, updated for date of flight and altimeter verification, (3) leveled to the Sea Line and, (4) interpolated onto a regular 80 m grid using a modified nearest neighbor method. The resulting data were then from the 80 m cell size down to a 25 m cell size to produce the maps and final grids contained in this publication.

This map is being compiled and drawn under contract from the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Survey (DGGS), and Fugro GeoServices, Inc. Airborne geophysical data for the area were acquired and processed by CGG in 2012, 2013, and 2014. Previously flown DGGS surveys adjacent to the current survey are shown in the location indicated on the map. The map is being published as a public data set for the open source publication. The project was funded by the Alaska State Legislature as part of the Alaska Airborne Geological & Geophysical Mineral Inventory Program.

All data and maps produced to date from this survey are available for download from the Alaska Division of Geological & Geophysical Survey through DGGS, 3354 College Road, Fairbanks, Alaska 99709-3707, and are downloadable for free from the DGGS website (www.dggs.alaska.gov/pubs). Most of the data are available in a format that can be viewed in a web browser. The data are available in a format that can be viewed in a web browser. The data are available in a format that can be viewed in a web browser.

ELECTROMAGNETIC ANOMALIES

Conductivity

●	>100 sterms
●	50-100 sterms
●	20-50 sterms
●	10-20 sterms
○	5-10 sterms
○	< 5 sterms
○	Questionable anomaly
△	EM magnetic response

Area

Area indicates the conductor has a thickness >10m

Dip direction

Magnetic correlation

in 80°

A Novatel OEM4-G2L Global Positioning System was used for navigation. The helicopter position was derived every 0.5 seconds using post-flight differential positioning to a relative accuracy of better than 5 m. Flight path positions were projected onto the Clarke 1866 (UTM zone 4) spheroid, 1927 North American datum using a datum conversion (CM) of 15 m. The datum constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10 m with respect to the UTM grid.

PARTS of EDITAROD C-3, C-4, D-3 and D-4 QUADRANGLES

by
Leonard E. Burns, CEO, and Pagra GeoServices, Inc.

2014

ELECTROMAGNETICS

To determine the location of EM anomalies or their boundaries, the DIOHEM[®] EM system measured inphase and quadrature components at five frequencies. Two vertical

coaxial-coil pairs operated at 1000 and 5500 Hz while three horizontal coplanar-coil pairs operated at 900, 7200, and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system responds to bedrock conductors

conductive overburden, and cultural sources. The type of conductor is indicated on the aeromagnetic map by the interpretive symbol attached to each EM anomaly. Determination of the type of conductor is based on the anomaly's

removal of the type of character is based on the unusual shapes of the cockpit- and coplanar-call responses, together with conductor and magnetic patterns and topography. The power line monitor and the flight track video were examined

to locate cultural stories.

RESIDUAL MAGNETIC FIELD

The magnetic total field data were processed using digitally recorded data from a Fugro D1344 magnetometer with a Schlumberger CCI coil system. Data were collected at a sampling interval of 0.1 seconds. The magnetic data were (1) corrected for diurnal variations by subtraction of the digitally recorded base magnetic data, (2) corrected (IGRF magnetic model 2010, updated for effects of night and estimated variations), (3) leveled to the tie line data, and (4) interpolated onto a regular 80 m grid using a modified Akima (1978) routine. All grids are then resampled to a regular 30 m grid size and then resampled to produce the maps and final grids contained in this publication.

Adams, H., 1972, A new method of interpolation and smooth curve fitting based on local procedures, *Journal of the Association of Computing Machinery*, v. 17, no. 4, p. 580-602.

SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys (DGGG) and the U.S. Geological Survey (USGS). The geophysical data for the area were acquired and processed by CGG in 2012, 2013, and 2014. The locations of the former and current surveys are shown in the location map by dashed lines, survey name, and date of acquisition. The project was funded by the Alaska State Legislature in part through the Alaska State Geological & Geophysical Mineral Inventory Program.

All data and maps produced to date from this survey are available to the public through the Alaska State Geospatial Data Center, 3354 College Road, Fairbanks, Alaska 99709-3707, and are downloadable for free from the DGGG website (www.dggg.alaska.gov). More information about the survey and the data is available at the USGS website (www.usgs.gov). The data are available under the Alaska State Geospatial Data Center's Creative Commons Attribution-NonCommercial-ShareAlike license (<http://creativecommons.org/licenses/by-nc-sa/4.0/>).

**INTERPRETATION MAP
OF THE SOUTHERN DISHNA RIVER
SURVEY AREA,
WESTERN ALASKA**

PARTS OF THE OPIK AND SITANOD QUADRANGLES
Interpretation by CGS
2014

The interpretation is based on the geophysical parameters
with reference to geological maps, which were supplied
by the State of Alaska.

LEGEND

F1	Inferred Structural Break
A1	EM Conductor, or group of
EM Conductors
C1	Contact approximately defined
by a change in magnetic feature
M1	Magnetic Zone
ML	Magnetic Low
H1	Highly Conductive Zone