Base from U.S. Geological Survey Talkeetna B-2, B-3, 1954; Quadrangles, Alaska

SCALE 1:31,680

0.5 0 0.5 1 1.5 2 MILES

0.5 0 0.5 1 1.5 2 2.5 KILOMETERS

CONTOUR INTERVAL 100 FEET
DATUM MEAN SEA LEVEL

29° EAST / MAGNETIC / TRUE NORTH

APPROXIMATE MEAN DECLINATION, 1984

TOTAL FIELD MAGNETICS AND DETAILED ELECTROMAGNETIC ANOMALIES OF THE SOUTHEAST PETERSVILLE MINING DISTRICT, ALASKA

1997

IGRF GRADIENT REMOVED

DESCRIPTIVE NOTES

The geophysical data were acquired with a DIGHEM^V Electromagnetic (EM) system, a Scintrex cesium CS2 magnetometer, and a Herz VLF system installed in an AS.350B-1 Squirrel helicopter. In addition, the survey recorded data from a radar altimeter, GPS navigation system, 50/60 Hz monitors and video camera. Flights were performed at a mean terrain clearance of 200 feet along survey flight lines with a spacing of a quarter of a mile. Tie lines were flown perpendicular to the flight lines at intervals of approximately 3 miles.

A Sercel Real-Time Differential Global Positioning System (RT-DGPS) was used for both navigation and flight path recovery. The helicopter position was derived every 0.5 seconds using real-time differential positioning to a relative accuracy of better than 10 m. Flight path positions were projected onto the Clark 1866 (UTM) spheroid, 1927 North American datum using a central meridian (CM) of 153°, a north constant of 0 and an east constant of 500,000. Positional accuracy of the presented data is better than 10 m with respect to the UTM grid.

ELECTROMAGNETIC ANOMALIES

Arcs indicate the conductor has a thickness >10m

Magnetic correlation in nT

Dip direction

Anomaly identifier

Interpretive symbol

Depth is greater than

:	15 m
:	30 m
⋮	45 m
⋮	60 m

Inphase and quadrature of coaxial coil is greater than

.	5 ppm
..	10 ppm
...	15 ppm
....	20 ppm

Anomaly	Conductance
●	>100 siemens
◉	50–100 siemens
⊕	20–50 siemens
⊕	10–20 siemens
⊕	5–10 siemens
○	1–5 siemens
○	<1 siemens
✳	Questionable anomaly
△	EM magnetite response

Interpretive symbol	Conductor ("model")
B	Bedrock conductor
D	Narrow bedrock conductor ("thin dike")
S	Conductive cover ("horizontal thin sheet")
H	Broad conductive rock unit, deep conductive weathering, thick conductive cover ("half space")
E	Edge of broad conductor ("edge of half space")
L	Culture, e.g., power line, metal building or fence

PETERSVILLE SURVEY AREA

ELECTROMAGNETICS

To determine the location of EM anomalies or their boundaries, the DIGHEM^V EM system measured inphase and quadrature components at five frequencies. Two vertical coaxial-coil pairs operated at 900 and 5000 Hz while three horizontal coplanar-coil pairs operated at 900, 7200, and 56,000 Hz. EM data were sampled at 0.1 second intervals. The EM system responds to bedrock conductors, conductive overburden, and cultural sources. The type of conductor is indicated on the peromagnetic map by the interpretive symbol attached to each EM anomaly. Determination of the type of conductor is based on EM anomaly shapes of the coaxial- and coplanar-coil responses, together with conductor and magnetic patterns and topography. The power line monitor and the flight track video were examined to locate cultural sources.

TOTAL FIELD MAGNETICS


The total field magnetic data were acquired with a sampling interval of 0.1 seconds, and were (1) corrected for diurnal variations by subtraction of the digitally recorded base station magnetic data, (2) leveled to the tie line data, and (3) interpolated onto a regular 100 m grid using a modified Akima (1970) technique. The regional variation (or IGRF gradient, 1985, updated to October 1998) was removed from the leveled magnetic data.

Akima, H., 1970, A new method of interpolation and smooth curve fitting based on local procedures: Journal of the Association of Computing Machinery, v. 17, no. 4, p. 589–602.

MAGNETIC CONTOUR INTERVAL

———	100 nT
———	20 nT
———	4 nT
———	2 nT
▼	magnetic low
✱	magnetic high

LOCATION INDEX FOR PDF 97-13 SHEETS A–C



SURVEY HISTORY

This map has been compiled and drawn under contract between the State of Alaska, Department of Natural Resources, Division of Geological & Geophysical Surveys, and WGM Inc., Mining and Geological Consultants. Airborne geophysical data for the area were acquired by DIGHEM, a division of CGG Canada Ltd., in 1996. Other products from this survey are available from the Alaska Division of Geological & Geophysical Surveys, 794 University Ave., Suite 200, Fairbanks, Alaska, 99709.