Overview of Environmental and Hydrogeologic Conditions at Iliamna, Alaska

U.S. GEOLOGICAL SURVEY

Open-File Report 95-346

Prepared in cooperation with the

FEDERAL AVIATION ADMINISTRATION



Overview of Environmental and Hydrogeologic Conditions at Iliamna, Alaska

By James D. Hall

U.S. GEOLOGICAL SURVEY

Open-File Report 95-346

Prepared in cooperation with the

FEDERAL AVIATION ADMINISTRATION



U.S. DEPARTMENT OF THE INTERIOR BRUCE BABBITT, Secretary

U.S. GEOLOGICAL SURVEY Gordon P. Eaton, Director

For additional information write to:

District Chief U.S. Geological Survey 4230 University Drive, Suite 201 Anchorage, AK 99508-4664 Copies of this report may be purchased from:

U.S. Geological Survey
Earth Science Information Center
Open-File Reports Section
Box 25286, MS 517
Federal Center
Denver, CO 80225-0425

CONTENTS

Abstract	1
Introduction	1
Physical setting	1
Location	1
History and socioeconomics	3
Climate	3
Vegetation	4
Geology	4
Bedrock geology	4
Surficial deposits	5
Permafrost	5
Hydrology	6
Surface water	6
Ground water	6
Drinking water sources and water use	7
Summary	8
References cited	8
Appendix 1. Well driller's logs for wells in Iliamna, Alaska	A-1
Appendix 2. Well driller's logs for wells in Newhalen, Alaska	A-2
Appendix 3. Well driller's logs for wells at the Iliamna FAA facility near	
Iliamna, Alaska	A-3
Appendix 4. Water quality analysis reports for wells in Newhalen, Alaska and at the	
Iliamna FAA facility	A-4
FIGURES	
Print Street 24 May 100 10 M. Marrier Street No. 10 May 100 Ma	
1. Map showing the location of Iliamna and Newhalen, Alaska and the Iliamna Federal	
Aviation Administration facility	2
TABLES	
TABLES	
1. Monthly mean and annual temperature, precipitation, and snowfall for the period	
1939 to 1987, Iliamna FAA facility, Alaska	4
2. Mean monthly flow at U.S. Geological Survey stream-gaging station 15300000,	
Newhalen River near Iliamna, Alaska, water years 1952-67 and 1982-86	6
3. Selected water-quality data from two wells at the Iliamna FAA facility and one well	
at a U.S. Public Health Service facility in Newhalen, Alaska	8

CONVERSION FACTORS, VERTICAL DATUM, AND ABBREVIATED WATER-QUALITY UNITS

Ву	To obtain
0.03937	inch
0.3937	inch
3.281	foot
0.6214	mile
0.3861	square mile
35.31	cubic foot per second
91.49	cubic foot per second per square mile
$^{o}F = 1.8 \times ^{o}C + 32$	degree Fahrenheit (°F)
	0.03937 0.3937 3.281 0.6214 0.3861 35.31

Sea level:

In this report "sea level" refers to the National Geodetic Vertical Datum of 1929—a geodetic datum derived from a general adjustment of the first-order level nets of both the United States and Canada, formerly called Sea Level Datum of 1929.

Abbreviated water-quality unit used in this report:

mg/L, milligram per liter μ S/cm, microsiemens per centimeter at 25 degrees Celsius

Overview of Environmental and Hydrogeologic Conditions at Iliamna, Alaska

By James D. Hall

Abstract

The Federal Aviation Administration is conducting preliminary environmental assessments at most of its present or former facilities in Alaska, including Iliamna. The villages of Iliamna, Newhalen, and the Federal Aviation Administration facility in Iliamna, Alaska are near the shore of Alaska's largest fresh-water lake, Iliamna Lake. The climate in this area is transitional from maritime to continental with a mean annual temperature of 1.2 degrees Celsius and a mean annual precipitation of about 675 millimeters. Iliamna Lake is surrounded by a mixed spruce forest growing on deposits of gravel, sand, and silt. These surficial deposits contain ground water and constitute the primary source of drinking water for the area. Alternative sources of drinking water include the Newhalen River and Iliamna and Pike Lakes, as well as numerous other lakes and streams.

INTRODUCTION

The Federal Aviation Administration (FAA) owns and (or) operates airway support and navigational facilities throughout Alaska. At many of these sites, fuels and potentially hazardous materials such as solvents, polychlorinated biphenyls, and pesticides may have been used or disposed of. To determine if environmentally hazardous materials have been spilled or disposed of at the sites, the FAA is conducting environmental studies mandated by the Comprehensive Environmental Response, Compensation, and Liability Act and the Resource Conservation and Recovery Act. To complete these more comprehensive environmental studies, the FAA requires supplementary information on the hydrology and geology of areas surrounding the sites. This report, the product of compilation, review, and summary of existing hydrologic and geologic data by the U.S. Geological Survey (USGS) in cooperation with the FAA, provides this supplementary information and describes general ground-water conditions, flood hazards, and other environmental conditions for the Iliamna FAA facility and nearby areas at Iliamna, Alaska (fig. 1).

PHYSICAL SETTING

Location

Iliamna, Newhalen, and the Iliamna FAA facility are in southwest Alaska near the southern end of the Alaska Range and the northern end of the Aleutian Range (Wahrhaftig, 1965; Selkregg,




Figure 1. Location of Iliamna and Newhalen, Alaska and the Iliamna Federal Aviation Administration facility.

1976). The Iliamna FAA facility lies at an elevation of about 44 m (Detterman and Reed, 1973). The facility is near the southeast shore of Pike Lake and about 4 km northwest of Iliamna Lake, Alaska's largest fresh-water lake. The Iliamna FAA facility is about 4 km north of the village of Newhalen, 4 km west of the village of Iliamna, and about 315 km southwest of Anchorage (fig. 1). Access to the area is typically by air, although small boats and shallow draft barges may reach Iliamna or Newhalen. The Iliamna FAA facility, Iliamna, and Newhalen are connected by a local road system.

History and Socioeconomics

The village of Iliamna was established in 1935 when the Tanaina Athabascans moved their village to this location (Selkregg, 1976). The population grew and by 1980 about 94 people lived in the village (Environmental Services Ltd., 1982). The population leveled off during the 1980's and in 1990 the population was still 94 people (U.S. Census Bureau, 1991). The economy of the Iliamna area is based primarily on commercial and sport fishing, hunting, and tourism. In 1990, 9 percent of the workforce was employed in a transportation-related field, which includes FAA services, and most residents added to their income through subsistence hunting and fishing (Alaska Department of Community and Regional Affairs, 1991).

The village of Newhalen was established in the late 1800's primarily because of the fish and game resources in the immediate area. About 90 people lived in Newhalen in 1990, and the village economy was based on fishing. In the summer, many villagers leave Newhalen to fish commercially as a supplement to their local jobs and to their subsistence lifestyle. Local jobs include regional and city government, education, transportation, and some construction (Environmental Services Ltd., 1982).

The FAA first began acquiring land and buildings near Iliamna and Newhalen in 1941, during the World War II defense buildup in Alaska. The Iliamna FAA facility consists of two maintained runways, a low power non-directional beacon, and additional service support buildings (National Oceanic and Atmospheric Administration, 1993). A detailed description of the Iliamna FAA facility is given in an Environmental Compliance Investigation Report by Ecology and Environment, Inc. (1994).

Climate

The Iliamna area has a climate that is transitional between maritime and continental (Hartman and Johnson, 1984). The region experiences cool summers and moderately cold winters. The mean annual temperature is 1.2°C, but temperatures range from a July mean maximum of 16.9°C and a December mean minimum of -12.9°C (Leslie, 1989). Mean annual precipitation is about 675 mm; about 1,534 mm of snow falls annually (Leslie, 1989). Mean monthly and annual temperature, precipitation, and snowfall are summarized in table 1.

Table 1. Mean monthly and annual temperature, precipitation, and snowfall for the period 1939 to 1987, Iliamna FAA facility, Alaska.

[Modified from Leslie (1989); *C, degree Celsius; mm, millimeter]

	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.	Oct.	Nov.	Dec.	Annual
					Temper	ature (°C	(2)		CHANE				SEPRIE
Mean maximum	-5.2	-4.2	-1.4	3.6	9.9	14.9	16.9	15.9	12.2	4.8	-1.1	-5.7	5.1
Maximum	32.8	(June,	1953)										
Mean minimum	-12.3	-12.3	-10.0	-4.6	1.3	5.7	8.7	8.6	5.1	-1.6	-7.5	-12.9	-2.6
Minimum	-43.9	(Jan.,	1947)										
Mean	-8.7	-8.2	-5.7	-0.6	5.6	10.4	12.8	12.3	8.7	1.6	-4.2	-9.3	1.2
H 42			Pr	ecipitati	on, in m	illimeter	s of moi	sture	1177		W. I E		Total
Messon	35.1	29.0	32.8	29.0	34.5	42.7	71.4	126.0	107.7	78.7	47.8	42.2	676.9
	Will.	3167	17/25	Sr	owfall, i	n millim	eters			No.	Euro s	6.15	Total
	264.2	251.5	274.3	157.5	27.9	0.0	0.0	0.0	0.0	66.0	200.7	297.2	1539.3

Vegetation

Vegetation in the Iliamna area consists mainly of mixed spruce forest and high brush (Detterman and Reed, 1973; Viereck and Little, 1972; Selkregg, 1976). The mixed spruce forest consists of black and white spruce with an understory of shrub tundra and sphagnum (Detterman and Reed, 1973). Open stands of both white and black spruce are present throughout the region (Detterman and Reed, 1973). High brush areas consist of thickets of alders interspersed with willow (Viereck and Little, 1972; Selkregg, 1976). The high brush area understory consists of grasses, fern, herbs, and shrubs (Viereck and Little, 1972; Selkregg, 1976). Aerial photographs of the area around the Iliamna FAA facility at Iliamna indicate that the vegetation is mixed spruce forest to the northwest near Pike Lake and high brush to the north, east, and south.

GEOLOGY

The Iliamna FAA facility is on a lake terrace north of Iliamna Lake, about 30 m above the present lake surface. Bedrock is exposed in nearby river banks and lake shores (Detterman and Reed, 1980). The mountains to the southeast contain numerous faults. There are more than 15 volcanic necks or plugs within 50 km of the Iliamna FAA facility (Detterman and Reed, 1980). Bedrock is overlain primarily by gravel and sand (Detterman and Reed, 1973).

Bedrock Geology

Bedrock near Iliamna was mapped by Detterman and Reed (1980) and consists primarily of volcanic rocks of Tertiary age. Outcrops of basalt, andesite and volcanic breccia are common along stream banks and the shore of Iliamna Lake. To the northeast on Roadhouse Mountain, bedrock consists of about 70 percent volcanic rocks and about 30 percent intrusive igneous rocks. The volcanic rocks of Roadhouse Mountain are composed of tuft interbedded with basalt and andesite

lava flows, whereas the intrusive rocks consist of granodiorite and quartz diorite. Roadhouse Mountain is the remnant of a large volcano which produced the tuffs and lava flows exposed along the north side of Iliamna Lake.

Drillers' logs1 for wells in the area indicate that bedrock is commonly present at depths of less than 10 m (Appendix 1 and 2). In the village of Iliamna, one well drilled to a depth of about 82 m indicated solid rock at a depth of 6 m below the ground surface (Hutchison, 1979a). In Newhalen, a series of wells reached bedrock at depths between 4.5 m and 10 m below the ground surface (Hutchison, 1979b). At the Iliamna FAA facility, well logs indicate that bedrock is 16 m to 18 m below the ground surface (Appendix 3).

Surficial Deposits

The surficial deposits near Iliamna were mapped by Detterman and Reed (1973). Near the Iliamna FAA facility, these deposits consist of lake terrace and beach ridge deposits. Prominent terraces and beach ridges are present at about 12 m, 24 m, 30 m, and 40 m above the 1965 lake elevation. Shallow pits excavated into lake terraces at various points around Iliamna Lake exposed a variety of volcanic ash deposits and beach sediment (Detterman and Reed, 1973). The beach sediment generally consists of layers of dark yellowish quartz sand, silt, and a yellow brown loam that overlie poorly sorted gravel and till.

One driller's log from Iliamna indicates that the surficial deposits are primarily coarse sand to about 2.5 m below the surface and angular bedrock rubble about 6 m below the surface (Hutchison, 1979a). Other logs indicate the presence of gravel overlying bedrock (Appendix 1). In the Newhalen area, surficial deposits are described in well logs (Appendix 2) as primarily clay² deposits intermixed near the surface with gravel, sand, and mud. At the Iliamna FAA facility, well logs indicate that surficial deposits consist of poorly sorted gravel, sand, and clay (Appendix 3).

Permafrost

Permafrost in this area of Alaska is generally found in isolated thin lenses at shallow depth and as relict permafrost at considerable depth below the surface (Ferrians, 1965). In the town of Iliamna, drillers' logs indicate unfrozen ground to a depth of 123 m (Appendix 4). At the Iliamna FAA facility, well logs indicate the absence of permafrost to a depth of 39 m (Appendix 3). Permafrost is generally absent in areas adjacent to or beneath large lakes and rivers (Hopkins and others, 1955). Absence of shallow permafrost at Iliamna is likely because the mean annual temperature is above freezing and Iliamna Lake is nearby.

¹Information garnered from well drillers' logs about geology and hydrology at a well site varies in accuracy depending on the driller. The quality of most of the drillers' logs noted in this report is unknown and drillers' vernacular may not be consistent with terms as they are used by geologists. When possible, logs of wells drilled by the U.S. Geological Survey will be used, as the level of accuracy is consistently good.

²The presence of pure clay in the region is possible but unlikely. Rather, it is probably silt intermixed with some clay-size particles (C. F. Waythomas, U.S. Geological Survey, oral commun., 1995). The permeability of these particles remains undetermined.

HYDROLOGY

Surface Water

Within about 5 km of Iliamna there are more than 50 lakes and ponds. Iliamna Lake is about 380 m deep and its surface is about 14 m above sea level (Detterman and Reed, 1973). The lake is enclosed on its western end by a moraine of late Pleistocene age (Detterman and Reed, 1973). Iliamna Lake is fed by numerous tributary streams, the largest of which is the Newhalen River. Many lakes and streams near the Iliamna FAA facility are used for subsistence fishing and recreation.

The Newhalen River flows about 1.5 km south of the Iliamna FAA facility. It drains an area of about 9,000 km² upstream from the U.S. Geological Survey stream-gaging station 15300000, which lies about 12 km northwest of the Iliamna FAA facility (fig. 1; U.S. Geological Survey, 1988). Mean daily discharge of the Newhalen River near Iliamna was reported from October 1951 to September 1967 and from October 1981 to September 1986. Monthly mean and mean annual discharge for the period of record are summarized in table 2. Monthly mean discharge for the period of record (water years 1952-67 and 82-86) ranged from an August 1967 maximum of 846 m³/s and a February-March 1956 minimum of 28.3 m³/s. The mean annual discharge for the period of record was 262 m³/s.

Table 2. Monthly mean flow at U.S. Geological Survey stream-gaging station 15300000, Newhalen River near Iliamna, Alaska, water years 1952–67 and 1982-86

[Values in cubic meters per second (m3/s)]

	Oct.	Nov.	Dec.	Jan.	Feb.	Mar.	Apr.	May	June	July	Aug.	Sept.
Mean	342	185	112	81.1	62.9	58.5	60.8	126	387	581	604	518
Monthly mean maximum	564	309	181	130	99.9	94.4	92.6	181	559	735	846	720
	(1962)	(1958)	(1958)	(1958)	(1984)	(1984)	(1984)	(1953)	(1964)	(1985)	(1967)	(1961)
Monthly mean minimum	202	96.3	51.0	34.0	28.3	28.3	34.0	69.3	230	455	441	271
	(1985)	(1956)	(1956)	(1956)	(1956)	(1956)	(1960)	(1964)	(1986)	(1954)	(1983)	(1983)

Both Iliamna and Newhalen have a low flood hazard and do not participate in national flood insurance programs (U.S. Army Corps of Engineers, 1993). The town of Iliamna did experience storm-surge flooding in 1969 and 1970; However, there are no records of flooding at Newhalen (U.S. Army Corps of Engineers, 1993). The Iliamna FAA facility is at a higher elevation than either Iliamna or Newhalen and should also have a low flood hazard.

Ground Water

Ground water is found in unconsolidated surficial deposits and in fractured bedrock under Iliamna, Newhalen, and the Iliamna FAA facility. Drillers' logs indicates layers of "clay" or layers of "clay" intermixed with coarser deposits (Appendix 1, 2, and 3; Hutchison, 1979a): However, the data are inadequate to determine if these strata are impermeable enough to separate the surficial deposits into different aquifers. Near Iliamna, sand and gravel deposits about 10 m below the surface contain ground water (Appendix 1; Hutchison, 1979a). Ground water also has been

obtained at a depth of about 30 m in fractured bedrock, at a depth of about 44 m in sand, and at a depth of 61 m to 67 m in fractured bedrock (Appendix 1; Hutchison, 1979a). Near Newhalen, ground water has been obtained in the sand and gravel of the beach deposits around Iliamna Lake (Appendix 2; Hutchison, 1979b) and from fractured bedrock 75 m below the land surface (Appendix 2; Hutchison, 1979b). Two wells at the Iliamna FAA facility obtained ground water at depths of 6 m and 18 m (Appendix 3).

Drinking Water Sources and Water Use

Ground water is the primary source of public-water supplies in Iliamna, Newhalen, and at the Iliamna FAA facility (Appendix 2, 3; Hutchison, 1979a, b). However most residents have private wells which augment or replace the water supplied by the public wells. Surface water is also a readily available source of drinking water. The close proximity of surface-water supplies (such as Iliamna Lake, Pike Lake, and the Newhalen River) to Iliamna, Newhalen, and the Iliamna FAA facility provide alternative sources of drinking water. The data available are inadequate to characterize the quantity or quality of these sources.

In Iliamna, most drinking water is obtained from private wells. Although a public access well is available, there are no public drinking water treatment facilities or distribution systems (Norman L. Fairbanks, U.S. Public Health Service, oral commun., 1995). Treatment of drinking water is done on an individual basis by personal choice rather than by need (Norman L. Fairbanks, U.S. Public Health Service, oral commun., 1995).

In Newhalen, water is distributed from the public-water supply wells to the public facilities, such as the Washeteria, the school, the health clinic, and to the U.S. Department of Health and Human Services, Housing and Urban Development (HUD) housing facilities (Lowdermilk, 1986). However, most residents obtain water from their private wells or individually transport it to their place of residence from Iliamna Lake or the Newhalen River (Norman L. Fairbanks, U. S. Public Health Service, oral commun., 1995). A water-treatment system was installed in 1990 for the fluoridation and chlorination of the HUD housing facilities' water supplies, but it is presently not in use (Norman L. Fairbanks, U.S. Public Health Service, oral commun., 1995).

Water-quality analyses of water from wells in Iliamna (Hutchison, 1979a) and Newhalen (Appendix 4) indicate an iron concentration greater than the U.S. Environmental Protection Agency's Secondary Maximum Contaminant Levels (U.S. Environmental Protection Agency, 1995). The reported concentration of iron in water from wells in Iliamna, in conjunction with a low or high pH and (or) a high specific conductance, will cause corrosion in the well and distribution system. These high iron concentrations can stain plumbing fixtures and affect the taste of the water, but are not hazardous to humans (Appendix 4; Johnson, 1966). In 1958, the U.S. Geological Survey sampled water from two wells at the Iliamna FAA facility. Table 3 shows the reported concentrations of iron and major ions, as well as specific conductance and pH (Appendix 4).

Table 3. Selected water-quality data from wells in Iliamna, Newhalen, and at the Iliamna FAA facility [All data in milligrams per liter, unless indicated; µS/cm, microsiemens per centimeter at 25°Celsius; USPHS, U.S. Public Health Service]

Constituent (or property)	Regulated contaminant levels ^a	Newhalen USPHS well (1982)	Newhalen USPHS well (1984)	Iliamna USPHS well (1979 ^b)	USFAA1 well	USFAA2 well
Sodium (Na)		1.4	15.0	24.0	8.0	2.6
Sulfate (SO ₄)	500 ^c	1.5	4.2	2.0	0.0	3.0
Fluoride (F)	4.0 ^d	<0.1			0.0	0.1
Chloride (Cl)	250e	<1.0	4.0	4.0	5.0	1.5
Iron (dis- solved; Fe)	0.3 ^e	.40	1.1	2.0	.05	0.0
pH (units)	6.5 - 8.5 ^e	5.4	8.4	8.7	5.5	7.0
Specific conductance (µS/cm)		20	95	120	110	62

^aFrom U.S. Environmental Protection Agency, 1995.

SUMMARY

The Iliamna FAA facility is located on a northern lake terrace of Iliamna Lake, Alaska's largest fresh-water lake, near the southern end of the Alaska Range and the northern end of the Aleutian Range. Iliamna has a mean annual temperature of 1.2°C and a mean annual precipitation of about 675 mm. This climate supports mixed spruce forest and high brush vegetation. The surficial geology near the FAA facility is characterized by 16-to-18-m-thick of poorly sorted sediments overlying volcanic rock. Ground water, the primary source of drinking water for the Iliamna FAA facility, is found at depths between 6 and 18 m in both the sand and gravel aquifer and within the fractured bedrock. Abundant local surface-water sources such as Iliamna Lake, Pike Lake, and the Newhalen River represent alternative drinking-water supplies. However, data are inadequate to characterize the quantity or quality of these sources.

REFERENCES CITED

Alaska Department of Community and Regional Affairs, 1991, Iliamna community profile: Municipal and Regional Assistance Division - Community Database, Juneau, Alaska, variously paged.

Detterman, R.L., and Reed, B.L., 1973, Surficial deposits of the Iliamna quadrangle, Alaska:, (Geology of the Iliamna quadrangle, Alaska): U.S. Geological Survey Bulletin 1368-A, 64 p.

^bFrom Hutchinson, 1979a.

^cMaximum Contaminant Level.

^dMaximum Contaminant Level-Under Review.

^eSecondary Maximum Contaminant Level.

- _1980, Stratigraphy, structure, and economic geology of the Iliamna quadrangle, Alaska -- A comprehensive study of Mesozoic to Holocene sedimentary, volcanic, and plutonic rocks of the Iliamna quadrangle (Geology of the Iliamna quadrangle Alaska: U.S. Geological Survey Bulletin 1368-B, 86 p.
- Ecology and Environment, Inc., 1994, Environmental compliance investigation report, Iliamna FAA Station, Iliamna, Alaska: Anchorage, [Copy available through the Environmental Compliance Section AAL-465 Federal Aviation Administration, Alaska Region, variously paged].
- Environmental Services Ltd., 1982, Alaska Peninsula -- Iliamna Lake community profiles: Alaska Department of Community and Regional Affairs, Division of Community Planning, 14 sheets.
- Ferrians, O.J., 1965, Permafrost map of Alaska: U.S. Geological Survey Miscellaneous Geologic Investigations Map I-445, 1 sheet, scale, 1:2,500,000.
- Hartman, C.W., and Johnson, P.R., 1984, Environmental atlas of Alaska: University of Alaska Fairbanks, Institute of Water Resources/Engineering Experiment Station, 95 p.
- Hopkins, D.M., Karlstrom, T.N.V., and others, 1955, Permafrost and ground water in Alaska: U.S. Geological Survey Professional Paper 264-F, 146 p.
- Hutchison, J., 1979a, Water well analysis sanitation facilities construction Iliamna, Alaska: Alaska Area Native Health Service-Environmental Health Branch, Project No. AN-77-625E, variously paged.
- 1979b, Water well analysis sanitation facilities construction Newhalen, Alaska: Alaska Area Native Health Service-Environmental Health Branch, Project No. AN-78-635, variously paged.
- Johnson, E.E., 1966, Ground water and wells: Saint Paul, Minn., Johnson Division, 440 p.
- Leslie, L.D., 1989, Alaska climate summaries (2d ed.): University of Alaska Anchorage, Arctic Environmental Information and Data Center, Alaska Climate Center Technical Note No. 5, variously paged.
- Lowdermilk, 1986, Newhalen, Alaska (aerial photo): U.S. Department of Health and Human Services, Public Health Service, Indian Health Service, Project No. AN-86-347, 1 Sheet.
- Selkregg, L., 1976, Alaska regional profiles--southwest region: University of Alaska, Arctic Environmental Information and Data Center, 313 p.
- U.S. Army Corps of Engineers, 1993, Alaskan communities--Flood hazard data: U.S. Army Corps of Engineers, Alaska District, 335 p.
- U.S. Census Bureau, 1991, Percent distribution Alaska population by sex, race, and Hispanic origin--1990 census: Alaska Department of Labor, Research, and Analysis, 3 p.
- U.S. Environmental Protection Agency, 1995, Drinking water regulations and health advisories: USEPA, May 1995 publication 11 p.
- U.S. Geological Survey, 1988, Water resources data for Alaska, water year 1987: U.S. Geological Survey Water-Data Report AK-87-1, 284 p.
- Viereck, L.A., and Little, E.L., Jr., 1972, Alaska trees and shrubs: U.S. Department of Agriculture, Forest Service, Agriculture Handbook No. 410, 265 p.
- Wahrhaftig, C., 1965, Physiographic divisions of Alaska: U.S. Geological Survey Professional Paper 482, 52 p.

APPENDIX 1 Well drillers logs for wells in Iliamna, Alaska

U.S. DEPT. OF THE INTERIOR

Recorded by Stare 9-10-92 WATER RESOURCES DIVISION Check One X English Metric, Unit	
Transaction To (A) D M A	1 172
GENERAL SITE DATA (0) Site Ident No 5191415128 115141419112 011 RG Number R=0 # Reporting 4- U.S.G.S	
	21.
Site-Type anifector, drain, encurs ainth-connector anatopic, cytores, pand, spring, sunnel, tredl, test anifector, drain, encurs ainth-connector anatopic, cytores, pand, spring, sunnel, tredl, test ion, ; fuole, svoil, ion, ; fuole, svoil, ion anifector, drain, encurs ainth-connector anatopic, cytores, pand, spring, sunnel, tredl, test accourate data	
Freject 5- LK, E, P,E, N, S, L, K Dietrice 5- 0,2 4 State 7- 0,2 County 6- 0,64 5	
Latitude 8= 519 415 2.9 6 Longitude 10= 11.541 4.31/2 4 Accuracy 11= 8 F V M 4	
Local 12- 1510 0 0 5 5 5 5 7 1 2 CA E A I 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	morid .
Map 14= 2,1,1,4,m,N,4, D,-15,	
Altitude 16 - 1 1 7 5 Method of 17 - A L M + Accuracy 18 - 125 *	
Setting 19 = A B C D E F G H K L M Ø P S T U V W + Hydrologic Unit (OWDC) 20 = /1916, 40, 9 Setting after plays street, depres dense, flee, flood hill-sink, events, mangrave, off- podi-hill-serrace, undutating, valley, septend if fan, channel sion, plain, sep, plain,	2/2
Use of 23 = A C D E G H M Ø P R S T U W X Z Secondary Site Use Sit	· 🗆 ·
Use of Us	
Secondary Water Use Tertiary Use 26 = \$ Depth of 27 = , , 2, 5, 10, 1	- d •
Water Level 30 =	
Method of Measurement 34 = A B C E G H L M .N R S T V Z * sirline, analog, calibrated, estimated, pressure, calibrated, geophysical, manameter, mon-roc. reported, steel, electric, calibrated, other sirline gape pressure gape tops 8494. tope tope electric tape	
Site Status 37 = D E F G H I J N Ø P R S T V W X Z . * dry, recently, flowing, eastly, mearly, injector, injecte, injector, i	
Source of Geohydrologic Data Source of Geohydrologic Data Pump Used 35 = * Pump U	8 8 8
OWNER IDENTIFICATION (1) R = 158 T = A D M * Date of 159 0,4/ /, 2/ 1,9/7 *	
add delete modify month day year	· .
Dete of Sea # / / B	
add, delete, modity month day year "	*
OTHER SITE IDENTIFICATION NUMBERS (1)	<u> </u>
Mont 190# 4,2,9, 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	*
R-189 + T- A D M + . 190# B. ed. Roick	*
Now Card Same R & T 190 # 4 0 9 7 7 7 1 1 4 Assigner 191 - 4 Assigner 191	•
190 #	•
SITE VISIT DATA (1)	_
R=186 # T= A D M # Date of 187# / # Person 188= Visit manth day year	⊗*
PERTINENT REMARKS (1)	
R-183 + T-A + 185-	*
New Card Same R&T	*

1.	SETUP 3-31-79 TEAR DOWN 4.	12-79
} —		CASING-
<u> </u>	STRATUM	10-3/2
i .	0-1 GRAVEL FULL	20-3314
U	1-6 ORGANICS	10 - 7/8
		30-45/8
1,	6-18 GREN SANDSTONE	40-55/8
T- :	18-23 HARD SANDSTONE	10-1/2
T.	23-30 SOFT SANDSTONE	50- 6.18 10-18
*:		60-644
<u> </u>	30-33 HARD CLAY	70-148
~_ :	33-40 SOFT SANDSTONE	10-0
		80-73/8
	40-43 FLOWING-SANDSTONE	90-73/4
. . #	43-45 ROCK	10-0
		100 - 73/4
	45-58 FLOWING SANDSTONE + GRAVER	110- 77/6
.~	58-76 SANDSTONE + GRAVEL	10-1
`	76-104 Rock	120-87/8
		130-97/
	104-112 HARD ROCK	140-97/6
<u>``</u>	112-175 SOFT ROCK	770-176
~	175-205 SOFT ROCK (WATER)	
-		>
<u></u>	BAIL TEST - Lot 29, Lake Vi	ew Acres Subd
		Hedlund
-	Box 18	5 AV 88 5 5
<u> </u>	150'- 56PM . Iliamn	9960b B
4	175'- 6 GPM	
	205'- 10 GPM PLUS	į
32	200 10 017 7200	75
~!	well in NE + NW + NE + SW +	E- 1
	LAS 9771 T 55, R33W, SM N36	00 1
-	cc: DGGS	W54 150
'		10
		120)
		Ý E

Hedland Well

9-155 (October 1950)

UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

WATER RESOURCES DIVISION Sleaning WELL SCHEDULE 9/23 ,1962 Field No. 22 Date__ Record by Williaman _____ Office No. ____ Source of data Drivere 1: Location: State ____ _____ County __ ______ ¼ _____ ¼ sec. _____ T. 2. Owner: Eran B. Hickory Address Illaming 3. Topography hase of law trill 4. Elevation 20 It above liana lak 5. Type: Dug, drilled, driven, bored, jetted _____19__ 6. Depth: Rept. 72 ___ft_ Meas. _____ft. 7. Casing: Diam in to Depth _____ft., Finish _____ 8. Chief Aquifer _____ From ____ Others ____ 9. Water level _____ft. rept. meas. above below __ft. above surface _____ which is _____ 10. Pump: Type _____ G. M. ____ Power: Kind _____ Horsepower ____ 11. Yield: Flow _____ G. M., Pump ____ G. M., Mess., Rept. Est. ____ Drawdown _____ft. after _____ hours pumping _____ G. M. 12. Use: Oord, Stock, PS., RR., Ind., Irr., Obs. adequate Adequacy, permanence 13. Quality Fair Temp °F. Taste, odor, color _____Sample Yes Unfit for _____ 14. Remarks: (Log, Analyses, etc.) over

U. S. GOVERNHENT PRINTING OFFICE 10-62891-1

112-5

o- pea gravel poch chips I'h ft grembo beach gravel inth water 22 grembo

M-W DRILLING, Inc. P. O. Box 4-1728 • 2811 Dawson A C 907-279-1741 ANCHORAGE, ALASKA 99509

DRILLING LOG

Well Owner	Ray Loesche - Rainbow	King Lodge		_Use of Well_	Dom tax
Location (address	s of: Township, Range, Se	ction if known or	distance main r	hen	
Location (address		Iliamna Alaska			
· · · · · · · · · · · · · · · · · · ·				1 11	
Size of casing 6	Depth of Hole 143	feet Cased to	18 feet		1
Static water level 10	ft. (above) (below)	land surface. Fini	sh of well (check	one) open er	id (x);
Screen ();	Perforated ().		2 (t e st	1.
Describe screen o	or perforation	None	*	-	
Well pumping test at of drawdown fro	12 gallons per (kökk) m static level.	(minute) for 1	hours with	100%	ft.
Date of completion	4 July 73	- 1		. 16	£ *
		WELL LOG			. :
Depth in feet from	, , , , , , , , , , , , , , , , , , , 				
ground surface	Give details of forma	tions penetrated, si	ze of material, co	lor and hardne	ess
0_TO_5	_Sand: fine, sil	_ty	ith ^y		
5_TO_10	Gravel: small				
10_TO_14	Gravelly Clay		,		
14_TO_28	_Bedrock: volcer	11c (½ GPM	28'- woter)		
28 TO 35	- K - H	grey			
	<u>n</u> n	Brown	- 1-		(
45 TO 47	<u> </u>	Red			
		Brown			
60_TO_62		Green			al.
62 TO EO		Grey Green	* 00		
		H ù			* 11/4
140TO_143.		Brown			
143TO	Sanda good ye	terbesring		.,	
TO					
TO		Wayn & Kill	they_		
3 3 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	7 18	darne s. Wester		e Well	
			Loesch	LE Mell	

M-W DRILLING, Inc. P. O. Box 4-1728 • 2811 Dawson A C 907-279-1741 ANCHORAGE, ALASKA 99509

DRILLING LOG

Well Owner	Mr. Leonard KcMillen	Use of W	Tell Dom .
	f: Township, Range, Section, if known		<u> </u>
	L31, Lake View Acres Subdivision		
	1,		
	epth of Hole 108 feet Cased		* ×
4	ft. (above) (below) land surface. F	inish of well (check one) ope	n end (X);
	Perforated (X).	81	
	perforation Four (4) 1 B. shot perforation		(4)
Well pumping test at 6 of drawdown from	gallons per (hour) (minute) for static level.	1 hours with 71	ft.
Date of completion 17	Sep 73	4 2 2	
	WELL LOG		
Depth in feet from ground surface	Give details of formations penetrated	l, size of material, color and ha	rdness
С ТО 5	Open		
_5_TO_12_	Boulder Cravel		
12TO30	Silty Clay		
_30_TO_32	Sandy Clay - wet		1
52_TO_40	Silty Send	•	¥
	.Clavey Sand - wet		
_80_TO_83	Pes Gravel: waterhearing		
83 TO 97	Hardnan Clay		
97 TO 108	Weathered Badrocks volcanic	s, becoming more competer	ot 1061:
TO		er in weathered fractures	
TO		w	
30			
TO		Waise EN other	,
TO		Wayne E. Bestheris	
TO			
то			

M-W DRILLING, Inc. P. O. Box 4-1728 • 2811 Dawson A C 907-279-1741 ANCHORAGE, ALASKA 99509

DRILLING LOG

Well Owner Dick	6 Sjoden i .		Use of Well Dom
	*	·	
, h	: Township, Range, Section,	if known; or distance	e main road
"D	mns Lake Lodge	1	
. · 		1 >	Marcha Terror
Size of casing 6 De	pth of Hole 196 feet	Cased to 10.	feet
Static water level 15	_ft. (above) (below) land s	surface. Finish of wel	l (check one) open end (X);
Screen (); P	Perforated ().	*	
. Describe screen or p	erforationNo	ne .	
Well pumping test at 15 of drawdown from s	gallons per (hour) (minu	ute) for 1 hou	rs with 1001 ft.
Date of completion 7	Aug 73	<u> </u>	9 91 91
	WELL I	LOG	*
Depth in feet from ground surface	Give details of formations	penetrated, size of ma	terial, color and hardness
	Gverburden		
			2
7 TO 16	Bedrock: blue gray	volcanics, fract	d off with A" liner 1 account
TO	after wel	i drilled to T.D.	311 with a liner a decision
16 TO 87 57	_ Bedr ck: s/a. ng we	ter)
57 TO 117	" Light cres	volcenice	3
117 _TO_ 1/0	" Multi-colo	red "	
_140 TO_1=4	" Rlue Trev,	very hard	
_1*4 TO 1.4	" Grown, re	diwa herd	
165 TO 160	hleck may	v, very hardl	
160 TO 190		f't-	
167 TO 19s	" Stank are	y, vory tord	
15t TO 196	" tony space	n , citablity cie	St. W. Comb. Street Co.
то		W. Fr	
TO		Mayor & Mark	L.
то		ericery.	/

Sjoden Well

APPENDIX 2 Well driller's logs for wells in Newhalen, Alaska

. 6/1	FORM NO 9-1904-A
N	U.S. DEPT. OF THE INTERIOR AKRG-800-27
~ 0.	- O D C T GEOLOGICAL SURVEY
	Recorded by WATER RESOURCES DIVISION Date 11 - 17
	SITE SCHEDULE
81b.	Check One
1 1 1 1 1 1 E	50.4.3 201/54.53 40 GH 52 P PAROLL R-00 T- (A) DAM V 0
	Die Reporting College College
· 2000	Site-Type 2" C D M PT M P T W P T W P Gallette, Selection, selecti
B .	Trained 1 1 1 1 1 1 1 1 1
[] []	
= 22 6	0- 5:414/3123 · 10- 15:458 3:20 · 11-15:458 3:20
w a a	New Towns and the Control of the Con
	12- SCIO10151013131211-DIDGID12
133 W	11-17-17-17-17-17-17-17-17-17-17-17-17-1
Mark In I	AND 18- 1/10/10: 10 10-125 10-125 10-125 10-125 10-125 10-125
O.K.	Aldreds 16 1/10/0 10 1 1 Measurement 17 1 Accuracy 18 1 Ac
12 4 9 1	100 0 C E F N K S T U V W . Unit (OWDC) -50- 404,000 T
	depression, streem, dunch Tiel, biliton, state, person, officiore, pedinees, billaide, torrees, undufriting, subant to channel of any and the draw
	Construction 21 = 0 4/9 7/1 9 6 25 A D E G H & M P R . 8 T "U (W) X Z *
	month of the second sec
GH GH	
1	supply
AKRG HEADER WATER KEY PUNT O	Secondary 25 = 8 Terdery Use 26 = 8 Depth of 27 = 1/2 = 1 Depth of 28 = 1/2 = 1 Source of 28 = 1/2 = 1 Source of 28 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/2 = 1/
AKRG HEAD WATE KEY F	Water Lord 30 - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	month day year
	Entrand of Resourcement
	abline proper proper proper tops tops district tops
	Side Status 37 = .D .F .G .N .Ø P .R .B .T .V .X .Z .B
	Standing recountly pumped pumped recovery management of the control of the contro
i ž	Source of Geotydrologic Data 9 Pump Used 35= 6 Messuring 265- 1 1 0 Messuring 267- 1
	OWNER IDENTIFICATION (1)
	R=158 + T4 A D M + Dets of 159 8 0:0/0 1/ 1/50 +
	and delete, modify ments day year
	and the grade of the second of
	OTHER SITE IDENTIFICATION NUMBERS (1) 190#7022 191
	R=188 + T= A D M + 1400 190# 0.011 1 1 4 Andgree 191= A.K.M.P. 11 1400 191
	New Cord Same K&T
•	The state of the s
27	SITE VISIT DATA (1) R=186 0 T= A D M 0 Date of 1878 / / 0 Person 188-
	R=186 © T= A D M © Detail 1878 / / © Name of 188-
	FIELD WATER QUALITY MEASUREMENTS (1)
	T- A D M # Deta 192# / / # Gookydro 185#
	New Card Same 15 New 125 Temperature 106 # 0,0,0,4,0 0 Oogross C 107 -
	No. of the Contract of the Con
	ALERO CONT. TAKE
	Odner (STORET) 194 # 167 = 167 = 167 =
	Other STORETI Too B 0 Volum 187 101 0
	FOOT NOTES:
	© Source of Deta Codes:
si	Rethod Feshod
	determined determined by
C:	Drawdown: fc Microscy Person has
.	WATER DATA: Iron Sulface Chloride Hard,
	the
	Tasta, color, etc.
157 / 29	

LAIBZU

Hell No. Newholes

WELL SCHEDULE


U. S. DEPT. OF THE INTERIOR . KP GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

	MASTER CARD
met ; 3	Record by AJF Source BIA- Date 11-14-69 May Illiaming (C-C)
My for	State Alaska OZ County Newholen F.K
Villa	Latitude: 59 43 20 N Longitude: 1 5 4 5 3 40 grumber:
1.79	LACUTACY: 4 T 5 Gys 330 Sec 2/ SW , SE & SE & SEWARD
of Copie	Focal SC 005033210DDCC pumber;
	Local user 80027 Owner BAR
F	Owner-or name: BIANEWHALEW) Address: Newholen
	(6) (7) (8) (8) (8)
	(A) (B) (C) (D) (E) (D) (D) (D) (D) (D) (D) (E) (D)
	Use of Air cond, Bottling, Com, Dewater, Fower, Fire, Dom, Irr, Med, Ind P S, Rec, water: (5) (7) (7)
9	Stock, Instit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other
	Use of (A) (D) (C) (H) (0) (F) (E) (X) (U) (W) (X) (S) vell: Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused Withdraw, Heate, Destroyed.
	DATA AVAILABLE: Well data Freq. W/L meas:: Field squifer char, 72
	Hyd. lab. data:
	Qual., water data; type: Comp # 7022
	Freq. sampling: Pumpage inventory: po, period:
	Aperture cards: yes 77
	the second of th
	Log data:
المارية الم	WELL-DESCRIPTION CARD
This depth	WELE-DESCRIPTION CARD SAME AS ON MASTER CARD Depth well: 65 Pet 65 Read. 24 6.
match ing	WELE-DESCRIPTION CARD SAME AS ON MASTER CARD Depth well: 65 Pet 65 Pept accuracy Depth cased: 61 Casing 20 Casing
down my	WEL E-DESCRIPTION CARD SAME AS ON MASTER CARD Depth well:
match and	WELL-DESCRIPTION CARD SAME AS ON MASTER CARD Depth well: Depth cased: (first perf.) (C) Finish: porous gravel w. gravel w. boriz. open perf., screen, sd. pt., sbored, open bole, other bole, oth
match and	WELL-DESCRIPTION CARD SAME AS ON MASTER CARD Depth cased: (first perf.) (C) Finish: Porous gravel w. gravel w. boriz. open perf., screen, sd. pt., shored, open bole, other concrete, (perf.), (screen), gallery, end, Method (A) (B) (C) (D) (H) (J) (P) (E) (T) (V) (W) (E) Drilled: air bored, cable, dug, byd jetted, air reverse trenching, driven, drive rot., percussion, rotary, Date
match ing EIA chard wells See drawing in AKA	WELL-DESCRIPTION CARD SAME AS ON MASTER CARD Depth well: Depth cased: (first perf.) (C) Finish: porous gravel w. gravel w. boriz. open perf., screen, sd. pt., shored, open bole, other concrete, (perf.), (screen), gallery, end, Method (A) (B) (C) (D) (H) (J) (P) (E) (T) (V) (W) (E) (Defilled: air bored, cable, dug, hyd jetted, air reverse trenching, driven, drive wash, other tot., percussion, rotary, Date Drilled: Pump intake setting: Fump intake setting:
match ing EIA chard wells See drawing in AKA	WELL-DESCRIPTION CARD SAME AS ON MASTER CARD Depth well: Depth cased: (first perf.) (C) Finish: porous gravel w. gravel w. boriz. open perf., screen, sd. pt., shored, open bole, other concrete, (perf.), (screen), gallery, end, Method (A) (B) (C) (D) (H) (J) (P) (R) (T) (V) (W) (E) (Defilled: air bored, cable, dug, hyd jetted, air reverse trenching, driven, drive wash, other rot., percussion, rotary, Date Drilled: Pump intake setting: Finish: porous gravel w. gravel w. boriz. open perf., screen, sd. pt., shored, open bole, other wash, other sot., percussion, rotary, Bate Drilled: Tot., percussion, rotary, Drilled: Tot., p
match ing EIA chard wells See drawing in AKA	WELL-DESCRIPTION CARD SAME AS ON MASTER CARD Depth well: Depth cased: (first perf.) (C) Finish: Porous gravel w. gravel w. boriz. open perf., screen, sd. pt., sbored, open bole, other concrete, (perf.), (screen), gallery, end, Method (A) (B) (C) (D) (H) (B) (P) (E) (T) (V) (W) (E) (E) (E) (E) (E) (E) (E
match ing EIA chard wells See drawing in AKA	WELL-DESCRIPTION CARD SANE AS ON MASTER CARD Depth well: Depth cased: (first perf.) (g) (h) (g) (h) (h) (h) (h) (h
match ing EIA chard wells See drawing in AKA	WELL-DESCRIPTION CARD SAME AS ON MASTER CARD Depth well: Depth cased: (first perf.) (C) Finish: Porous gravel w. gravel w. boriz. open perf., screen, sd. pt., sbored, open bole, other concrete, (perf.), (screen), gallery, end, Method (A) (B) (C) (D) (H) (B) (P) (E) (T) (V) (W) (E) (E) (E) (E) (E) (E) (E
match ing EIA chard wells See drawing in AKA	SAME AS ON MASTER CARD Depth well: SAME AS ON MASTER CARD Depth well: Sating 10 Same
match ing EIA chard wells See drawing in AKA	SAME AS ON MASTER CARD Depth well: Depth cased:
match ing EIA chard wells See drawing in AKA	SANE AS ON MASTER CARD Depth well: Casing 10 Casi
match ing EIA chard wells See drawing in AKA	SAME AS ON HASTER CARD Depth well: Casing 10 23 Cept
match ing EIA chard wells See drawing in AKA	SAME AS ON MASTER CARD Depth well: Casing 10
match ing BIA chand Wells See drawing in AKA	SAME AS ON MASTER CARD Depth well: SAME AS ON MASTER CARD Depth well: State Casing 20 Casin

New Holen, Toustard april 26/962 Michor of Marken com, mos. 4/24/62 FIN-MOV 4/25/22 Sale Land com Dully 4/26/62 Fin Polling 426 second or L Sonrer of data Contact - + X . - . - X see · Owise & LA Back Loor pumped for 17 his continues · Loose growl No Lechne in water Table ayers of clay water crystal clear 200 gfor hr. Sen Haller Zeocher to Let Reen for at lost one

LONG FORM	AND THE PROPERTY OF THE PROPER
Ground-water Site Visit Field Notes	AGENCY FILE NO.
U.S.G.S W.R.D., Alaska 1977 System 2000 updated on	GWSI SITE ID
LOCAL WELL DESIGNATION Hole #4	Site Register Numbers
	A.D.L.
VISITED BY Dearbur, Patrick	A.D.G.&G.S. —
AGENCY	A.D.E.C
INITIAL SITE; INFO, VISIT	U.S.G.S
PURPOSE OF VISIT: field inventory, water level (circle) survey levels, verify locate	el, water quality, geophysical logging, tion, other
WELL DESCRIPTION	AND CONSTRUCTION
OWNER: 1st BFA School now.	as of moyr
	Sec T S R W B&M
Plotted on aerial photo/field map	Scale
Subdivision	blk_lot_; photos taken 2 35 m
SOURCE OF INFORMATION: owner, neighbor, drill (circle) other (specify)	er, driller's log, personal observation,
DRILLER AND COMPANY	
DATE COMPLETED TYPE OF	DRILL RIG
HOLE DEPTHft, WELL DEPTH_/28 YEP	ft, TOTAL CASINGft, DIAMin
WELL FINISH	•
PUMP: mfg. name & no,	depth setft, diam discharge pipein
	<u></u>
WELL YIELD:gpm forhours wit	
discharge	; aquifer test date
WATER LEVEL: describe MP tog of coming	Sal which is 4 ft above LSD
Hold-cut WL below MP	WL below LSD Time
2: none - con't get 3. modelied pit	into com
modelied pit	len
Installedreco	order, W#, funding project
	1 / 1 / / / 2



Recorded by FE 7:T

U.S. DEPT. OF THE INTERIOR
GEOLOGICAL SURVEY
WATER RESOURCES DIVISION
GROUND WATER SITE INVENTORY
SITE SCHEDULE

Date 11-21-72

					SHE SCHEDEE
				9	Check One English Metric, Units GENERAL SITE DATA (0)
					Site Ident No 511451 (1 515 27121) RG Number R=0 + Transaction T= A D M V +
					6 19 Bdd, Giorie, medity, verhied
5	П	Ī	T	ī	Site-Type 2= C D H 1 M P T. (W) & Reliability 3= C (U) L M & Reporting 4= 11.516.5. + Site-Type 2= C D H 1 M P T. (W) & Reliability 3= C (U) L M & Reporting 4= 11.516.5. +
Ž	П		1.		Project S- County
INITIALS	1.1	· V	13	3	150/2510 [150/5227] Latters [10-10 5/2] W.B.
	H	7	-	-	Projected Sec. 10 11-11-12 Longitude Sec. 10 oct. 10
DATE		4	1	1.7	Local 12- 51(1)106101313121211DDCD111 100114 Not 13-5 1/5 5 5 5 5 5 12 11 T 0.0 5 5 12 D 2 W 15 + Boundary 12 S 1/4 1/4 1/4 1/4 1/4 1/4 0001000 100000 100000 100000 100000 100000 100000 100000 100000 100000 100000 100000 100000 100000 100000 100000 1000000
	-	-	1	1	Coordina 14-7,474,444 C-G
KEMA.CK	V	j		1	Attitude 16- /10,3 0 0 Method of Measurement 17- A L M & Accuracy 16-25 *
E E	-	1	11	1	Topo Setting 18- D C E F H K L & P. S T U V W + Hydrologic 20- /19,0,4,0,0,0,2 +
7	- "	· <u>'</u>	-	-	dispression, streem, dunce, Tier, billiop, sink, ownerp, offshore, podiment, billiside, serroce, undutating, unitary, episand shannel Date of First Use
1	i	1.		2	Dete of First Construction/ menth day year Use of 23 - A D E G H d M P R S T U W X Z + Site seade, drain, gas-selemic, best, observ- mine, all or, eacherge, copress, cest, succeed, distin-treats, destroyed drawd, formal record atlant, gas
1	1	LEVEL	F		Use of Water 24 = A & C D E F M I M N P R S (T) U Y Z & alr cond., bettling, commercial, dewater, power, fire, domestic, terigotion, medicinal, industrial, public, representation, stock, institution, sunosed, decat, other
1	ER		PUNCH		supply
AVD	HEADER	I - I	KEY P		Water Use at Water And Hole And Hole Well Well Tries and Depth Deta
1	11	>	× 10	J	Water Level 30 = 1 , 1/7, 0, 9, 4 Date Measured 31 = 0, 2/2, 0/1, 7, 674 Source 32 = 10 +
19.5					Method of Measurement 34 = A C E G H L M R B T V Z alriling catherood, actionated, pressure, actionated, geophysical, assumenter, imported, action, delarated, action
					sirline gape processes gaps logs tope tope stockic tope
					Site Status dry, Stooring, country, obstruction, pumping, recently, nearby; Sereign purface water other
					Heaving scountry pumping recontry abstance officess
					Source of Geolyydrologic Date Pump Used 35 = 6 Measuring 266- 1 4 Measuring 267- / / / 4 Point Date 266- 14 4 Measuring 267- / 4 Point Date 267- / 4 Point Dat
				•	OWNER IDENTIFICATION (1)
					R=158 * T= A D M * Deta ef Ownership 159 # 7 2/2 7 1 7 6 7 *
					Name: Last 161- 1/ C P J P 4 First 152- 1/ C V P P 6 Initial 163- 4
					1962 6 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
					OTHER SITE IDENTIFICATION NUMBERS (1) R=189 T= A D M + Ident 190 # 0,0,1/1 Audignor 191- A,K,MP
					New Card Same R & T 190 # 5 9 0 Z. /c + 191 = A.K.R.G.
					1900 BEDRUCKY 1910 CANFINELY
					SITE VISIT DATA (1)
					R=186 * T= A D M * Orte of 187# / / a Name of 188= Add, delete, modify Manual
					FIELD WATER QUALITY MEASUREMENTS (1) R = 192 T = A D M 0 Date 193 # , / , / , 4 Gookydro- topic Unit 195 # 1 1 1 1 0
	171				add, delete, medify menth sley year
					New Cord Same R thru 195 Temperature 196# 6,0,0,1,8 Degrees C 197 - , , , , , , , , , , , , , , , , , ,
					Conductance 196 g 0 0 9 9 9 6 9 g Mhos 197 - 1 1 1 0 0
					Other (STORET) 196 # # Value 187 - 191 #
					Other (STORET) 196 # 9 Value 107 - 4
					FOOT NOTES:
					① Source of Deta Codes:
					S D Ø A R L G Z reporting, driller, owner, other gov't, other legs, geologist, other
					genery reported.

Well No. Nowhols.

WELL SCHEDULE
GEOLOGICAL SURVEY u. s. dept. of the interior \mathcal{KP}

WATER RESOURCES DIVISION

and the second s
MASTER CARD
Record by ASF Source BIA Date 11-14-69 Kap Illiamna (C-6)
State Aloska 02 County (or town) F.K
Latitude: 5 9 4 3 2 0 No Longitude: 1 5 4 5 3 3 0 Sequential 1 gumber: 12 degrees 13 min sec 10
Lat-long T 5 6 1 330 Sec 21 . SW . SE . SE & SEWARD
well number: SCO05033326DDCD Other number: WY 11 4
Local use: 80026 Ovner RIA
Owner or name: BIANEWHALEND Address: Nowholen Alette
34 61 04
Ownership: County, Fed Gov't City, Corp or Co, Privete, State Agency, Water Dist (A) (B) (C). (D) (E) (F) (E) (I) (N) (F) (R)
Use of Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec,
Stock, Instit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other
Use of (A) (D) (G) (H) (\$\phi\$) (F) (R) (T) (U) (V) (X) (5) vell: Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdray Waste, Destroyed.
DATA AVAILABLE: Well data 70 Freq. W/L meas:
Hyd. lab. data:
Qual. water data; type: Comp# 9992
Freq. sampling: Pumpage inventory: no, period: 76
Aperture cards:
Log data:
WELL-DESCRIPTION CARD
SAME AS ON MASTER CARD Depth well: 127, 7 ft 129 Fept 24 3
Depth cased: 4/0' Screen ft 1/2:4 Casing 20 the Blam. 4/ in 14
(C) (F) (G) (H) (\$\phi\$) (P) (S) (T) (W) (X) (E) (Finish: concrete, (perf.), (screen), gallery, end, (screen), screen, sd. pt., shored, open hole, other
Other
Method (A) (B) (C) (D) (H) (J) (P) (R) (T) (V) (W) (E) Drilled: air bored cable, dug, hyd jetted, air reverse trenching, driven, drive vash, other Date
Drilled: 2 3/- 5.7 9:6:7 Pump intake setting:ft 34 36
Driller: Ray Linabrilge.
Lift (A) (B) (C) (J) multiple, multiple, multiple, mone, piston, rot, submerg, turb, other (E) (H) (R) (P) (R) (S) (T) (E) (type): air, bucket, cent, jet, (cent.) (turb.) mone, piston, rot, submerg, turb, other 39 Shallow
Power nat LP Irans. or (type): diesel, elec, gas, gasoline, hand, gas, wind; H.P.
Descrip. HPft below LSD , Alt. HP
Accuracy:
Water 17'10' above above 45
Date 1010 12 2 2 2 6 7 255 10 Hethod
Pumping 40
QUALITY OF C
WATER DATA: Iron Sulfate Chloride Hard. 72
Sp. Conduct K x 106 Temp. °F 74 74 sampled
Taste, color, etc.

WATER SUPPLY WELL LOG

()

PROJECT	NO. 0175	WORK O	RDER NO. 7026 LOCATION Newhalen	DATE STARTED 11/1:
DATE COM	PLETED_	2/20/67	DRILLER Dirksen & Pooler . Typ	E OF RIG Hillman-Fair
TOTAL DE	PTH 128'	7" FT. CA	SING INSTALLED 43°2"-6in GRO	UT Aqua-gel
			ot Johnson LENGTH 5'8" DIA	
PRODUCTI	ON: HRS	PUMPED (52 STATIC WATER LEVEL 17'10TT. AVAI	LABLE DRAWSOWN 105
			DRAHSOWN . 45 FEet FT SPECIFIC CAPA	
•				
DATE.	DEPTH FROM	IN FEET TO	FORMATION	DRILLER
11/9/66	0	6	Clay & Gravel	
-	6	16'6"	Clay, gravel & sand	
	16'6"	20'4"	Brown Clay	
	20'4"	23'8"	Brown Clay & Gravel	
-	2348"	31'6"	Gravel some clay	3
	31'6"	44 '2"	Blue clay & gravel	95.1
11710	44 '2"	66 '9"	Hard pan and sand	
11/11	6619"	86*	Green hard pan & sand	
11/12	86 1	113'7"	Green slate	7
11/13	113'7"	125'1"	Blue slate	
11/13	125'1"	128'6"	White limes,tone with cracks carrying	vater.
Eine-		1	•	
			this well was closed down on 11715/66	
2/3/67 b		42'2" bec	se we could only get the 4 theh casing ause of rock and hard pan. Ordered an	underreamer
		wn to bott	on it to come in so we could get the com.	sing
			1	d'Ing last
***************************************			Foreman	II woll driller

Newhalen, Alaska Hole # 4 WO # 7026 Feb. 20,1967

Ground Level

6 * Clay & Gravel

16'6" Clay, Gravel & Sand 20'4" Brown Clay 23'8" Brown Clay & Gravel

31'6" Gravel some clay
42'10"-6inch Casing

44'2" Blue clay & Gravel

51'6" Green Clay, Coarse Sand

57' Hard Pan & Gravel ... Water-1 Gal @ Min.

66 9" Hard Pan & Sand

86' Green Hard Pan & Sand

Drillers: Galen Dirksen Homer Pooler

Total Depth 128'7"

on full drawdown.

this well.

43'2" 6inch casing

4°10" screen exposed. Static level 17°10", Available drawdown 105'.

One 5'8" .030 slot screen,

Will produce 60 gal @ min

casing. Would advise not

Heat tape is hanging on

127'10" 4 inch casing, 4inch casing is supported by 6inch

to use a pitless adapter on

bottom of well cap. But is probably not me cessary, for

this well should not free cc.


200 ft. of heat tape in well

113'7" Green Slate

125'1" Blue Slate 128'7" Lime Stone (White) & Water in crack (no sand) 2-3 Sketch by

reman II well Driller

Te.	Latitude-longitude 39	43, 20 8 1.54	153, 30
HYDROGEOLOGIC CARD			
SANE AS ON HASTER CARD Province:		Section:	
Prainage Basin;	808	Subbasin:	
(D) (Q) (E)	(1) (1) (H) (Y)	•	
Topo of depression, stream channel, dunes, well site: (6) (7) (5) (T)	(A) (A)		
offshore, podiment, hillside, terro	ace, undulating, valley flat		
AQUIFER: system series	<u></u>	quifer, formation, group	
Lithology:	Origin:	Afulfer Thickness:	£c
Length of well open to:	ft Depth t		
HINOR AQUIFER:			
system . series .		Muifer, formation, group Aquifer Thickness:	
Lithology: Length of	Depth t		
31 sell open to:	ft top of:		57 59
Screened: 124 - 127			
Consolidated rock:ftft	Source of da	ta:	
basement:ftft	Source of da	ta:	
material:	characteristics:		
Coefficient gpd/ft	Coefficient Storage:		ا السالية
Coefficient gpd/ft ² ; Spec	c cap:gpu/ft;	Number of geologic cards	·
,			5.5
Lag			-
1 Cley		ļ -	
0-6 - Great 6-1 Clay 11.12 Clay grand on ser	1		
" 16.12 Clay grand on Se-	J	1	4
List y Bring Clay	/ /		1-1-1
50.4, - 13 6, - 3 cm. (-lay 1.	1 9-15		0 8
317" - 31 Va - France Sime C'	.4	<u>870 370</u>	E
311/2 - 44'D' - Bloe clay and	govel	314	2001
41/2" - 51.6" - Green ting	· Courte giver	3-1	
51.6' - 57' Herd per 6.	I grant	2/6	2
57 -66 '9' " " "	Isund	No	.0
		*	. 10
66'9' - 86 - Green hors			10
16'- 113'7' - Gran Siet	2		
3'7" - 125' 1" - Blue slote	11	in creek in the	10
15'1" - 128'.7" - Limeston	, while - ws		6.6
			1



APPENDIX 3
Well driller's logs for wells at the Iliamna FAA facillity near Newhalen, Alaska

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR KP GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

	3
MASTER CARD	- 500
Record by AJF Source FA.4 . Date //- 12-C4 Map	Illianna (0-6) or 03
State Aloska 0:2 County Illiana	FR
Latitude: 594545 N & Longitude: 154494	10 Sequential /
Lattlong 4 T 5 (s)R 32 4/Sec 12 N(W k, SW) k, 1	NIII > SFUIAPD
Local Signal Signal Tiping City Other	BAH
23	9A - Ots W-11 2?
35 (7)	
Owner or name: FAA Address: J	11. omna, Aloska
Ownership: County, Fed Gov't City, Corp or Co, Private, State Agency, Water Dist	er F
(A) (B) (C) (D) (E) (F) (H) (I) (N) (F) (R) Use of Air cond, Bottling, Comm, Devater, Power, Fire, Dom, Irr, Med, Ind. P S. Rec.	
water: (S) (T) (U) (V) (W) (X) (T) (E) Stock, Instit, Unused, Repressure, Recharge, Desai-F S, Desai-other, Other	44 P
	(3) (6)
Use of (A) (D) (G) (H) (Q) (F) (R) (T) (U) (W) well: Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused Withdra	Waste, Destroyed, 49
DATA AVAILABLE: Well data 70 Freq. W/L meas:: 71	Field aquifer char. 72
Hyd. lab. data:	
Qual. water data; type: Comp. #4880	74 P
Freq. sampling: Pumpage inventory: no. period:	.74
Aperture cards:	yes 27
Log data: LOG ON back of Analysis	7
WELL-DESCRIPTION CARD 70= 6/	74 74
- Keas.	24
Depth(cased) 5 2 Casing	accuracy in
(C) (F) (C) (H) (\$\phi\$) (P) (S) (T) (W)	29 30
Finish: concrete, (perf.), (screen), gallery, end,	, open hole, other (%) (2)
Method (A) (B) (C) (D) (H) (J) (P) (R) (T) (V) Drilled: air bored, cable, dug, hyd jetted, air reverse trenching, driven, cot., percussion, rytary,	drive LC
Drilled: 11./54 9:5:4 Pump intake setting:	ft 5
Driller:	34 31
name de address	(E) Deep
Lift (A) (B) (C) (J) multiple, multiple, multiple, mone, piston, rot, submerg, turb, Power nat LP	Trans. or
(type): diesel, elec, gas, gasoline, hand, gas, wind; H.P	meter no.
Descrip. HPft below LSD	, Alt. NP
Alt. LSD: 100 Accuracy: Topo	50'CI. "5
Level /8 ft below MP; Ft below LSD Accuracy:	
meas: 53 N: 5:4 55 Yield: 050 gpm 2	Method determined
Drawdown: ft Accuracy: Pumping period	hre 4
QUALITY OF WATER DATA: Iron Sulfate Chloride	Hard.
Sp. Conduct K x 106 Temp. of 4 Date sampled	bbar
73 74 76	77 76
Taste, color, etc.	

·CAA.

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY WATER RESOURCES DIVISION

No	
OTHER NOG	

WELL LOG

StateAlas	ska County South WEST Subarea Iliamna	**********	
OwnerCiv	vil Aeronautics Authority		
Location Wes	st side of present pump house		
Location	**************************************		****
			······································
	Address		
Date12/1/5	Casing diam. 6 inch Land-surf. a	lt	
Source of data	TOUTH A DECEMBER OF THE PROPERTY OF THE PROPER		
	(Enter type of well, perforations, yield, and drawdown at end of	log)	
CORRELATION	Material	THICKNESS (feet)	DEPTH (feet)
***************************************	? Soil?	5	5
	Silt and little gravel	1.5	20
	Glacier silt (15' water in pipe)	14	34
	Glacier silt (no water)	8	42
	Silt and slide rock	1	43
	Shale rock - broken up	3	46
	Shale rock - broken up (25! of water)	3	49
***************************************	Very hard shale rock - no water	4	53
***************************************	Broken up rock, some silt, struck seams of water 59!	7	60
	Total depth - 60 feet Water level - 12½ feet		
	pumped 57 hrs. at 600 gph 51' dd. 250 gph 7'10" dd.		

RECORD BY	DATE	SHEET	OF

U. S. GOVERNMENT PRINTING OFFICE 18-81587-1 WSFAA 1

SCHEL M TLIAMNA ILL-1 Filled well logi 5-20 - set o little grand 20-34'- flacial sell, 15" water to pipe 34-42' - Flacial rell - no with 42-4 - silt o slide rock 24-46 shale rock, broken up 47-49" shale rock, broken up 25" water in pipe 50.53' - Very hard whele, not no water in casing Frille below caring 54-58- very hard shale rock. no water 59-60'- Broken up wocho some sell. Struck sean of 3.10 water. Water come up in casing to height of 12'6" from top of casing . I rilling from now 10. Dec 1. 1954 Housing area 6" cased well abulled on W side of pung house to a dyth 161: caring 5' welded sections Caring down 53', Solid Rock executives at 49' Frelling continued & below end of cooling a Waler vein encountered at 59' " a flow of 600 fl to State water level 12't" felow USFAAI

Surface of ground, Jot placed 55 below of about of the freed of the freed of 600 feet for fill pergeng at 600 hall freed of 1 to the pergeng at 600 halls freed of 1 to the freed of the freed of the free of the over freed of the trade of the trade will staying well or out freed well about thous of hear to have the well suffer freed will be the beaute with filler of hear to have with filler of hear.

a e

(6)

s

1

Well No. Ilivania

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

KP GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

	MASTER CARD
	Record by AST Source FAA Date 11-12-69 Has Illiomna 12-6 -
	State Alorka 62 County Thomas Fix
	Latitude: 5945160 S Longitudes 15425 Sequential 1
	Lat-long 4 T 5 GIR 73 (1) Sec 9 . LINK & SE & SWESEWARD
	rell number: 5000503509000 DED Other number: 16'
	The state of the s
9	31 21 21 21 21 21 21 21 21 21 21 21 21 21
	Owner or namer' (F.A.A. T. L.T.A.M.A.) Address: Ill. sma 17/01/14
	Ownership: County Fed Coy't, City, Corp or Co, Private, State Agency, Water Dist
	Uas of Air cond, Bottling, Comp. Devater, Fover, Fire, Dom, Irr, Ned, Ind, P S, Rec,
	vater: (5) (7) (9) (9) (9) (9) (6)
	Use of (A) (D) (G) (H) (\$\psi\$) (P) (R) (T) (U) (W) (X) (S) well: Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Racharge, Test, Unused, Withdrew, Wasta, Destroyed, 40
	DATA AVAILABLE: Well data Freq. W/L mess:: Field squifer char.
	70 n
	Qual., water data; type: C 4879
	yes yes
	Freq. sampling: Pumpage inventory: no: period:
	Aperture carda:
	Log data:
	WELL-DESCRIPTION CARD TD 31'4"
	SAME AS ON MASTER CARD Depth well: -/ T ft 21/ rept /
	Depth cased; 16 ft 16 type: ; Diam. 2 in 2
	27 30
	Finish: concrete, gravel w. gravel w. boriz. open perf., screen, ad. pt., shored, open bole, other (a) (C) (D) (H) (J) (P) (R) (T) (V) (W) (E)
	Method (A) (B) (C) (D) (H) (J) (P) (R) (T) (W) (M) (E) Drilled: air bored, cable, dug, hyd jetted, air reverse trenching, driven, drive vash, other
	Drilled: - Pump intake setting: ft 6
	priller:
	Lift (A) (B) (C) (J) multiple, multi
	(cype): air, bucket, cent, jet, (cant.) (curb.) none, piston, rot, submerg, curb, other of Shallow 40 Power nat LP
	(cype): diesel, elec, gas, gasoline, hand, gas, wind; H.P
	Descrip. HP
	Alt. LSD: (source) 70 PU (150)
	Level 14 8 3 ft below HP; Ft balow LSD 48 Accuracy: 52
-	Date meas: 33 35 Yield: 156 1000111 apa 17 Hethod determined 41
11.	Drawdown: 6 ft Accuracy: Pumping period hre
-	QUALITY OF Sulfate Chloride Hard,
	Sp. Conduct K x 106 Temp. "F Date sampled
	Taste, color, etc.

FEDERAL AVIATION AGENCY

Chief, Plant Maintenance Branch, Fr-5100

November 16, 1960

Arthur J. Lappi, Utilities Equipment Hechanic

Completion of Well Drilling Assignment - Ilinsma

Control Building !

1. Drilled six inch dismeter cased well to a depth of 53 feet encountering solid rock. Continued drilling open hole through rock to a depth of 100 feet. Only water strata was from 18 feet to 23 feet.

'2. Pulled casing back and installed 30 thousands opening Johnson Nerdur well screen between 12-21 feet.

3. Installed one-third H.P. Jacuzzi jet pump booked up for challow well one pipe operation. Tump Kodel #3-RPE-C- WIH-783, Motor Model C968 2D6Cl. H.I. 1/3. h.P.N. 3450. Volts 115. Amp. 5.6. New pressure tank and all new piping was installed from well to pump and from pump to pressure tank.

4. Built wood duct from well to underneath floor of control building. Installed 30 feet heating cable around drop pipe and pipe

from pump to wall.

5. Test pumped well 1000 gal per bour with 6 inch drawdown. Depth of well 21 feet 4 inches. Tougth of drop pipe 21 feet. Static level 8 feet 3 inches.

Carago Well: brilled & inch cased well to a depth of () feat encountering solid rock and no water. Continued drilling through rock to a depth of 93 feat and no vater. Fulled onelly and discontled drill.

Suggest that if maker is required for power house and purge an underground pape line could be run from quarters area to power house approximately two hundred feet and them to garage one hardest lifty to to

Smill frame and noter made ready for his present to inchange for overhaul. Related of Smill equipment stored and made ready for chipment to Sold Day. Drill log: Stacked.

exturned to suchorage via Pacific Parthern etrlines October 18, 1960.

arthur J. Loppin, To. 158

Linchrent

" se: P:-5123

Swife, belief, fator, Wellis

selvel

CAAJSN

COMBROT BUILDING KETT

· COT-15	Solld rock - gruen band rock
1 . 85-77	Clay layers and gravel - no water
84-75	Clay and come gravel - no water
56-22	Grey sand - no water
15-31	Gravel and sand - water hydrostatic pressure
JC	Gravel - little water
6-t	Clay and gravel mixed
-	:
4 1	DESCRILLION

, £6-09

09-15 isrd pan - no water 35-78

Clay and little gravel - no water.

Solid rock - Ereen basic rock

Hard pen mixed with gravel - no water

Clay and gravel sixed - no water

DESCRIMING

APPENDIX 4	
Water quality analysis reports for wells in Newhalen, Alaska and at the Iliamna FAA	A facility

ANALYTICAL NOTES

cation Illamna, Alaska		County
ourceDri!led	-	Depth (ft) 61 Diam (in.) 5
ased to (ft) 53 Date drilled 11/54		t of coll. Qts. #2
reatment	_OwnerC	Use Dom.
BF_	WI	12 ft Yield 250/Hw?
emp (° F) Appear w.c. Clear	-	
Ilected 7/18/58		By W. S. Holmes.
emark s		•
, ppm	epm	ррт / ерт
10 ₂ /O _{ml} \	- FRAN	
** OD Samp 440		
0.0. 10ppin 420 Dil: 1+1		31.00
1		
Abs. (A1+Fe)		CO ₃ ml
Abs.(Fe)		
	/	1
e,		
Abs. O.F. Grayno 700		au .
MI std 25 Ships 515		OH
e,m		
Abs		
MI std		100000
		504 8.60 25 AFMI 8.04.0 .17
n,		axs +10 ppm
Abs		
MI std		1010 1095
		16
ml		CI 1.65 _ 50 ml _ 3.51 .101
1		7.45
1		0.351
ml		F
		as opt
/	,	MI std
Ca & 4/ 6.30 50 ml 13 -14	.651	
1.4.3 417-1	.65	m1
1.30		
3.9		
10 8.95 8.75 SUMI 3.540	.32	ml
6330		
12.00 2.45		1
*		
7		NO ₃
ml		NO3
		MI std O.D. 1 from 300
		14 400
m1		mi
		,
		USFALL RNO.

	ppm / epm		ppm	epm
Reading Avg	35.		mi	
0 30	1		ml	-
COLOR LAWY	21.		mi	7
std 100	1			1
Sample 3.0		#4.12	4.1	
			ml	·
m1				
m1				
ota I cations	1.32	Total anions		1.2
25-1		.07 Pe	ercent difference	
otal ions, epm 2.57	ifference, epm	, 07	ercent difference	1
	ppm			
		Specific Conductano	e .	
		(mic romhos at 25° C) R KC1 R	Sample 2374	110
		рН		5.9
		Color		5
7.	COL	Color		-3
Sum	88,	-		
Residue on evap. at 180° C		1		
· ·		İ		1
Residue on evop. at 180° C				}
			Ву	Date
8				.,
Smi		Analyzed	EEC-	8/15/
97	98 45	Cake, checked	· EUS .	8-18-58
Honcarbonate	78 75	Reviewed	1670	5/25%
로 Noncarbonate	0	Reviewed	1.CAC	8/28/58
- Honearbona				1
	100	Typed	iest b.	6/2-7/-
	1.1	Typed Typing checked	(.33h	8/27/51

USFAA1

Dup UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY WATER RESOURCES DIVISION ANALYTICAL STATEMENT [Parts per million] Location Diamna, Alaska 21 Source __Drilled well Temperature (°F) Fe. 0.00=1 Color __ 5 __ pH __ Ca Depth: 61 Suspended matter_ Mg. 6.4 : Hardness as CaCO. Na_ CAA station N. C. _ O ___ Total _ 44 0.1 K. Ignition loss _____ CO. 0 11.19 Dissolved solids . HCO, 68 Specific conductance at 25°C SO4 -3.0 (micromhos) _____117_ CI. 1.5_ 0.1 ... F. NO. 0.0-0.00 82 Chemist ESB REC Sum . Lab. No. 4050_ Collector_ 10-55245-4 3

USFAA1

Lab. No. 4050 --

rCa rMg rNa rK	.748 .140 .278 .003	1.169 1.223 .054 2.392 = - 2.3% error
rCO ₂ rHCO ₃ rSO ₄ rCI rF rNO ₂	.000 1.114 .062 .042 .005 .000 1.223	
	mpleted _	ESB 4-23-57 REC 4-24-57

Project ______
Transmitted _____
Remarks _____

aro 16-65348-

9-185 (October 1950)

UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Date MR RCh - 1) - L 19 Field No.	WATER RESOUR	RCES DIVISION	ر
Record by Source of data Chis M BNAL 1: Location: State HLAS MA County SW Map Map Map Map Map Map Map Ma	WELL SCHEDULE	-1	
1: Location: State PLRS XA. County SW Map Map	Date MARCH-1)-62	, 19 Field No	
1: Location: State PLRS XA. County SW Map Map	Record by		
Map Map Map Madress Matre Mass Matress Ma	Source of data Chis M HWAL		
2. Owner: A sec. T S R W Tenant Address Driller Address Driller Address 3. Topography 4. Elevation ft. above 5. Type: Dug, Grilled, driven, bored, jetted 1/19/19/ 6. Depth: Rept. 6/ ft. Meas. ft. 7. Casing: Diam. 5 in., to in., Type Depth 53 ft., Finish 8. Chief Aquifer From ft. to ft. Others 9. Water level 1/2 ft. rept. 19 above below which is ft. above surface 10. Pump: Type Capacity G. M. Power: Kind Horsepower 11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est. Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. Adequacy, permanence 13. Quality Temp °F. Taste, odor, color Sample Yes No		_ County SW	*********
Tenant Address Driller Address 3. Topography 4. Elevation ft. above 5. Type: Dug, drilled, driven, bored, jetted 1/2 1959 6. Depth: Rept. 6/ ft. Meas. ft. 7. Casing: Diam. 5 in., to in., Type Depth 53 ft., Finish 8. Chief Aquifer From ft. to ft. Others 9. Water level 1/2 ft. rept. 19 above below which is ft., above surface which is ft., above surface 10. Pump: Type Capacity G. M. Power: Kind Horsepower 11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est. Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. Adequacy, permanence 13. Quality Temp °F Taste, odor, color Sample Yes No	Map	- N-	E
Tenant		T SR	W
Driller Address 3. Topography 4. Elevation			
3. Topography 4. Elevation ft. above below 5. Type: Dug, Grilled, driven, bored, jetted 1/1954 6. Depth: Rept. 6/ ft. Meas. ft. 7. Casing: Diam. 5 in., to in., Type Depth 53 ft., Finish 8. Chief Aquifer From ft. to ft. Others 9. Water level 1/2 ft. rept. 19 above below which is ft. above surface ft. below surface ft. below surface ft. below surface ft. above surface ft. ft. Pump: Type Capacity G. M. Power: Kind Horsepower 11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est. Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. Adequacy, permanence 13. Quality Temp °F Taste, odor, color Sample Yes No			
4. Elevationft. above below 5. Type: Dug, irilled, driven, bored, jettedft. 6. Depth: Reptft. Measft. 7. Casing: Diam	Driller	_ Address	
5. Type: Dug, drilled, driven, bored, jetted 77 19.17 6. Depth: Rept. 6 / ft. Meas. ft. 7. Casing: Diam. 5 in., to in., Type Depth 23 ft., Finish 8. Chief Aquifer From ft. to ft. Others 9. Water level 72 ft. rept. 19 above below which is ft. above surface 10. Pump: Type Capacity G. M. Power: Kind Horsepower 11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est. Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. Adequacy, permanence 13. Quality Temp °F. Taste, odor, color Sample No	3. Topography		
5. Type: Dug, drilled, driven, bored, jetted 77 19.17 6. Depth: Rept. 6 / ft. Meas. ft. 7. Casing: Diam. 5 in., to in., Type Depth 23 ft., Finish 8. Chief Aquifer From ft. to ft. Others 9. Water level 72 ft. rept. 19 above below which is ft. above surface 10. Pump: Type Capacity G. M. Power: Kind Horsepower 11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est. Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. Adequacy, permanence 13. Quality Temp °F. Taste, odor, color Sample No	4. Elevationft. above below		+
7. Casing: Diam. 2 in., to in., Type Depth 53 ft., Finish 8. Chisf Aquifer From ft. to ft. Others 9. Water level 12 ft. rept. 19 above below which is ft. above surface ft. below surface ft. below surface ft. Bolow ft. above surface ft. Flow G. M. Power: Kind Horsepower 11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est. Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. Adequacy, permanence 13. Quality Temp °F. Taste, odor, color Sample Yes No	5. Type: Dug. drilled. driven, bored, jet	ted // 1954	
7. Casing: Diam. 2 in., to in., Type Depth 53 ft., Finish 8. Chisf Aquifer From ft. to ft. Others 9. Water level 12 ft. rept. 19 above below which is ft. above surface ft. below surface ft. below surface ft. Bolow ft. above surface ft. Flow G. M. Power: Kind Horsepower 11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est. Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. Adequacy, permanence 13. Quality Temp °F. Taste, odor, color Sample Yes No	6. Depth: Rept. 6/ ft. Meas.	ft.	
8. Chisf Aquifer From ft. to ft. Others 9. Water level 12 ft. rept. 19 above below which is ft. above surface of the below surfac	7. Casing: Diam. 5 in., toin	., Туре	
Others 9. Water level 12 ft. rept. 19 above below which is ft. above below surface 10. Pump: Type Capacity G. M. Power: Kind Horsepower 11. Yield: Flow G.M., Pump G.M., Meas., Rept. Est. Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. Adequacy, permanence 13. Quality Temp °F. Taste, odor, color Sample Yes No			
9. Water level 12 ft. rept. 19 above below which is ft. above surface 10. Pump: Type Capacity G. M. Power: Kind Horsepower G. M. Horsepower Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. Adequacy, permanence Sample Yes No	8. Chief Aquifer	From ft. to	ft.
which isft. above surface 10. Pump: Type Capacity G. M Power: Kind Horsepower 11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs Adequacy, permanence 13. Quality Temp °F. Taste, odor, color Sample No			
which isft. above surface 10. Pump: Type Capacity G. M Power: Kind Horsepower 11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs Adequacy, permanence 13. Quality Temp °F. Taste, odor, color Sample No	9. Water level 12 ft. rept.	19above_below	
10. Pump: Type Capacity G. M Power: Kind Horsepower 11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs Adequacy, permanence 13. Quality Temp °F Taste, odor, color Sample Yes No		which isft, abo	ow surface
Power: Kind Horsepower 11. Yield: Flow G.M., Pump G.M., Meas., Rept. Est. Drawdown ft. after hours pumping G.M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. Adequacy, permanence 13. Quality Temp °F Taste, odor, color Sample Yes No			
11. Yield: Flow G. M., Pump G. M., Meas., Rept. Est Drawdown ft. after hours pumping G. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs Adequacy, permanence 13. Quality Temp °F Taste, odor, color Sample No			
Drawdownft. afterhours pumpingG. M. 12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs Adequacy, permanence 13. Quality Temp°F Taste, odor, color Sample Yes To stee for			
12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. Adequacy, permanence 13. Quality Taste, odor, color Sample Yes No			
Adequacy, permanence			
Taste, odor, color Sample Yes No			
Taste, odor, color Sample No	13. Quality	Temp	•F
Trifft for	Teste odor solor	Sample Yes	
14. Remarks: (Log. Analyses, etc.) 7-18-58- # 4880	nerva se	No	
Lemarke: (Log, Analyses, sto.)	14 Bornelin Gran Colonia Van 7-	18-58- # 4880	
	Lemarks: (Log, Analyses, sto.)		

9-185 (October 1950)

UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

Da Re	te March 19, 1959 cord by P.R.Lord arce of data Copied from La		Office No.
_	Location: State Alaska		
2.	Owner: Civil Aeronautics Tenant W side of fung fr	Address	NR E ST. W
3:	Driller	Address	i i i i i i i i i i i i i i i i i i i
4. 5. 6.	Elevationft. above below	ted12-119 54 , Type	
8.	Chief Aquifer		ft. toft.
9.	Water level 122 ft. rept.	which is	19above below ft. above surface
10:	Pump: TypePower: Kind	Capacity	G. M
11.	Yield: Flow G.M., Pump_	G. M	, Meas., Rept. Est.
12.	Use: Dom., Stock, PS., RR., Ind., Ir Adequacy, permanence	r., Obs.:	
	Quality Taste, odor, color Unfit for	***************************************	Temp°F.
	Remarks: (Log, (Analyses, etc.)	A	4050

9-185 (October 1950)

UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

WELL SCHEDULE		-	一2
Date MARCH 13- 6-	, 19	Field No	
Record by		Office No.	
Source of data Chem ANAL			
1: Location: State ALAS KA	County	SW	
Map			
			E
2. Owner: CAA	Address /	IAMNA	
Tenant	Address		
Driller	Address		
3. Topography			
4. Blevation ft. above below			1
5. Type: Agg drilled driven, bored, jet	tted19		
6. Depth: Rept. 18 ft. Meas			
7. Casing: Diam. 2 in., toi	п., Туре		
Depth 18 ft., Finish			
8. Chief Aquifer		ft. to	ft
Others			
9. Water levelft. rept		19 above	
meas.	which for	ft. abov	efaar
10: Pump: Type			
Power: Kind			
11. Yield: Flow G.M., Pump			
Drawdownft. after			
	10.00	The state of the s	
12. Use: Dom., Stock, PS., RR., Ind., I			
Adequacy, permanence			
13. Quality			
Taste, odor, color		Sample No	
Unfit for			
14. Remarks: (Log Analyses) etc.)	In/ro H	4030	

E. S. GOVERNMENT PRINTING OFFICE 16-62891-

ANALYTICAL NOTES

Focation -	amma Station,	Alaska		Cour	ty Libiam (in.)	2 in
Source18			of coll. sta	Depth (ft)Depth (ft)	Diam (in.)_	
Cased to (ft)	Date drilled	Point	CAÁ	Iliamna		
Treatment			·	Use		
WBF		WL	. 14 ft	Yie	ы 150	
	Appear w.c. Clear					
Collected 7	718/58 V.c. Clear			By W.S. I	Holmes	•
Remark s						
		/	A about the sight the		ppm	/ epm
510	ppm /D'ml i.i.		HCO	.57)_ml	281	еріп
SIO ₂	. /.	2-1	HCO36.60	mı	140	.46
Abon O.D. San	No. 620		5.24	- 1	17.	. 10
0.D. 10.pg	om 420		1.40			
100	ml		1 "			
A1						
Abs.(A1+Fe)		1	CO 3	ml		
Abs.(Fe)					1	
			1		1	
Fe,		2.7				
Abs /p	pir -300		ОН	2.4		
MI stdo. D.	ret .015		1011	ml		
Fe,						
Abs		_	1		/	
MI std	-	1			/	
MI BIG			so de	District ISEMI	0.0 10	.00
4.	ml	1	0.00	-0316		.00
Mn,			0. X	03/	1	
Abs.	_		1 2	0.00	1	
MI std			0.03	0.	/	
57.0	ml		C11.20	, 50 ml	_5,0°	.14
				/		,11
			0.60			
			0.50) i	1	
						7
	ml		F		0.00	.001
			1	4.00		
	1.57		MI std			
CHARLES TO SERVICE TO		. / /		- United to the Control of the Contr		
Ca 4.60	Si_mlGi	432		ml		
3.80			1			
0.80			1			
200		1			I	
N- 125		11 .71		ml		
Mg 6.35 5.10		.171	H ID			*:
6.25						
1.22		1		WT	1	
		1				/
4			NO ₃	<u>\$5</u> ml	0.2	:00 /
±0	ml		3			.00
			MI and	D. Stary. OGS		
-			MI STO_C	D 100m.300		
				ml		
	—ml		(A)			
-						
Lab. No. Col- 4	879	Field No			R No.	
	The second secon			USE		

	. ppm	epm		ppm	epm
la 10 pp		.11		m1	
Samp Sp	pm 34.0	/: /			
	Reading Avg	.00		mt	
	ple 40		F/	128°°	
	—_m!	1	2	ml	-
		-			
	mt	1	() ±		
otal c	ations	.65 /	Total anions	•	.60 -
otal i	ons, epm 1.20 / Differe	nce, epm	,00 / Pe	rcent difference	0.0 -
		ррт			
	ž.	19 4	Specific Conductance (micromhos at 25° C) R KC1 R S	. 5330	
			RKCI KS	omple	62
			рН	ample	5.5
				ample	
	Um	45 /	рН	omple	<u>5</u> ,5
	Residue on evop. at 180° C	45/	рН	omple	<u>5</u> ,5
Dissolved Solids	Residue on evop. at 180° C	45/	рН	By	<u>5</u> ,5
Dissolved Solids	Residue on evop. at 180° C	45.1	рН		<u>5</u> .5
Dissolved Solids	Residue on evop. at 180° C		pH Color	Ву	<u>5</u> .5
ardness as CaCO ₃ Dissolved Solids	Residue on evap. at 180° C	24/	PH Color	By	5.5 0 Date
ardness as CaCO ₃ Dissolved Solids	Residue on evop. at 180° C	24/	PH Color Analyzed Calc. checked	By	5.5 0 Date
ardness as CaCO ₃ Dissolved Solids	Residue on evap. at 180° C	24/	Analyzed Calc. checked Reviewed	By ESEO. SUB SUB	Date 8/5/5 8-18-58 8/26/5

9-185 (October 1950)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY WATER RESOURCES DIVISION

WELL SCHEDULE		Hearn ?	
Record by William		_ Office No	
Source of data OB Hudson	Deanes		
1: Location: State			
Map	-		772
2. Owner: FAA - at axis	pour Address		
Tenant	Address		
Driller	Address		
3. Topography			
4. Elevationft. above		.	\vdash
5. Type: Dug, drilled, driven, bore			
6. Depth: Rept. 70 3 ft. 1	Measft.		11
7. Casing: Diamin., to	in., Type		1-1
Depthft., Finish			
8. Chief Aguifer	From	ft. to	ft.
Others		<u> </u>	
9. Water levelft. rej	pt.	19above_	
me	which is	ft abo	ve surface
10: Pump: Type			
Power: Kind	Hor	epower	
11. Yield: Flow G.M., F	rump G.M	Meas Rept. Es	ıt
Drawdownft. after			
12. Use: Dom., Stock, PS., RR., I			
Adequacy, permanence			
13. Quality			
Taste, odor, color		Sample Yes	
Unfit for		No -	VERNOR
warks: (Log, Analyses, etc.	Walit D	n in 196	/
thog, Analyses, etc.	J JANES BARRELLE	Acces of the Second control of	
L			,

> 1	1 :		1000	0100000	1) 2) 2-		:	ž.	,		
•			e ,			•		5 4			¥ *
S'm/	22	į.	25.m								. 1
1. Sta.	0.D. Sample . 36c	٠ (/ Poin Std. /8/ 3.D. Std. /8/	10,70		TONS, PER ACRE-FOOT					· · · · · · · · · · · · · · · · · · ·
•	1	<u> </u>	7 71	7		179 1	1/1	1/1	00000		
na, Alaska	/ (5	707)7a	K . 0.	CO ₃ C	r	60/201	3.95	\$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	Color	Hq
TIAL ANALYSIS NOTES 11ed Well, Illamna, th: 61' Station	(Mi	5° 1.7° . 1≡52.	5.5: m.	1	00 ml. 40 siere	zómi.	5€ m1.	- i	.□°.	Total +4 V	AMERY PRINTING OFFICE 16-67
PARTIAL Depth: CAA Sta	oonduote 3 4 8		7,80	810.)	HCO	18 18 18	.k. Smg. AgNO,)s / /s /</td <td>Sample .do</td> <td>Lab. No. 76 570</td>	Sample .do	Lab. No. 76 570
Cot. 1943) Lab. No.	pecifi R KCL	සු	Mg	Na+K(calo.)	°CO	20%	임 ',	Es.	ro I	O.D. Sam Hardness	ab. No
. 81 4	ίΩ.		۷-	· - ٤ ·		ysinys	- 5.52	118	7	USFA	1

9-185 (October 1960)

UNITED STATES


DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

Rec	ord by		Office No.
Воц	roe of data, Chen ANAL;	i and the	and the same of th
	Location: State ALASKA "	County	SE LEBENT USE
1 .	Map	T	NH lolo, 1
2.	Owner: BIA	Address	4.1.4.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1
72.77	Driller	Address	
	Topography above		
	Elevationft. above below		19 July 20 1
	Type: Dug, drilled, driven, bored, jett		
	Depth: Reptft. Meas.	The state of the s	S SELENTHE .
7.	Casing: Diamin., toin Depthft., Finish		
8.	Chief Aquifer		
9.	Water levelft. rept	1	9above
		which is	ft. above surface
10	Pump: Type		
	Power: Kind		
11.	Yield: Flow G.M., Pump _		
	Drawdownft. after	hours pumpir	gG. M
12.	Use: Dom., Stock, PS., RR., Ind., Ir. Adequacy, permanence	r., Obs	
13.	Quality		
	Taste, odor, color		Sample Yes
	TI-CLC-		
	Unfit for		
14.	Remarks: (Log, Knalyses, etc.) # 7	022 - MAY 7	762

	EK - Samestyles at		HAB NU.	1011
County : SUREAU OF	Than AFFAIRS PC.NO		IL DATA	
Sample No.:	Legion	· Ty	pe :	Drilled:
Inv.		De	pth : Ft.	Dia. : In.
W.O.No. :	The second second of	Ca	sed : Ft.	Perf.
GW Basin :	Tollers i section of	Gr	avel packed:	
Loc. : NEW A	HALEN, ALASKA	Us	e :	
		Ow	ner :	****
		Re	marks 2	right.
Samp. Pt. :		, av.	A red rate with both many water	
17			CALCIUM 50 -ml	MAGNESIUM
Pumptime :	Disch.		at a second of the second of the second	Advance (Cat.
remp. :	F. <u>Coll</u> .	27 MAY 1962	1.20 ml	epm TH <u>A.6.4</u>
Agency :	Lil	PST	2 V 1.4	epm Ca 0.48
Remarks :		****	9 rbs 234018	epm Mg Del6
SILICA_/0ml	IRON (dis) 25 mi	RON(total)ml	1 1/4	¢A ² e
1 Ata 1.11	A_//6 Tmg 0.0/		F. 20 FPM	
			Ca ppm : 2 9.6	Mg ppm 49
	a the state of the sale of the	00.01	п) тентина 1.к.	LINITY
Asample 46.0	Asample 2.0	Asample	HCO 32	- Co
	and property of the same of the same		HCO ₃ 48	2_ml 3
SiOn nom 10	Fa 35- 4 49	- and [2.10-ml	A STANDER
SiO ₂ ppm /0		e_ppm	The same of the sa	30 ² • 2
SODIUM	dii POTASSIUI	Ndil	Taken	proper.
	%T Sample 3	<i>5</i> %T	इंट्र में विस्तित	574 F
Curve LIO PPM	Sumple X	0.128	men in the same transfer this per designation and other de-	
Na ppm	8.6 K ppm	0.4	TOTAL-ALKALINITY	ds C03_24
			as HCO3 48	as CaCO3 39
SULFATE	ml CHLORIDE 50" ml	FLUORIDE 10 ml		
0.15-8=0.10	I ml = 0.5 mg Cl		NITRATE 25_ml	BORONml
	0.70-8=0.60ml		ml Ag2504	
201 (42)		Corr. mt -6.5	A 9.0 mg0.0/	A
		X-0.025		Amg
28	1	X-0.020	Factor 0.044	Factor
it i		mg Std 0-0/	Asample 6.0	A sample
	100 110			
00		C [A d	NO 42	
SO4 ppm 2.0		F ppm 0.2	NO ₃ ppm 0.3	R bbw
SUM 6.3	HARDNESS 50 ml	%Na 36	pH epm .	epm.
	as cacux		0.48	ca _ 0.77 co ₃
T/A ft	160 ml	PECIFIC	6.1	
DISSOLVED		ONDUCTANCE	0.76	MgHCO3
SOLIDSml	1	1401 2/1	COLOR	0.04 50
		(KCI) 34/	20	0.04 SO4
		Sample 3430	1.27	No 0./7 CI
	. [1	sample 2730	TURB	V V
1 69	£ ;	₹	0.01	K 0.01. F
ge B	Total 32	· 40 1		
		**** E S	% E	0.00 NO3
la se se a constitue de la con	HCO3(0-82) 39 N	licromhos	Transmitter of the state of the	
D.S. ppm		t 25°C 99-	10.5 1.02	1.01
PP.		20 0 [//	Sum	Sum
) <u>).</u> C			D +0.01	· 6. Transmanner
ľ		4616 6 6 4	11156 ft. 11156 ft. 11156	signes4
			Σ.2.03	
		14.1007 (_ mcd	. 10*76*
E	Jan 141 4	eranosati barat afilia Tata Taka Pa ^T idi bi Tib ^A land (1987)		¥ # # .
	T40			
I . X	0	2	7 P	
	h*,	8		e e e e e e e e e e e e e e e e e e e
			1 362	
Palmer 1958	GPO STERES DATE ST	ARTED MAY 14	1962 CHEMIST E	EL .


22 ALUMINUM COPPER ____ mg__ Appar.Al ___ Asample. Fe-X .12-Asample _ Factor Mn X .04-Acolor F X.05+ Acort. Cu ppm LEAD _mg__ Asample _ MANGANESE (qual.) Factor Pb ppm ZINC 1 22 1 Asomple Asample -Zn ppm ARSENIC : Asample Asample . יה שונה שונים: A Treese Asample_ Asample_ Factor ATE SU DATE COMPLETED WAS CHECKED BEST



Water level (pumping, static) 35 ft.
:above,:below
Sampled after 60 HR
Yield 60 G.M. Flow POMP
Point of collection DISCHARG
Appearance (Clear, colored, turbid, sediment, etc.)
Temperature 36 Degrees F.
Circle Use
Dom, Public Supply, Stock, Irr., Ind., RR,
Air Cond., Bottling, Condensing
Collected by Roy F. LONG-BOTHAM
/
Remarks

LEAVE A LITTLE AIR SPACE IN BOTTLE

USBIAZ



MSBAAD

THIS WELL WAS STARTED BY JOHNSON & CO. AND DRICK. TO A DEPTH OF 225! THE DRICKERS STARTED AT WELL LOG

THIS DEPTH. U.S. PUBLIC HEALTH SERVICE, DIVISION OF INDIAN HEALTH

LOCATION NEWHALEN, ALASKA	DATE STARTED
DATE COMPLETED 8/27/84	DRILLER BOB 4000 / JOHN MILLER
TOTAL DEPTH OF WELL 405 FT.	CASING INSTALLED OPEN HOLE DIAMETER. 6"
GROUT 15' TOC SCREEN SIZE	N/A MFG. N/A LENGTH N/A
STATIC WATER LEVEL 14 FT. H	RS. PUMPED 24 @ 7 GPM DRAWDOWN 97' FT.
HOLE DIAMETER	
DEPTH CASING DIAMETER	
AT TH	SOIL DATA TO 15 FT.
225 ///	MIZET SIPPEDIEE I HAWED
V///	BOTTOM OF FROST & MATERIAL
HARD	SEASONAL OR PERMA FROST
1//	
1///	
BLACK.	WATER DATA FIELD TEST
	TASTE GOOD
// ROCK	APPEARANCE FRESH VES
// KOCK	IRON
1//	CHLORIDES.
	TDS
	and the second second
	AT 267, THE WELL WAS TEST PUMPEL
	AT 267, THE WELL WAS TEST PUMPET AND PROPULED 31/2 GPM - THIS WINSUFFICIENT SO THEY DRILLED
	PUMPING LEVEL /// 3" 0 7 GPM
	PUMPING LEVEL 777 5 GPM
	AFTER 24 HRS.
1///	AT 368, THE WELL PRODUCED 4 6pm
342 HORD	A. 366, THE MEET (
DARK-GA	EEN .
ANN ROCK	HIGHEST RECOMMENDED PUMP RATE 7 GPM
	WILL STATIC LEVEL CHANGE WITH
373	TIDES NO OR FROST NO
HORD	
1// BLACK	THIS WELL WAS DEEDELIED TO
1/1/ ROCK	OF THE PREVIOUS 5 GPM WAS DUE TO,
1//	SURFACE WATER RUNNING DOWN THE OUTSIDE
405	OF WELL IT HAS SENED OF LEMANS 3 GAM.
DEVELOP PROCEDURE	OF WELL IT HAS SENED OF LEWING 3 GOM.
ESTIMATED MAN HOURS FOR DRILLING	HOURS FOR TOTAL JOB
	1
REW ROBT HOPD	/ PINK MILLER USPHS&

completed 10/82 Then Harles Test Well By Johnson Drilling Co. King Salmon 6" Cosing - Static keel 15 (overnight) 17' Graves Open horehole 20 22 24 25 30 31 32 200' 35 37 39

CHEMICAL & GEOLOGICAL LABORATORIES OF ALASKA, INC.




TELEPHONE (907)-279-4014 ANCHORAGE INDUSTRIAL CENTER 5633 B Street



Drinking Water Analysis Report for Inorganic, Organic, and Radiochemical Contaminants

		UB	ECU	MPL	- 150	DIFUD	LIC WA	EN SUP	ruun				
PUBLIC WATER SY	STEM:						SAME	LE DE	SCRIPTIO	N:			
							Collected By James Appleton						
I.D. NO. Alaska Area Na	tima Ha	111	Set	rvic	е		Explanatory Well						
Public Water System Name	itive ne					-	Sample Location						
701 C. Street,	Pov 65												
Address	DOX 03	-					Source T	ype 🗆	Surface Water	☑ Gro	und Water		
UNAMED AND STREET	Alaska			99	513					ГТ			
Anchorage City	Stat				Cod	ā	Sample	Date		0	4 8 2		
City	Otal			210	000	50			Mo.	Day			
Note: Check box to left of	ted b	elow	8		tine Sar		VIII.	treated Water					
analyses desired.	00111						☐ Special Purpose Sample ☐ Treated Water						
									-				
		го в	E CO	MPL	ETED	BY CEF	TIFIED L	ABORA	TORY				
895				27.3.5 <i>2</i> 7 (1.1111)		1000 A							
CHEMICAL & GEOLOG	ICAL LAB	ORA	TOR	ES C	FAL	ASKA, I	NC.						
Laboratory Name						-	Sample I	No.		Station No.			
5633 "B" STREET								929					
Address						-		ry Analys	is No.				
ANCHORAGE,	AT	ASK	A		99502	2	DB			Novem	ber 5, 1982		
City		tate			ip Cod		Received	by			Date		
									OB	GANICS			
									Oli		Mg/I		
INO	RGANICS						. [Endrin		Limit (0.0002)			
				War.				Lindar		(0.0002)	H		
	Limit		Mg	/1					xychlor	(0.004)	14111		
☐ Arsenic	(0.05)<		0 1	П					hene	(0.005)			
☐ Barium	(1.)<		5					2, 4-D		(0.1)	HHHH		
☐ Cadmium	(0.010)<	0.	0 1	0	Ц				TP Silvex	(0.01)			
☐ Chromium	(0.05)<	0 .	0 5		Н			ı					
☐ Fluoride	(2.4)<	0	. 1	0	Н.								
□ Iron	(0.3)	QU.	A F	111	1						A TOTAL TOTAL CONTROL OF THE STATE OF THE ST		
□ Lead	(0.05)<	0		5	H				RADIO	DACTIVIT	Y		
☐ Manganese ☐ Mercury	(0.05)<		0 0		H				IIADI		100000		
□ Nitrate - Nitrogen		+	0 .	3 0	H		_		Alaba	Limit	POM		
□ Selenium	(0.01)<		01	1310	H			Gross	m 226 & 228	(15)	HHHH		
□ Silver	(0.05)<		0 5		\vdash			Gross		(5) (50)	HHHH		
☐ Sodium	(250)	1	1	. 4	П		177		ium - 90	(8)	HHHH		
	The second secon						-	Tritiun		(20,000)			
							č	The second secon					
							Ē						
ND Indicat	es Not Dete	cted			2			,		2.5			
November 1	1, 1982				S	terner	C.	Ede			11-11-82		
Date Analysis Completed				Sign		-11	ory Super	risor	LLSPI	ds i	Date reported		



CHEMICAL & GEOLOGICAL LABORATORIES OF ALASKA, INC.

TELEPHONE (907)-279-4014 ANCHORAGE INDUSTRIAL CENTER 274-3364 5633 B Street



ANALYTICAL REPORT

[]K,Potassium 1 []Kjedahl []H Units 5.4 []Mg,Magnesium 0.34 []Nitrate-N 0.30 []Turbidity NTU []Mn,Manganese <0.005 []Nitrite-N []Color Units []Mo,Molybdenum <0.05 []Phosphorus []T.Coliform/100ml (Ortho)-P <1 []Chloride <1 []	1 []Kjedahl []pH Units []pH Units	1 []Kjedahl []pH Units	1 []Kjedahl []pH Units		ury<0.001		[]Cu,Copper<0.05 []Zn,Zinc<0.05 []	[]Cr,Chromium<0.05 []V,Vanadium<0.05 []	[]Co,Cobalt<0.05	[]Cd.Cadmium<0.01 []Ti,Titanium<0.05 []Alkalinity as9		[]Bi,Bismuth<0.05 []Sn,Tin<0.10 []Volatile Sus	[]Ba,Barium<0.5	[]B,Boron <0.05 []Se,Selenium <0.01 []Total Volatile	[]Au,Gold<0.05 []Sb,Antimony<0.10 []Total Dissolved16	[]As,Arsenic	[]A1,Aluminum0.40 []Pb,Lead<0.05 []Sulfate1.5	[]Ag,Silver<0.05 []P,Phosphorous<0.05 []Cyanide	-		with low buffering capacity and low ph will be DATE	STIGHT SOURCE EXPLANATORY WELL DAIL KELLIVED MOVEMBER 3,	KECAN BI THE COULECTED: KECAN BI	11-4-82 TIME COLLECTED. SWIFTE LOCALION. FOR LAB USE ONLY	Alaska Area Native Health Service SAMPIF IOCATION: Newhalen,	Newhalen, Alaska FOR LAB USE ONL RECVD.BY DB LAB # DATE RECEIVED November 5 DATE REPORTED November 1 SIGNED OF PARA O. I]Cyanide []Sulfate []Phenol []Total Dissolved Solids []Suspended Solids []Wolatile Suspended Solids []Hardness as CacO3 CacO3 []Alkalinity as CacO3 [] [] [] [] [] [] [] [] [] [OLLECTED: Dlanatory Well Extremely soft and low ph will ed untreated. Phosphorous Phosphorous Phosphorous Antimony t,Platinum t,Platinum t,Platinum i,Silicon i,Silicon i,Titanium vanadium Vanadium Vanadium Vanadium T,Zirconium T,Zirconium T,Zirconium			CUSTOMEP Alaska DATE COLLECTED_ SAMPLED BY James REMARKS Slightly with low excessiver
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------	------------------------	------------------------	--	-----------	--	------------------------------------	-----------------------------------------	------------------	-------------------------------------------------------	--	------------------------------------------------	-----------------	------------------------------------------------------	-------------------------------------------------------	--------------	-----------------------------------------------	-------------------------------------------------	---	--	-----------------------------------------------------	----------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------	--------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--	---------------------------------------------------------------------------------------



Date Analysis Completed

CHEMICAL & GEOLOGICAL LABORATORIES OF ALASKA, INC.

TELEPHONE (907) 562-2343

ANCHORAGE INDUSTRIAL CENTER 5633 B Street



Date reported

USPHS

Drinking Water Analysis Report for Inorganic, Organic, and Radiochemical Contaminants

anic, Organic, and Radiochemical Contamina

TO BE COMPLETED BY P	UBLIC WATER SUPPLIER
PUBLIC WATER SYSTEM:	SAMPLE DESCRIPTION:
	Collected By B. Hopp
Alaska Area Native Health Service	Hendricks 400' Well Newhalon, Alaska
Public Water System Name	Sample Location
701 C Street, Box 65	Source Type Surface Water Ground Water
Anchorage, Alaska 99513	Sample Date 0 8 0 8 8 4
City State Zip Code	Mo. Day Year
Note: Check box to left of contaminants listed below for the analyses desired.	☐ Routine Sample ☐ Untreated Water ☐ Special Purpose Sample ☐ Treated Water
TO BE COMPLETED BY C	CERTIFIED LABORATORY
CHEMICAL & GEOLOGICAL LABORATORIES OF ALASKA	A, INC.
Laboratory Name	Sample No. Station No.
5633 "B" STREET	6168
Address	Laboratory Analysis No.
ANCHORAGE, ALASKA 99502	GY - 8/8/84
City State Zip Code	Received by Date
	ORGANICS
	Limit Mg/I
INORGANICS	☐ Endrin (0.0002)
Limit Mg/I	☐ Lindane (0.004)
	☐ Methoxychlor (0.1)
□ Arsenic (0.05) 0 . 0 0 5 □ Barium (1.) < 0 . 0 5 □	☐ Toxaphene (0.005)
□ Cadmium (0.010) < 0 . 0 0 2	□ 2, 4-D (0.1) (0.1)
□ Chromium (0.05) < 0 . 0 1	□ 2,4,5 - TP Silvex (0.01)
□ Fluoride (2.4) 0 . 2 4	
□ Lead (0.05) < 0 . 0 1	
□ Mercury (0.002) < 0 . 0 0 0 2	
☐ Nitrate - Nitrogen (10.) ☐ 0 . 1 0	RADIOACTIVITY
☐ Selenium (0.01) < 0 . 0 0 1	Limit pCi/I
□ Silver (0.05) < 0 . 0 1	☐ Gross Alpha (15)
☐ Turbidity (1 NTU) 1 3	☐ Radium 226 & 228 (5)
g ————————————————————————————————————	☐ Gross Beta (50)
	☐ Strontium - 90 (8)
	☐ Tritium (20,000)
August 14, 1984	hen C. Ede August 14, 198

Signature of Laboratory Supervisor



CHEMICAL & GEOLOGICAL LABORATORIES OF ALASKA, INC.

TELEPHONE (907) 562-2343

ANCHORAGE INDUSTRIAL CENTER 5633 B Street



ANALYTICAL REPORT

CUSTOMERALASKA	Area Native He	SAMP	LE LOCATION:	New Halen, Alaska
	7-21-84 TI	ME COLLECTED:		RECVD.BY GY LAB # 6168
SAMPLED BY B.	Hopp Source	Hendricks Well		DATE RECEIVED August 8, 1984
REMARKS Soft an	d potentially o	orrosive water with	h high Iron	DATE COMPLETED August 14, 1984
and high pH				DATE REPORTED August 14, 1984
	10 (10 K) 10 (10 K)			SIGNED Stephen C. Eds
	mg/l		mg/l	mg/l
[]Ag,Silver	<0.05	[]P,Phosphorous_	<0.05	[]Cyanide
[]Al,Aluminum	0.43	[]Pb,Lead	<0.05	_ []Sulfate4.2
[]As,Arsenic	<0.05	.[]Pt,Platinum	<0.05	[]Pheno1
[]Au,Gold	<0.05	[]Sb,Antimony	<0.05	_ []Total Dissolved55
[]B,Boron	<0.05	[]Se,Selenium	<0.05	Solids _ []Total Volatile
[]Ba,Barium	<0.05	.[]Si,Silicon	7.1	Solids []Suspended
[]Bi,Bismuth	<0.05	[]Sn,Tin	<0.05	Solids _ []Volatile Sus
[]Ca,Calcium	3.8	.[]Sr,Strontium	<0.05	pended Solids 11 []Hardness as
[]Cd,Cadmium	<0.01	.[]Ti,Titanium	<0.05	CaCO ₃ _ []Alkalinity as35
[]Co,Cobalt	<0.05	[]W,Tungsten	<1.0	CaCO ₃
[]Cr,Chromium	<0.05	[]V,Vanadium	<0.05	_ []
[]Cu,Copper	<0.05	[]Zn,Zinc	0.12	_ []
[]Fe,Iron	1.1	.[]Zr,Zirconium	<0.05	_ []
[]Hg,Mercury	<0.05	.[]Ammonia		_ []umhos Conductivity*95
[]K,Potassium	4	Nitrogen-N []Kjedahl		_ []pH Units8.4
[]Mg,Magnesium	0.40	Nitrogen-N []Nitrate-N		_ []Turbidity NTU
[]Mn,Manganese	<0.05	.[]Nitrite-N		_ []Color Units
[]Mo,Molybdenum_	<0.05	. []Phosphorus		[].Coliform/100ml
[]Na,Sodium	15	(Ortho)-P []Chloride	4.0	- []
[]Ni,Nickel	<0.05	[]Fluoride		- []
				(人 ろとは)